

# Gas Engine Pressure Washers

**Direct Drive Design - No Need for Belts or Guards.  
Pumps Bolt Directly to the Honda Engines  
- 2 Wheel Carts -**



**PMC-SF35C**  
(Aluminum 2 Wheel Cart)  
2.5 GPM @ 2700 PSI



**PM5500G**  
(Aluminum 2 Wheel Cart)  
4.0 GPM @ 4200 PSI



**PM2565C**  
(Powder-Coat 2 Wheel Cart)  
3.0 GPM @ 2500 PSI

**Standard Features Include:** Triplex Plunger Pumps • Honda Engine • Adjustable pressure regulators • Trigger style shut-off wands  
• Chemical injectors • 25' or 50' hose assemblies as noted • Pneumatic tires • Aircraft grade aluminum or powder-coated frames as noted.



**PM9000G**  
(Powder-Coat 2 Wheel Cart)  
4.0 GPM @ 4000 PSI



**PMC-3228**  
(Aluminum Skid Frame)  
2.5 GPM @ 3400 PSI



**PMC-950H**  
(2 Wheel Cart)  
3.5 GPM @ 3800 PSI

<b>Wheeled Models</b>						
<b>Part No.</b>	<b>Flow GPM</b>	<b>PSI</b>	<b>Pump</b>	<b>Engine</b>	<b>Frame</b>	<b>Wt</b>
<b>BI PMC-SF35C</b>	2.5	2700	AR	GC190 Rope	Aluminum	95 lbs.
<b>DU PMC-3228</b>	2.5	3500	CAT	GX200 Rope	Aluminum	90 lbs.
<b>BI PM2565C</b>	3.0	2700	COMET	GX200 Rope	Powder-Coat	95 lbs.
<b>BI PMC-950H</b>	3.5	3800	AR	GX270 Rope	Powder-Coat	125 lbs.
<b>DU PM5500G</b>	4.0	4200	CAT	GX390 Rope	Aluminum	145 lbs.
<b>DU PM9000G</b>	4.0	4000	GP	GX390 Rope	Powder-Coat	175 lbs.