

E0052 Injection Pumps • Pump/Tank Systems

Blue-White Industries, Ltd. Injection Pumps



Adjustment Dial

Blue-White Diaphragm Metering Pumps. Ideal for dispensing a precise and wide variety of solutions.)

Blue-White Industries, Ltd.

C1500N Series

Standard Features include the following:

- Weather-resistant housing for indoor or outdoor use
- Easy to adjust feed rate; you always know exactly what your injection rate is
- PVDF (Kynar) Pump heads
- Double-sealed PVDF cartridge fittings
- Pressures to 125 psi (70 PSI on 10 oz. and Larger)
- Chemically resistant internals
- Anti-siphon check valve and foot valve strainer
- ETL Listed
- Can be wall or shelf mounted
- Viton® O-ring & Teflon/EP Diaphragm
- 115 or 24 Volt (230 volt also available)
- Minimum output is 5% of maximum shown
- Dimensions: 9-1/16" H x 4-1/2" W x 5-3/4" D
- Maximum fluid temperature is 130° F. **Includes 3/8" OD suction and discharge tubing, flow indicator and mounting hardware.**

Part No.	Max. Oz.		Wt.
	Per Minute	Voltage	
BL C15N202X06	1.00	115	9 lbs.
BL C15N302X06	1.49	115	9 lbs.
BL C15N202X	2.40	115	9 lbs.
BL C15N302X	2.70	115	9 lbs.
BL C15N402X	6.10	115	9 lbs.
BL C15N404X	† 10.15	115	9 lbs.
BL C15N232A06	1.00	24	9 lbs.
BL C15N332A06	1.49	24	9 lbs.
BL C15N232A	2.40	24	9 lbs.
BL C15N332A	2.70	24	9 lbs.
BL C15N432A	6.10	24	9 lbs.

† Maximum of 70 PSI.

Part No.	Replacement Parts for C1500N Pumps
BL K568-6E	Bullet Valve Kit with 3/8" OD Top & Bottom Fitting & "EP" Seal, Pack of 2.....
BL K568-6A	Bullet Valve Kit with 3/8" OD top & Bottom Fitting & Viton® Seal, Pack of 2.....
BL C-406VT-15N	Diaphragm Assembly, "Viton®"
BL C-406T-15N	Diaphragm Assembly, "EPDM"
BL C-340A	Foot Valve "Viton®"
BL C-340E	Foot Valve "EPDM"
BL A-014PHD-6V	Anti-Siphon Valve for 3/8" OD Tubing, "Viton®" ..
BL C-535A6-6E	Complete Liquid End - "EPDM"
BL C-535A6-6	Complete Liquid End - "Viton®"



Great Response from Company Rep . . .
 "Great response from company rep. Quick shipping and a fair price. Hope to do business with you again."

Randy

Viton® is a registered trademark of DuPont Performance Elastomers



XP Pumps

XP Pumps from Cat Pumps are an ideal choice for carpet extractors, Misting/cooling, hydrostatic testing and truck mount applications. Patented, greaseless design for added life, serviceability and performance.

Pump and Motor Combinations are rated from 0.5 to 2.0 GPM and 100 to 800 PSI. Standard motors are 1/3, 1/2 or 3/4 HP, single phase, 120/240 volt. Pumps feature ceramic plungers, stainless valves, Viton® seals and aluminum housings. Easy drain out feature is also standard.



Part No.	GPM	PSI	HP	Wt.
CC 1XP050.031	0.50	800	1/3	25 lbs.
CC 1XP075.031	0.75	650	1/3	25 lbs.
CC 1XP085.031	0.85	600	1/3	25 lbs.
CC 1XP100.031	1.00	500	1/3	25 lbs.
CC 1XP125.031	1.25	400	1/3	25 lbs.
CC 1XP150.031	1.50	325	1/3	25 lbs.
CC 1XP200.031	2.00	250	1/3	25 lbs.
CC 1XP085.051	0.85	800	1/2	30 lbs.
CC 1XP100.051	1.00	800	1/2	30 lbs.
CC 1XP125.051	1.25	600	1/2	30 lbs.
CC 1XP150.051	1.50	500	1/2	30 lbs.
CC 1XP200.051	2.00	400h	1/2	30 lbs.
CC 1XP125.071	1.25	800	3/4	35 lbs.
CC 1XP150.071	1.50	700	3/4	35 lbs.
CC 1XP200.071	2.00	500	3/4	35 lbs.
CC 7085	Unloader, .5 - 6.5 GPM & 1000 PSI			1 lbs.

Call Toll Free For Prices

Visit our office in Omaha, Nebraska



13808 Industrial Road • Omaha, NE 68137
 1-800-228-9666 • 1-402-333-1444 • FAX: 1-402-333-5546

Visit our office in Davenport, Iowa



601 West 76th St. • Davenport, IA 52806
 1-800-553-6975 • 1-563-386-0930 • FAX: 1-563-386-5448

email: dultmeier@dultmeier.com • website: dultmeier.com