

**Plunger Pumps** from PumpTec can be used in a wide variety of spraying applications including: Carpet Cleaning, Agriculture, Pest Control, Turf Spraying, Misting and Reverse Osmosis Systems. Available with 12V, 120V or 230 volt motors. Sold in pump/motor combinations or as replacement pumps. Regulators, repair kits and misting nozzles are also available.

## PUMPTEC Model 112



**112 Pumps** feature aluminum bodies with SS/Acetal valves, stainless plungers and Buna or Viton® seals. Rated to 250 PSI and 140° F. Ports are 1/4" FPT inlet and outlet.

112 Series

Part No.	Volts	GPM Flow	Maximum PSI	Amp Draw	Seals	Wt.
PX 112V-M35	120V	.67	200	1.2	Buna	10 lbs.
PX 80056	120V	.89	200	1.4	Buna	10 lbs.
PX 112-075	12V	1.0	200	15	Viton®	10 lbs.
PX 112T	Pump Only	1.4	250	-	Viton®	3 lbs.
PX 112V	Pump Only	1.4	250	-	Buna	3 lbs.

## PUMPTEC Model 113

**113 Pumps** feature aluminum bodies with stainless plungers and valves. Seals and o-rings are Buna. Rated to 1000 PSI and 140° F. Ports are 1/4" FPT inlet and outlet.



113 Series

Part No.	Volts	GPM Flow	Maximum PSI	Amp Draw	Seals	Wt.
PX 113VM-075/M15	12V	.20	800	15	Buna	11 lbs.

## PUMPTEC Model 114

114 Series




**114 Pumps** feature plastic bodies with Acetal valves, stainless plungers and Buna or Viton® seals. Rated to 200 PSI and 140° F. Inlet ports are 1/2" hose barb, 3/8" MPT. Outlet ports are 1/4" MPT.

Part No.	Volts	GPM Flow	Maximum PSI	Amp Draw	Seals	Wt.
PX 114T-M35	120V	.89	200	1.4	Buna	10 lbs.
PX 114T-075/M15	12V	1.50	250	15	Viton®	10 lbs.
PX 114T	Pump Only	1.50	200	-	Viton®	2.5 lbs.

## PUMPTEC Model 205V / 207V

**205 & 207 Pump and Motor Units.** 205V has maximum flows to 2.1 GPM and maximum pressure of 800 PSI. 207V has maximum flows to 1.47 GPM and maximum pressure of 800 PSI.

**Pumps Feature:** Aluminum bodies with stainless plungers and Buna seals • Rated to 140° F. • 3/8" FPT ports. Different cams and flow rates are available in all models in addition to models shown.



Part No.	Volts	GPM	PSI	Wt.
PX 207V-085/M92	120V	.750	@ 500	30 lbs.
PX 81293	* 120V	.800	@ 500	29 lbs.
PX 205V-125/M77	120V	1.20	@ 400	30 lbs.
PX 205V	Pump Only	2.13	@ 100	5 lbs.
PX 60062	207V Pump Only	1.27	@ 100	5 lbs.

\* Series 205V-085

## PUMPTEC Model 350U



**350U Pumps** feature aluminum bodies with stainless steel plungers and valves. Seals are Viton® or Buna. Rated to 1000 PSI and 140° F. Ports are 3/8" FPT inlet and outlet.

Part No.	Volts	GPM Flow	Maximum PSI	Amp Draw	Seals	Wt.
PX 80483	120V	1.50	1000	11.5	Viton®	30 lbs.
PX 81161	12V	3.00	150	28.5	Viton®	28 lbs.
PX 60074	Pump Only	2.83	1000	-	Viton®	5 lbs.

## PUMPTEC Model 356U

**356U Pumps** feature aluminum bodies with stainless steel plungers and valves. Seals are Viton® or Buna. Rated to 1200 PSI and 140° F. Ports are 3/8" FPT inlet and outlet.



Part No.	Volts	GPM Flow	Maximum PSI	Amp Draw	Seals	Wt.
PX 356-M96	12V	2.50/2.0	250/450	44/66	Viton®	47 lbs.
PX 356U	Pump Only	2.9	1000	-	Buna	6.5 lbs.

## PUMPTEC X Series



81518

**New X-Series Pumps from Pumptec.** Four plunger design provides high flows at medium pressure. Ideal for use as a fill pump and a wash down pump as well as other applications. Rated from 85 to 160 PSI and 3.4 to 6.4 GPM. Aluminum head with Viton® seals and ceramic plungers.

Part No.	Volts	Max. Flow	Maximum PSI	Amp Draw	Seals	Wt.
PX 81518	12V	6.4	160	30-70	Viton®	30 lbs.
PX 81526	110V	5.4	110	7.2	Viton®	35 lbs.

## PUMPTEC REPAIR KITS

Part No.	Kit Description
PX 112KITA	Plunger/Seal Kit, 112/114, Buna .....
PX 112KITA-V	Plunger/Seal Kit, 112/114, Viton® .....
PX 10034	Plunger/Seal Kit, 113, Buna .....
PX 204KITA	Plunger/Seal Kit, 205/207, Buna .....
PX 348KITA	Plunger/Seal Kit, 348U, 350U .....
PX 10007	Plunger/Seal Kit, 356U, Buna .....
PX 10004	M Valve Kit, 112/113/348/356, Buna .....
PX 10014	U Valve Kit, 114, , Buna .....
PX 10020	G Valve Kit, 114, Viton® .....
PX 10022	M Valve Kit, 205V/207, Buna .....
PX 10008	S Valve Kit, 212, Viton® .....
PX 10004	S Valve Kit, 348/356, Buna .....

Viton® is a registered trademark of DuPont Performance Elastomers