



Trigger Guns

Ideal for Car & Truck Wash Applications



YRL20



YG5000
DG4000

General Trigger Wands feature contour design and smooth trigger pull. Ideal for use in car and truck wash applications as well as for pressure washing and general high pressure cleaning. Inlet ports are 3/8" FPT. Discharge ports are 1/4" FPT. Maximum temperatures to 300° F.

DGE and YG Series guns are "Rear Entry" design. **YRL20** is a "Front Entry" design.



DGE5010

Part No.	Seat	Max. Flow	Max. PSI
IP YRL20	* Zero	8.0 GPM	2900
IP DG4000	Zero	10.5 GPM	4500
IP DGE5010	Zero	10.5 GPM	5000
IP DGE4012W	Weep	10.5 GPM	5000
IP YG5000	Zero	10 GPM	5000

* Front Entry Style.

High Flow Trigger Wands

High Flow Trigger Wands are ideal for hydro excavation and high gpm flow requirements. Ergonomic design minimizes fatigue.

Standard Models are rated to 195° F. **Inline Models** are rated to 250° F.



ST2320
YG1732
YG2953B
ML210
RL84



YG2527S &
YG4032S
(Inline)

Lances & Extensions On Other Pages

Part No.	Max. Flow	Max. PSI	Ports
MV RL84	21 GPM	8100 PSI	1/2" FPT x 1/2" FPT
IP YG1732	32 GPM	1750 PSI	1/2" FPT x 1/2" FPT
IP YG2953B	53 GPM	2900 PSI	3/4" FPT x 1/2" FPT
MV ML210	53 GPM	3200 PSI	3/4" FPT x 1/2" FPT
IP YG2527S	* 27 GPM	2500 PSI	1/2" FPT x 1/2" FPT
IP YG4032S	* 32 GPM	4000 PSI	1/2" FPT x 1/2" FPT
NP ST2320	† 21 GPM	1800 PSI	1/2" FPT x 1/2" FPT

* Straight Inline Design.

† SS Inlet/Outlet, 300° F Rating.

High Pressure Trigger Wand



Trigger Spray Wand and **Lances** rated to 10,000 PSI. 3/8" Inlet x 3/8" outlet ports. 250° F.



Part No.	Max. Flow	Max. PSI
MV ML710	16 GPM	10,150
MV L7031	3/8" x 31" Lance Extension with Handle....	
MV L7047	3/8" x 47" Lance Extension with Handle....	

GIANT Trigger Guns

Performance Under Pressure

Giant Trigger Style Spray Guns are rated to 10 GPM and 5000 PSI these guns will handle a wide variety of cleaning applications.

Available with stainless steel discharge ports. Also available with Zero leak or Weep style seats. 3/8" FPT inlet and 1/4" FPT outlet. Maximum Temperature is 300° F.



21295B



Part No.	Inlet	Outlet	Seat
GU 21290B	Brass	Plated	Zero
GU 21295B	Brass	Plated	Weep
GU 21250B	Brass	S.S.	Zero
GU 21255B	Brass	S.S.	Weep
GU 21227	Repair Kit, 21250B & 21290B ...		
GU 21240	Repair Kit, 21255B & 21295B ...		

Trigger Spray Guns

Great Choice for car wash, truck wash or pressure wash applications. Available in weep or non-weep versions. Contour design and easy trigger pull for ease of use. Exact replacements for many of the popular spray guns on the market today. Brass 3/8" FPT inlet and 1/4" FPT outlet. Rated to 300° F.



925 & 925W
(8 GPM)



951
(10 GPM)



AL36
(12 GPM)

Part No.	Seat	Flow	Max. PSI
MV 925W	Weep Style	8 GPM	4000
MV 925	Zero Leak	8 GPM	4500
MV 951	Zero Leak	10 GPM	5100
AR AL36	Zero Leak	12 GPM	5100

Pressure Wash Spray Wands Non Slip Grip



2002



ML956

Designed for the pressure washer and truck wash industry. Heavy duty, unique gun features a soft, non-slip rubber grip for ease of use. Zero Leak design. Rated to 5800 PSI and 320° F. Standard with 3/8" FPT inlet and 1/4" FPT outlet. Brass or Stainless construction.

Part No.	Ports	Max. PSI	Max. GPM
MV 2002	Brass	5800	10.5
MV ML956	Stainless	5800	10.5



Trigger Guns

Adams Model 5030 Trigger Guns. Available with "weep" or "zero leak" seats. Designed with 3/8" FPT brass inlet and 1/4" FPT brass discharge port.

Standard Features: Stainless steel seat, ball and actuator pin • Glass-filled handle • Nylon construction • Maximum temperature is 300° F.

Part No.	Seat	Max. PSI	Max. Flow
AA 5030	Zero	4500	12 GPM
AA 5030W	Weep	4500	12 GPM

Viton® is a registered trademark of DuPont Performance Elastomers