

Back Mount Pressure Gauges

Dry Design & Liquid Filled



Back Mount Gauges for those requirements where rear mount plumbing is required. These gauges are available with 1-1/2", 2" or 2-1/2" dial faces and in either Glycerin-filled or Dry design. All gauges feature brass MPT stems. Cases are stainless.

DRY GAUGES Center Back Mount (CBM)

Part No.	Max. PSI	Fill	Size	Case	Stem
AH J504	15	Dry	1-1/2"	Stainless	1/8"
AH J505	30	Dry	1-1/2"	Stainless	1/8"
AH J507	60	Dry	1-1/2"	Stainless	1/8"
AH J508	100	Dry	1-1/2"	Stainless	1/8"
AH J518	160	Dry	1-1/2"	Stainless	1/8"
AH J519	200	Dry	1-1/2"	Stainless	1/8"
AH J509	300	Dry	1-1/2"	Stainless	1/8"
AH J511	30	Dry	2"	Stainless	1/4"
AH J512	60	Dry	2"	Stainless	1/4"
AH J513	100	Dry	2"	Stainless	1/4"
AH J516	300	Dry	2"	Stainless	1/4"
AH 2DP60	60	Dry	2-1/2"	Stainless	1/4"
AH 2DP100	100	Dry	2-1/2"	Stainless	1/4"
AH 2DP200	200	Dry	2-1/2"	Stainless	1/4"


LIQUID GAUGES Center Back Mount (CBM)

Part No.	Max. PSI	Fill	Size	Case	Stem
AH 2640-60	60	Liquid	2-1/2"	Stainless	1/4"
AH 2640-65	100	Liquid	2-1/2"	Stainless	1/4"
AH 2640-70	200	Liquid	2-1/2"	Stainless	1/4"
AH 2640-6	300	Liquid	2-1/2"	Stainless	1/4"
AH 2640-80	600	Liquid	2-1/2"	Stainless	1/4"
AH 2640-85	1000	Liquid	2-1/2"	Stainless	1/4"
AH 2640-90	2000	Liquid	2-1/2"	Stainless	1/4"
AH 2640-95	3000	Liquid	2-1/2"	Stainless	1/4"
AH 2640-50	5000	Liquid	2-1/2"	Stainless	1/4"
AH 2640-25	10,000	Liquid	2-1/2"	Stainless	1/4"
AH 26CL	U Clamp for Back Mount Gauges.....				



Water Temperature Gauge

An ideal option for checking water temperatures at your wand. Unique design mounts the backplate to a standard 1/4" wand extension. Shows your operating temperature to up to 240° F while water is flowing. Includes 4 stainless mounting screws.



Part No. NP 2097425
Max Temperature 240° F



Gauge Accessories

Gauge Damper B301A

This "pulsation-check" prolongs gauge life when placed between control line and pressure gauge. 3000 PSI rating.

Part No. TW B301A
Brass Pulsation Check 1/4" FPT x 1/4" MPT Connection.....

Lower Mount

Pressure Gauges Liquid-Filled • Brass Stems



Bottom Mount, Glycerin-Filled Pressure Gauges are the best choice where vibration or pulsation may be present. Dial faces are either 2-1/2" or 4". Stainless case. **Inlet stem is 1/4" MPT brass on all except WGGSS Series which feature stainless stems.** Pressure range from 60 to 10,000 PSI. (Models *2640-15, 16, 18 & 20 are combination Vacuum/Pressure Gauges.

Part No.	Maximum PSI	Fill	Size	Case	Brand
AH 2640-9	60	Liquid	2-1/2"	Stainless	Ashcroft
AH 2750-9	60	Liquid	2-1/2"	Stainless	Import
AH GG604	60	Liquid	4"	Stainless	Import
AH 2640-10	100	Liquid	2-1/2"	Stainless	Ashcroft
AH 2750-10	100	Liquid	2-1/2"	Stainless	Import
AH GG1004	100	Liquid	4"	Stainless	Import
AH 2640-11	200	Liquid	2-1/2"	Stainless	Ashcroft
AH 2750-11	200	Liquid	2-1/2"	Stainless	Import
AH 2750-14	400	Liquid	2-1/2"	Stainless	Import
AH 2750-8	600	Liquid	2-1/2"	Stainless	Import
AH 2640-1	1000	Liquid	2-1/2"	Stainless	Import
AH 2640-2	1500	Liquid	2-1/2"	Stainless	Import
AH 2640-3	2000	Liquid	2-1/2"	Stainless	Ashcroft
AH 2750-3	2000	Liquid	2-1/2"	Stainless	Import
AH 2640-4	3000	Liquid	2-1/2"	Stainless	Ashcroft
AH 2750-4	3000	Liquid	2-1/2"	Stainless	Import
AH 2640-5	5000	Liquid	2-1/2"	Stainless	Ashcroft
AH 2750-5	6000	Liquid	2-1/2"	Stainless	Import
AH 2640-14	10,000	Liquid	2-1/2"	Stainless	Import
AH 2640-15	* 30 HG to 100#	Liquid	2-1/2"	Stainless	Import
AH 2640-16	* 30 HG to 30#	Liquid	2-1/2"	Stainless	Import
AH 2640-17	30 HG Only	Liquid	2-1/2"	Stainless	Import
AH 2640-18	* 30 HG to 30#	Liquid	4"	Stainless	Import
AH 2640-20	* † 30 HG to 60#	Liquid	2-1/2"	Stainless	Import

* Combo Vacuum/Pressure Gauge. † Stainless Stem Also

Stainless Steel Gauges

Liquid-Filled

WGG Gauges are liquid-filled, lower mount with 304 stainless steel case and stem. Back mount also available.



Part No.	Max. PSI	Fill	Size
AH WGGSS30	30	Liquid	2-1/2"
AH WGGSS60	60	Liquid	2-1/2"
AH WGGSS100	100	Liquid	2-1/2"
AH WGGSS200	200	Liquid	2-1/2"
AH WGGSS400	400	Liquid	2-1/2"
AH WGGSS1000	1000	Liquid	2-1/2"
AH WGGSS2000	2000	Liquid	2-1/2"
AH WGGSS3000	3000	Liquid	2-1/2"
AH WGGSS5000	5000	Liquid	2-1/2"
AH WGGSS60-4	60	Liquid	4"
AH WGGSS100-4	100	Liquid	4"
AH WGGSS160-4	160	Liquid	4"
AH WGGSS200-4	200	Liquid	4"
AH WGGSS400-4	400	Liquid	4"

Dry Design

Lower Mount Gauges

Dry Pressure Gauges, Bottom Mount are economically priced and recommended for use where vibrations, pulsations and hydraulic shock are minimal. Cases are ABS plastic or steel. Dial faces are 2", 2-1/2" or 4". Brass inlet stem is 1/4" MPT. Pressure range from 15 to 1,000 PSI. Gauges shown are import brand.



Part No.	Max. PSI	Fill	Size	Case
AH J500	15	Dry	2"	ABS
AH J501	30	Dry	2"	ABS
AH J502	60	Dry	2"	ABS
AH J503	100	Dry	2"	ABS
AH J506	300	Dry	2"	ABS
AH 1DP60	60	Dry	2-1/2"	ABS
AH 1DP100	100	Dry	2-1/2"	ABS
AH 1DP160	160	Dry	2-1/2"	ABS
AH 1DP200	200	Dry	2-1/2"	ABS
AH SG400	400	Dry	2-1/2"	ABS
AH SG1000	1000	Dry	2-1/2"	ABS
AH SG60-4	60	Dry	4"	Steel Case
AH SG100-4	100	Dry	4"	Steel Case