

High Pressure Foamers



These unique foamers can be attached to your discharge gun to apply foamed chemicals downstream from your high pressure pump. Rated to a maximum of 2900 PSI. Foam supply can be easily changed with the adjustment knob.

Features: Rust-proof construction • chemical resistant material • filtered chemical bottle. Buna seals.

YLS12 is a foamer with an injector barb inlet for hose or tubing, not tank.

YLS12T & YLS31T are the same as YLS12 but with 1 quart tank.

Specifications: Maximum temperature of 140° F. • Weight is approximately 1-lb. • Materials of construction are plastic, brass, stainless steel and Buna-N. • Tank is 1 quart capacity. Inlet is 1/4" FPT. Minimum operating pressure of 700 PSI.

Part No.		Maximum Pressure	Maximum GPM
IP YLS12	Foamer WITHOUT Tank	2900 PSI	6.50
IP YLS12T	Foamer WITH Tank	2900 PSI	6.50
IP YLS31T	Foamer WITH Tank	2300 PSI	5.30

ProFoam Foamer - Low Pressure



DEMA Hand-Held Bottle Foamer dispenses foaming degreasers and sanitizers on a variety of surfaces. Ideal for use in car washes, food service areas, quick lube bays etc. Easily attaches to standard garden hose with city water pressure. Produces excellent foam quality with good distance, (10' throw at 40 psi inlet water pressure). Spray gun and quick connect fitting are standard. Bottle has 32 oz. capacity. Buna and EPDM seals.

Part No.
DE 289 ProFoam Bottle Foamer

SUTTNER High Pressure Foamers

Hand Foamers from Suttner can be adjusted for vertical or horizontal spray pattern. Ideal for industry, agriculture, institutional cleaning and food processing. Easy-to-fill 32 or 64 oz. tanks.

Plastic stainless and brass construction for corrosion-resistance. Unique design cuts chemical consumption by up to 50% over other foamers. 1/4" FPT inlet. Buna seals.



Part No.		Maximum Pressure	Maximum GPM
NP ST73	Foamer and 32 oz. Tank	4350 PSI	5.2
NP ST732	Foamer and 64 oz. Tank	4350 PSI	5.2
NP ST473	Foamer and 32 oz. Tank	5000 PSI	5.3

Foam Cannon

— Adjustable Pattern —

The **Foam Cannon** is the new standard in the Foaming Industry. From vehicle detailing to Food Processing applications to livestock barns to construction equipment, this is the tool that will save you time and money. Simply attach to your pressure washer, fill the tank with your cleaning solution and you are up and running.

Adjustable front spray pattern (*vertical or horizontal*) throws a thick foam up to 20' • Adjustable top chemical knob allows for more or less chemical us • 32 oz. Tank • Rated from 1000 to 4000 PSI • Rated from 1.4 to 5.3 GPM • Rated to 140° F.

PF22 is Foam Cannon with tank, no trigger. 1.8 to 5.3 GPM, 1100 to 5000 PSI.

PF22CO is Foam Cannon, tank, trigger wand with swivel, stainless coupler fittings. 1.4 to 5.3 GPM, 1100 to 4000 PSI.



Part No.
MV PF22 Foam Cannon with Tank
MV PF22CO Foam Cannon with Tank & Trigger Handle

Adjustable Foam Lances

No. 140263 Foam lance with bottle can throw a dense chemical foam up to 20'. Adjustable design allows for user to spray varying distances with a wide or concentrated pattern. Chemical bottle has 32 oz. capacity. Rated to 5.3 GPM and 5000 PSI. Inlet port is 1/4" FPT. 1/4" QC plug and 22mm adapter are also included. Viton® seals. Minimum operating pressure of 1,100 PSI.

No. 140289 Foam lance without chemical bottle. Simply put tubing and foot valve into your chemical pail or drum. Kit includes foam lance, 30' tubing, foot valve and (3) orifices for 3.0, 4.0 or 5.6 GPM pumps. Rated to 5.6 GPM, 5000 PSI and 140° F. Inlet is 1/4" FPT. Viton® seals. Minimum operating pressure of 1,100 PSI.



Part No.		Maximum Pressure	Maximum GPM
MV 140263	Foamer WITH Tank	5000 PSI	5.3
MV 140289	Foamer WITHOUT Tank	5000 PSI	5.6

Viton® is a registered trademark of DuPont Performance Elastomers