


Control Transformers



Electrical Step Down Transformers are ideal for controlling solenoids, magnetic switches, control valves and many more. Available in 20/40/100VA ratings and from 120/208/240/480 volt primary to 24 volt secondary output as noted.

33 Series feature NEMA 1 enclosures and are UL listed and CSA

Certified. 100VA, single or three phase.

All models are 50/60hz except *33100208 which is 60hz only.



4X and **3T Series** are Class 2, UL and C-UL recognized, 20 and 40VA. Single phase, 50/60hz.

Part No.	Input Voltage	Output Voltage	VA Rating	Wt.
GO 33100K	120V	24V	100	4 lbs.:
GO 3310018	208V	24V	100	4 lbs.
GO 33100HLK	240/208V	24V	100	4 lbs.
GO 33100208	*120x208x240x480V	24V	100	4 lbs.
GN 4X744	120V	24V	20	1 lb.
GN 4X746	120V	24V	40	1 lb.

Ground Fault Circuit Interrupter

For indoor or Outdoor Use.



GFI power cord is UL listed and features Test Button, Reset Button and Power-On indicator light. 25ft cord has 3-prong plug on one end and blunt cut 3 wires on other end for direct wiring to existing motors. 12 gauge, 20amp rating.

Part No.	Length	Rating	Gauge
DU 1051-12-25	25'	20amp	12

Power Cords

Plug with Bare Wire Ends



Part No.	Gauge	Wires	Length	Grounded	Ends
GN 1FD92	14	3	8'	Yes	Bare
GN 1FD93	12	3	8'	Yes	Bare

BESTWAY SHIPPING

"BestWay" shipping may not be the quickest option, but it will help to lower your freight bill. If you select this method of shipping, Dultmeier will calculate the cheapest way to ship your package(s) at the time of shipment.

Hour Meters



Compact, top quality elapsed time indicators for implementing an efficient preventive maintenance program on your pumps or equipment.

These hour meters are available in 24 Volt or 120 Volt and in resettable and non-resettable models. Counter wheels have large, easy-to-read numbers. Whole numbers are white against black background. Decimal number is black on white background.

High impact housing with round faces. All models include 6" wire leads. All models are UL listed.

2PAT4: 115 Volt push button **resettable** meter. Registers elapsed time up to 9999.9 hours. 2-1/2" face.

2PAT3: 115 Volt **non-resettable** meter. Registers elapsed time up to 99999.9 hours. 2-1/2" bezel face. Length is 2-3/4" front to back.

3410-1000: 24 Volt non-resettable meter. Registers elapsed time up to 99999.9 hours. 2-13/16" round bezel face. Length is 2-3/4" front to back.



Part-No.		Voltage
GN 2PAT4	Resettable Meter	120
GN 2PAT3	Non-resettable Meter ...	120
NP 3410-1000	Non-resettable Meter ...	24


Hose & Cable Ties

Flexible Nylon Cable Ties are an ideal way to bundle, attach or secure hose, wire, cable and tubing in commercial, industrial and agricultural applications. High tensile strength and low insertion force design. Tapered tail is pulled through the head to securely lock in place. Working temperature from -40° to +185° F. **UV rated, black nylon construction** for indoor or outdoor use. UL listed, CSA certified. Manufactured in USA. Sold in bags of 50 or 100 ties as noted. *Quantity Discounts are available for multiple bag purchases.*



Part No.	Length	Tensile Strength	Max. Diameter	Ties Per Bag
AL 07500C	7"	50 lb.	1.87"	100 *
AL 11500C	11"	50 lb.	3.06"	100 *
AL 14500C	14"	50 lb.	4.00"	100 *
AL 141200C	14"	120 lb.	4.00"	100 **
AL 241750L	24"	175 lb.	7.18"	50 **
AL 361750L	36"	175 lb.	11.0"	50 **

* 10% Discount for 20 Bags Not Assorted.
 ** 10% Discount for 10 Bags Not Assorted.



Shipped ASAP!
"Todays Engines require clean, clean fuel, and when you live in the bush, when something breaks or if you just need a filter, it could take weeks to arrive, Dultmeier sales shipped ASAP and now Im ready for the season."

Kodiakcombos