

**Portable Hot Water Pressure Washers** for tough industrial cleaning. Professionally engineered to combine Hot Water, Pressure and Volume to provide efficient and effective cleaning. Available in oil-fired portable units, electric or gas drive. Designed to provide water temperatures to 160° to 170° F. depending on incoming water temperatures. All units feature *General* Plunger Pumps (*Other Pump Options Available*).



## Oil Fired Pressure Washers - Electric Motor Drive

**Portable Oil-Fired Pressure Washers** feature single phase, TEFC motors, (3 phase available). 2 wheel or 4 wheel carts with pneumatic tires, *General* plunger pumps, Trigger wand assembly with 50' hose, downstream chemical injector, pressure control valve and Schedule 80 coils. Rated to 160° - 170° F. output depending on incoming water temperatures.

**DG Series** are made in USA. 2-wheel carts, 7-1/2 gallon tank for #1 diesel or kerosene.

**EZ Series** are made in Canada. 4-wheel carts, 10 gallon tank for #1 diesel or kerosene.



**DP3 & DP4 Series**  
Made In USA



**FREE FREIGHT ALL MODELS**



Hose Reel Mount

**EZ Series**  
Made In Canada

Part No.	Output	Motor	Wt.
DU DP3-1000	3.0 GPM @ 1000 PSI	2 HP, 115 Volt	340 lbs.
DU DP3-2000	3.0 GPM @ 2000 PSI	4 HP, 230 Volt	380 lbs.
DU DP4-3000	4.0 GPM @ 3000 PSI	8 HP, 230 Volt	475 lbs.
EZ 2435EGP	3.5 GPM @ 2400 PSI	5 HP, 220 Volt	465 lbs.
EZ 3035EGP	3.5 GPM @ 3000 PSI	7.5 HP, 220 Volt	500 lbs.
EZ HR150HP	Hose Reel Option for EZ Series, 100 Foot Capacity.....		



**DG Series**  
Made In USA



**EZ Gas Series**  
Made In Canada

## Oil Fired Pressure Washers - Gas Engine Driven

**Portable Oil-Fired Pressure Washers** feature Gas Engines with 12 volt start. All units include trigger wand assembly, 50' hose, downstream chemical injector, pressure regulator valve, *General* plunger pumps, Schedule 80 coils, safety pop-off valve, heavy-duty 4-wheel carts with pneumatic tires, 12 Volt burner motors, and electronic ignition. Rated to 160° - 170° F. output depending on incoming water temperatures.

**DG Series** are made in USA and have 7-1/2 gallon tanks for #1 diesel or kerosene.

**EZ Series** are made in Canada and have 10 gallon tanks for #1 diesel or kerosene.

All models include battery holders but batteries are not included.

Part No.	Output	Engine	Wt.
DU DG3-4000	3.0 GPM @ 4000 PSI	GX390 Honda Gas	590 lbs.
DU DG4-3000	4.0 GPM @ 3000 PSI	GX390 Honda Gas	560 lbs.
DU DG4-4000	3.5 GPM @ 4000 PSI	Vanguard Gas	690 lbs.
EZ 4035GK12	3.5 GPM @ 4000 PSI.	Kohler Gas	400 lbs.
EZ 4035GH12	3.5 GPM @ 4000 PSI.	Honda Gas	400 lbs.
EZ 4035DK12	3.5 GPM @ 4000 PSI.	Kohler Diesel	400 lbs.
EZ HR150HP	Hose Reel Option for EZ Series, 100 Foot Capacity .....		

### Vertical Inline Tanks

Part No.	Tank Capacity		Connection	Dimensions	Wt.
	Gallons	NPTM			
WO MAX-03	.35	1/2"	7.9" H x 5.1" D	6.8 lbs.	
WO MAX-05	.50	3/4"	8.5" H x 5.1" D	10.4 lbs.	
WO MAX-20	2.0	3/4"	11.4" H x 8" D	5.1 lbs.	
WO MAX-30	3.2	3/4"	15.4" H x 9.1" D	7.1 lbs.	
WO MAX-45	4.5	3/4"	15.4" H x 11" D	8.2 lbs.	
WO MAX-60	6.0	3/4"	16.3" H x 11.6" D	10.6 lbs.	
WO MAX-100	10.0	3/4"	21.7" H x 11.6" D	15 lbs.	

### Vertical Inline Tanks with Base

Part No.	Tank Capacity		Connection	Dimensions	Wt.
	Gallons	NPTM			
WO MAX-215	14	1"	23.6" H x 15" D	24.3 lbs.	
WO MAX-220	20	1"	30.7" H x 15" D	32.2 lbs.	
WO MAX-225	28	1"	39.2" H x 15" D	40.6 lbs.	
WO MAX-230	32	1"	44.1" H x 15" D	50.1 lbs.	
WO MAX-235	34	1-1/4"	29.5" H x 22" D	54.1 lbs.	
WO MAX-245	44	1-1/4"	36" H x 22" D	61.3 lbs.	

### Horizontal Tanks with Base

Part No.	Tank Capacity		Connection	Dimensions	Wt.
	Gallons	NPTM			
WO MAXH-45	4.5	3/4"	15.4" L x 12" D	9.7 lbs.	
WO MAXH-60	6.0	3/4"	16.3" L x 12.6" D	11.9 lbs.	
WO MAXH-100	10	3/4"	21.7" L x 12.6" D	16.4 lbs.	
WO MAXH-215	14	1"	22" L x 17" D	24.5 lbs.	
WO MAXH-220	20	1"	32" L x 17" D	32.5 lbs.	

## Pressure Tanks Precharged with Nitrogen



**More Sizes Available!**



**Features:** Precharged with Nitrogen – holds pressure much longer and more consistently than air • NSF/ANSI 61 rated • Corrosion-resistant baked epoxy Coating • Leak-free, O-ring sealed air valve cap • 100% Pressure tested and factory pre-charged to 30 PSI • Maintenance-Free operation • 304 Stainless Steel water connection • Horizontal or Vertical models available • Blue is standard color but green and tan are also available • Maximum Working Pressure is 150 PSI • Maximum Working Temperature is 195°F • Polypropylene liner & butyl diaphragm for ensured longevity.