



## 390SD EPDM All Weather Suction/Discharge Hose



- Lightweight - Low Cost
- 100% EPDM Tube
- Abrasion Resistant Cover
- Smooth I.D. for Maximum Flow Rates
- Ideal for High Ozone Areas

**390SD Series EPDM Suction or Discharge Hose.** 100 PSI rating at 72° F. Full vacuum rating at 72° F. Polyethylene Helix. Corrugated OD. Smooth Bore. Internal Braiding for higher pressure. Color: Black. -40° F. to +140° F. **TSD400** is a Kuriyama brand. CW Helix wrap.



Series 390SD

**NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY**

- Bulk or Fitted Assemblies -

Part No.	I.D.	O.D.	* Std. Pkg.	** Working Pressure	Bend Radius
KA 390SD-1-1/4	1-1/4"	1.80"	100'	100 PSI	3"
KA 390SD-1-1/2	1-1/2"	2.10"	100'	100 PSI	3"
KA 390SD-2	2"	2.60"	100'	100 PSI	5"
KA 390SD-3	3"	3.70"	100'	90 PSI	9"
TF TSD400	† 4"	4.53"	100'	75 PSI	15"

\*\* Base on 72° F. † 4" is Kuriyama Brand.

**\* 25% Discount for Standard Package**

**Fitted Hoses with Aluminum Male x Female Lever Couplings (SS Fittings Also Available). Specified Length is Overall Assembly Length.**

Part No.	I.D.	Length	Wt.	Bend Radius
DU 390SD2X20	2"	20'	22 lbs.	11"
DU 390SD2X30	2"	30'	32 lbs.	11"
DU 390SD2X40	2"	40'	42 lbs.	11"
DU 390SD3X20	3"	20'	25 lbs.	12"
DU 390SD3X30	3"	30'	35 lbs.	12"
DU TSD4X20	4"	20'	31 lbs.	15"
DU TSD4X30	4"	30'	41 lbs.	15"

- Heavy Duty Flexible -



## EPDM Rubber Suction / Discharge Hose



**Heavy Duty Water Suction/Discharge Hose** for agricultural, construction, and industrial applications. Black EPDM cover and tube designed to handle a variety of liquids including fertilizers and others. Wire helix reinforcement. **Maximum Working Pressure is 150PSI. Temperature Rating: -40°F to 212°F.** Not designed for applications involving acid-based chemicals or alcohols. **Cut Lengths Sold in 5' Increments Only.**

Part No.	I.D.	O.D.	Std. Pkg.	Working Pressure	Bend Radius (in @ 68°F)	Vacuum Rating (inHG)
TF T202-1	1"	1.38"	100'	150 PSI	4"	30"
TF T202-1-1/4	1-1/4"	1.65"	100'	150 PSI	5"	30"
TF T202-1-1/2	1-1/2"	1.89"	100'	150 PSI	6"	30"
TF T202-2	2"	2.40"	100'	150 PSI	8"	30"
TF T202-3	3"	3.46"	100'	150 PSI	10"	30"
TF T202-4	4"	4.49"	100'	150 PSI	12"	27"
TF T202-6	6"	6.54"	50'	150 PSI	30"	24"
TF T202-8	* 8"	8.70"	20'	150PSI	40"	21"

\* Can be bought in 20' or 25' lengths from factory.

\*\* Additional Sizes Available - Call for Details

**25% Discount for Standard Package**

**Fitted Hoses with Aluminum Male x Female Lever Couplings and Band-It Clamps (SS Fittings Also Available)**

Part No.	I.D.	Length	Wt.	Bend Radius
DU T202-2X20	2"	20'	22 lbs.	8"
DU T202-2X30	2"	30'	31 lbs.	8"
DU T202-2X40	2"	40'	39 lbs.	8"
DU T202-3X20	3"	20'	35 lbs.	10"
DU T202-3X30	3"	30'	48 lbs.	10"
DU T202-4X20	4"	20'	47 lbs.	16"
DU T202-4X30	4"	30'	67 lbs.	16"

\* Hose Assemblies made to Overall Length as Noted.

## tigerflex Suction & Discharge Hose

**Flexible EPDM Rubber Hose** with green or yellow polyethylene helix combines chemical resistance with durability. Excellent cold weather flexibility. Weather resistant exterior. Lightweight and easy-to-handle. Abrasion resistant design slides easily on rough surfaces. Rated from -40 to 160° F. Full vacuum rating to 4" size at 68° F. Sold in rolls, cut to length and fitted assemblies. Red & Blue also available.



- Septic Handling
- Liquid Waste, Slurries
- Liquid & Dry Chemical
- Agriculture Liquid & Dry Fertilizers
- Grains & Seeds
- Water Transfer
- Mining
- Construction, Rental Equipment, Sewer Cleaning, Plant Maintenance



Series TG / 300G Green



Series TY / 300Y Yellow

**NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY**

Part No.	I.D.	O.D.	Color	PSI @ 68° F.	Wt./Lbs. Per Foot
TF TG100	1"	1.40"	Green	65	.28
TF TG125	1-1/4"	1.63"	Green	60	.33
TF TG150	1-1/2"	1.93"	Green	50	.44
TF TG200	2"	2.51"	Green	50	.67
TF TG250	2-1/2"	3.07"	Green	45	.95
TF TG300	3"	3.60"	Green	45	1.14
TF TG400	4"	4.70"	Green	40	1.84
TF TG600	6"	6.85"	Green	30	3.70
TF TY100	1"	1.40"	Yellow	65	.28
TF TY125	1-1/4"	1.63"	Yellow	60	.33
TF TY150	1-1/2"	1.93"	Yellow	50	.44
TF TY200	2"	2.51"	Yellow	50	.67
TF TY300	3"	3.60"	Yellow	45	1.14
TF TY400	4"	4.70"	Yellow	40	1.84
TF TB200	2"	2.51"	Blue	50	.67
TF TB300	3"	3.60"	Blue	45	1.14
TF TB400	4"	4.70"	Blue	40	1.84

**\*25% Discount if Ordered in 100' Rolls**

## tigerflex Suction/Discharge Hose Assemblies



TG Series Hose Assemblies



Use TY in place of TG for Yellow Assemblies

**Flexible TigerFlex Hose Assemblies.** All of the same qualities shown in the bulk hose but in cut lengths. Aluminum female lever coupler on one end and male adapter on the other end. Banded clamp design for added life and performance. Stock hoses are Tiger Green, but Tiger Yellow or Tiger Blue can also be made to order. Lengths other than those shown are also available.

Part No.	I.D.	Length	Color	Wt./Lbs.
DU TG200X20	2"	20'	Green	15
DU TG200X30	2"	30'	Green	22
DU TG200X40	2"	40'	Green	29
DU TG300X20	3"	20'	Green	27
DU TG300X25	3"	25'	Green	32
DU TG300X30	3"	30'	Green	38
DU TG400X10	4"	10'	Green	24
DU TG400X20	4"	20'	Green	42
DU TG400X30	4"	30'	Green	61

Please remember there are No Returns on customer specified cut lengths of hose.