




## EVA Applicator Tubing

Translucent & Black

**V1160 EVA Tubing** for the safe handling of: Anhydrous Ammonia, Ammonium Nitrate, Aqua Ammonia, Liquid Fertilizer Solutions, Herbicides, Insecticides, Phosphates, Phosphoric Acid and Potassium Products. For up to 26" of vacuum. Flexible to -30° F. Will not crack to -75° F. **Sold in Standard Packages ONLY.**

Part No.	I.D.	Length	Wt.	Color
GD V1160-1/4	1/4"	100'	4 lbs.	Clear
GD V1160-1/4X500	1/4"	500'	17 lbs.	Clear
GD V1160-3/8	3/8"	500'	26 lbs.	Clear
GD VB1170-3/8	* 3/8"	500'	26 lbs.	Black
GD V100X3/8	3/8"	100'	9 lbs.	Clear
GD V1160-1/2X500	1/2"	500'	30 lbs.	Clear
GD VB1170-1/2X500 *	1/2"	500'	30 lbs.	Black
GD V100X1/2	1/2"	100'	11 lbs.	Clear
GD V1160-3/4X250	3/4"	250'	30 lbs.	Clear
GD V1160-1"	1"	100'	30 lbs.	Clear

\* **Black Tubing.** NOTE: EVA tubing is priced and sold in full reels only. 3/8" & 1/2" are available in 100' Packages. Working pressure @ 70°F = 75 PSI thru 1/2", 60 PSI 3/4"-1"



## Braided EVA Tubing

**Reinforced EVA Tubing** is designed to transport a variety of chemicals and liquids. Translucent for easy view of flows. Higher working pressure than unbraided tubing.



EVAB x 1-Braid

Lightweight and flexible. Not suitable for gasoline or diesel. Rated from -30° to +125° F. Formulated to comply with FDA and RoHS requirements. Polyester yarn reinforcement. Natural color. **Sold by the foot or in standard packages for lower pricing. Cut Lengths in 5' Increments.**

Part No.	I.D.	O.D.	Max PSI @ 70° F.	* Std. Pkg.
TF EVAB14	1/4"	.460"	250 PSI	300'
TF EVAB38	3/8"	.594"	250 PSI	300'
TF EVAB50	1/2"	.720"	250 PSI	300'
TF EVAB75	3/4"	1.00"	150 PSI	200'
TF EVAB100	1"	1.312"	150 PSI	200'

\* 25% Discount for Standard Package.

## Braided Vinyl Tubing



**Reinforced Vinyl (PVC) Tubing** is flexible and translucent. Higher work pressures than unbraided tubing. Designed for a variety of chemicals and liquids. Natural color permits viewing of flow. Rated to +25° to +150° F. NSF51 and 61 dual certified.

**Cut Lengths in 5' Increments.**

Part No.	I.D.	O.D.	Max PSI @ 70° F.	* Std. Pkg.
TF RF014	1/4"	.438"	250	300'
TF RF038	3/8"	.594"	250	300'
TF RF050	1/2"	.750"	200	300'
TF RF058	5/8"	.625"	200	300'
TF RF075	3/4"	1.025"	150	100'
TF RF100	1"	1.312"	125	100'
TF RF125	1-1/4"	1.937"	100	100'
TF RF150	1-1/2"	1.656"	100	100'

\* 25% Discount for Standard Package Purchase.

**Sold by the Foot with Discounts for Standard Package Purchase.**

## Vinyl Poly Spring® Tubing

Clear PVC reinforced with a spring wire. One piece construction that embeds the spring wire reinforcement


**Features:** Anti-collapsible. • Anti-kinking. • Full Vacuum rating. • Light-weight. • Chemical resistant. • Ozone and atmospheric resistant. • Temperature range +25° to +150° F. • FDA/USDA Rated.



NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY

Part No.	I.D.	O.D.	Max. PSI @ 70° F.	Std. Pkg.	* Std. Pkg. DISCOUNT
TF WF014	1/4"	.447"	100	100'	25%
TF WF038	3/8"	.600"	100	100'	25%
TF WF050	1/2"	.736"	100	100'	25%
TF WF075	3/4"	1.028"	70	100'	25%
TF WF100	1"	1.290"	70	100'	25%

\* 25% Discount for Standard Package Purchase.



## High Pressure Spray Hose

Chemical Resistant

A1661 is Yellow & A1687 is Green

Tube: PVC/Polyurethane Blend

Excellent for use on a Hose Reel


A hose for agricultural, commercial and pest control spraying. Has ribbed PVC cover with black PVC/Polyurethane blend tube for excellent chemical resistance including aromatic hydrocarbon based products.

**Specifications:** Pin pricked cover to vent vapor and prevent ballooning • 600 PSI Rating • Temperature range is +15°F. to +160°F. (Specify A1687 - 800 PSI Series for tree spraying.) Standard stock coil size is 300', but is available in 400'. **Note:** Reusable type fittings are not recommended. **Cut Lengths in 5' Increments.**

Part No.	I.D. & Description	O.D.	PSI @ 70° F.	Wt.
DU A1661-3/8	3/8" ID Cut Lengths	0.65"	600	14/C
DU A1661-1/2	1/2" ID Cut Lengths	0.79"	600	19/C
DU A1661-3/4	3/4" ID Cut Lengths	1.17"	600	35/C
TF A1661-06	3/8" x 300' Coil	0.65"	600	41 lbs.
TF A1661-06X	** 3/8" x 300' Hose Assembly, Yellow	-	-	-
TF A1661-06-400	3/8" x 400' Coil	0.65"	600	55 lbs.
TF A1661-08	1/2" x 300' Coil	0.79"	600	57 lbs.
TF A1661-08-400	1/2" x 400' Coil	0.79"	600	76 lbs.
TF A1661-08X	** 1/2" x 300' Hose Assembly, Yellow	-	-	-
TF A1661-10	5/8" x 300' Coil	1.03"	600	82 lbs.
TF A1661-12	3/4" x 300' Coil	1.17"	600	106 lbs.
TF A1687-08	* 1/2" x 300' Coil	0.79"	800	57 lbs.
TF A1687-12	* 3/4" x 300' Coil	1.17"	800	106 lbs.
TF A1628-16	† 1" x 200' Coil	1.5"	200	65 lbs.

\* Green. † Gray \*\* Includes 3/8" or 1/2" Steel MNPT ends, crimped style.

## Clear Vinyl Tubing



**Clear Vinyl Tubing** is flexible, lightweight and transparent. Provides full flow viewing. Construction is Polyvinyl Chloride (PVC). Ideal for handling a wide variety of liquids. Excellent resistance to many types of acids, detergents and alkalis. Formulated to comply with FDA and RoHS requirements. Rated from +25° to 150° F. **Sold in rolls only, no cut lengths.**

Part No.	I.D.	O.D.	Wall	Max. PSI @ 70° F.	Roll Size
TF 1A	1/8"	1/4"	1/16"	65	100'
TF 1	1/4"	3/8"	1/16"	50	100'
TF 1X500	1/4"	3/8"	1/16"	50	500'
TF 2	3/8"	1/2"	1/16"	40	100'
TF 2X500	3/8"	1/2"	1/16"	40	500'
TF 2A	3/8"	9/16"	3/32"	50	100'
TF 4A	1/2"	5/8"	1/16"	25	100'
TF 4	1/2"	3/4"	1/8"	45	100'
TF 6	5/8"	13/16"	3/32"	30	100'
TF 5	5/8"	7/8"	1/8"	40	100'
TF 7	3/4"	1"	1/8"	35	100'
TF 9	1"	1-1/4"	1/8"	25	100'
TF 11	1-1/4"	1-1/2"	1/8"	20	50'
TF 13	1-1/2"	1-3/4"	1/8"	16	50'
TF 13A	1-1/2"	2"	1/4"	35	50'
TF 15	2"	2-1/2"	1/4"	30	50'

## Rubber Air Hose Assemblies



- Lightweight & Super Strong
- Ozone Resistant Cover Protects from Weather
- Rated from -40° F. to +190° F., & 300 PSI
- Brass 1/4" MPT Fittings
- Abrasion & Kink Resistant
- Bend Restrictor Guards
- Oil Resistant Cover

Part No.	Hose	Wt.
DU AH25	3/8" x 25'	2.7 lbs.
DU AH50	3/8" x 50'	5.3 lbs.
DU AH100	3/8" x 100'	10.6 lbs.