


Center Punch

Open-End Clamps

– For Wrap-Around Applications –

Austenitic stainless open-end clamps are tensioned, then locked by striking tool punch with mallet or hammer. Requires T300 tool.




Part No.	Band Width	Max. Diameter Once Around	Max. Diameter Twice Around	Total Length	Pkg. Qty.
BD O10S	5/8"	5"	2-1/2"	23"	50
BD O16S	5/8"	8"	4"	31"	50

— Sold In Full Packages Only —

Center Punch Clamps

Band-It® CP Series Center Punch Clamps are 201 stainless steel. CP clamps are locked with a standard conical punch, ensuring a strong, powerful lock for reliable and consistent clamping. **Note:** CP clamps should be installed with Band-It's T300 tool.



Part No.	Clamp I.D.	Band Width	Pkg. Qty.
BD CP8S	2"	5/8"	100
BD CP10S	2-1/2"	5/8"	50
BD CP11S	2-3/4"	5/8"	50
BD CP12S	3"	5/8"	50
BD CP16S	4"	5/8"	25
BD CP20S	5"	5/8"	25
BD CP24S	6"	5/8"	25
BD CP28S	7"	5/8"	25

Sold in Full Pkgs. ONLY

BAND-IT Jr®

Preformed Clamps

Band-It Jr.® Preformed Clamps are vibration resistant and require no hammering or crimping. They are automatically locked under full tension in one simple lever movement. **Note:** Jr® preformed clamps should be installed with Band-It's C001 Tool and J001 Junior Adapter.



Part No.	Width	Clamp I.D.	Std. Pkg.	Std. Discount
BD JS201	3/8"	13/16"	100	20%
BD JS243	3/8"	1"	100	20%
BD JS202	3/8"	1-3/8"	100	20%
BD JS205	5/8"	1-1/2"	100	20%
BD JS207	5/8"	2"	100	20%
BD JS208	5/8"	2-1/4"	100	20%
BD JS210	3/4"	2-3/4"	50	20%
BD JS213	3/4"	4"	25	20%
BD JS215	3/4"	5"	25	20%
BD JS218	3/4"	7"	25	20%

BAND-IT Ultra-Lok® Preformed Clamps

Band-It Ultra-Lok® Preformed Clamps offer 2 to 3 times the strength as other preformed clamping systems for demanding applications. Double-wrapped 201 Stainless Steel. Smooth ID eliminates leak paths. Unique lock system maximizes tightness while a heavy-duty buckle hood protects from snags. Install using **Ultra-Lok®** Tools.



Part No.	Width	Clamp I.D.	Std. Pkg.	Std. Discount
BD UL210	3/4"	2-3/4"	50	20%
BD UL211	3/4"	3"	50	20%
BD UL212	3/4"	3-1/2"	50	20%
BD UL213	3/4"	4"	25	20%
BD UL214	3/4"	4-1/2"	25	20%
BD UL215	3/4"	5"	25	20%
BD UL216	3/4"	6"	25	20%
BD UL217	3/4"	6-1/2"	25	20%
BD UL218	3/4"	7"	25	20%
BD UL219	3/4"	8"	25	20%
BD UL228	3/4"	9"	10	10%

SmartSeal™ Clamps

Helps to Stop Leakage From Thermal Changes

SmartSeal™ Clamps were designed in response to the leakage attributed to thermal changes and to meet today's challenging lighter weight and space requirements.



Integrated Two-Piece Design:

SmartSeal™ clamps are comprised of two main parts, the clamp assembly and the SmartLiner.



- The SmartLiner is a 1/2" spring liner made of high quality stainless steel integrated inside the clamp.
- Designed to be smart, the thin gauge steel expands and contracts around hose with temperature changes.
- Clamp rides on top of lubricated liner, distributing pressure more evenly around hose.

SmartSeal™ Clamps are engineered to last longer, and perform better than traditional clamps in the most demanding environments.

Features:

- All 300 stainless steel construction.
- 5/8" wide band - 5/16" hex screw.
- Spring compensation over 360 degrees.
- Improved clamp roundness eliminates leak paths at housing juncture.
- Grooved design creates higher pressure loading compared to conventional worm gear, increasing resistance against potential leaks.
- Trough shape helps clamp "grip" by penetrating deeper into the hose wall resulting in a more effective cross sectional pressure footprint.
- 150 in/lb. Maximum torque at screw.

The SmartSeal Channel Design



High Pressure

Part No.	Band Width	Min. Inches	Max. Inches	Std. Pkg.	Std. Pkg. Discount
MP 0238	5/8"	1.64"	2.12"	10	10%
MP 0262	5/8"	1.90"	2.38"	10	10%
MP 0275	5/8"	2.03"	2.51"	10	10%
MP 0288	5/8"	2.16"	2.64"	10	10%
MP 0300	5/8"	2.29"	2.77"	10	10%
MP 0325	5/8"	2.53"	3.03"	10	10%
MP 0350	5/8"	2.74"	3.28"	10	10%
MP 0375	5/8"	2.92"	3.54"	10	10%
MP 0400	5/8"	3.12"	3.79"	10	10%
MP 0425	5/8"	3.31"	4.04"	10	10%
MP 0450	5/8"	3.48"	4.29"	10	10%
MP 0512	5/8"	4.06"	4.91"	10	10%
MP 0562	5/8"	4.55"	5.41"	10	10%
MP 0612	5/8"	5.03"	5.90"	10	10%

Pinch/Crimp Clamps

Pinch Clamps are designed for quick, easy field installation on a wide range of common polyethylene and polybutylene tubings. Their single-ear crimp design ensures low-profile clamping and eliminates tag ends as found with traditional worm clamps. Constructed of 300 stainless steel with a 7mm band width. Ideal for irrigation systems, turf sprinklers, and other low-pressure water service applications.



Sold ONLY in Bags of 100 Clamps

Part No.	Nominal Dia.	I.D. Range	Std. Pkg.
MP 6119	3/4"	0.67" to 0.78"	100
MP 6121	13/16"	0.72" to 0.83"	100
MP 6125	1"	0.90" to 1.00"	100
MP 6127	1-1/16"	0.95" to 1.07"	100
MP 6131	1-1/4"	1.12" to 1.24"	100
MP 6133	1-5/16"	1.18" to 1.30"	100
MP 6134	1-3/8"	1.24" to 1.36"	100
MP 6141	1-5/8"	1.49" to 1.61"	100
MP 6142	1-11/16"	1.55" to 1.67"	100
MP 6148	1-7/8"	1.79" to 1.91"	100

Quantity Discount: 20% on 10 Bags (1000 Clamps) of One Size.