

Gasoil Thread & Gasket Sealer



2J

No. 2J is a general purpose, lead-free, thread and gasket sealer. Non-toxic, gray paste. Readily adheres to iron, stainless steel, aluminum, plastics and rubber compounds. Can be used with diluted acids, solvents, ammonia, dilute alkalis, chlorine, diesel fuel, gasoline, kerosene, jet fuel, LPG, Natural Gas, butane, hydraulic oils, refrigerants and steam. **Not for Oxygen.** Rated from -100° to +600° F. Pressures to 10,000 PSI liquids and 3,000 PSI gases. UL classified. Sold in 1/4 pint cans with brush applicator.

Part No.	Container	* Std. Pkg.
CR 2J	Thread & Gasket Sealer 1/4 Pint	24

*** Standard Packages Qualify for 10% Discount**

Gasoil Teflon Thread Sealer

No. SS08 is a soft-setting, non-toxic, Teflon sealer paste. Provides a positive seal on threads, joints, fittings, hoses, nozzles, hydraulic fittings, plugs, couplings, etc. Can be used with brass, copper, stainless, CPVC, PVC, nylon, polyethylene and polypropylene. Excellent resistance to solvents, kerosene, diesel, propane, butane, LPG, ammonia, acids, steam, compressed air and gasoline up to 20% blends. **Not for Oxygen.** Rated from -100° to +600° F. Pressures to 10,000 PSI liquids and 3,000 gases.



Part No.	Container	* Std. Pkg.
CR SS08	Teflon Thread Sealer 1/2 Pint	24

*** Standard Packages Qualify for 10% Discount**

Anaerobic Thread Sealant with Teflon



Tough, insoluble, vibration-proof, anaerobic FasSeal-ATS forms a leak-free seal even on miscut threads. This product delivers a high-speed cure on inactive metals such as stainless steel and monel and a super fast cure on conventional materials such as carbon steel and brass.

FasSeal-ATS is resistant to petroleum, butane, propane, natural gas, water, steam, refrigerants, chlorine, caustic sodas, acids, oils, gasoline and more.

Temperature Ranges: -65° to +400° F.

Pressure Ranges: 10,000 PSI, 250 PSIG steam at 400° F.

From Seal to Operating Pressure: Carbon and most other steel + 30 minutes. Stainless Steel + 3 hours.

Part No.	Anaerobic Thread Sealant
CR AS25	250ML Tube - 8.45 oz.

L-P Seal Anti-Seize Compound



An excellent pipe and fittings anti-seize sealant for NH3, LPG, gas, water, air, acids, alkali fuel and oils. Metallic lead sealer and lubricant. Non-seizing, non-galling, non-corrosive. Effective for pressures to 20,000 PSI. Unaffected by high or low temperatures. 1 lb. container.



Part No.	L-P Seal, Anti-Seize, 1 lb.
CN LP1	



Pipe Thread Compounds

Can Be Used on Galvanized Steel, Iron, Brass, Copper, Aluminum, Stainless, Polyethylene, Fiberglass & PVC.



No. 5 Off Yellow

#5 and #21 Multi-Purpose Lead-Free Sealants. Soft-set, slow drying compounds which seal, lubricate and protect threaded pipe and fittings. Can be used on galvanized steel, iron, brass, copper, aluminum, stainless, polyethylene, fiberglass and PVC. (Not for ABS or CPVC). Rated to 12,000 PSI liquids and 2,600 PSI gas. Brushable from +20° to +140° F.



No. 21 Black

Both products can be used with diluted acids, ammonia, diesel fuel, gasoline, 10% gasohol, hydraulic oils, jet fuel, kerosene, LP gas, nitrogen gas, petroleum solvents, compressed air and hot or cold water.

Both products are available in 1/2 pint or 1 pint cans with brush top lids. #5 is an off-yellow color and #21 is black.



Part No.	Product	Can Size	* Std. Pkg.
RS 25551	#5 Yellow	1/2 Pt.	24
RS 25431	#5 Yellow	1 Pt.	12
RS 28651	#21 Black	1/2 Pt.	24
RS 28541	#21 Black	1 Pt.	12

Extra 10% Discount If Ordered In Standard Packs.

Rectorseal Thread Sealant

#7 Multi-Purpose, Lead-Free Sealant is designed for use with chemicals, concentrated acids, concentrated caustics, oils, diesel, gasoline, 10% gasohol, alcohol, ethylene glycol, ammonia, glycerine, inert gases, jet fuel, kerosene, LP gases, nitrogen, petroleum solvents, compressed air and water.

Soft-set, medium dry formula is for use on threaded galvanized steel, iron, brass, copper, aluminum and stainless steel. Impervious to freeze damage. Rated to 12,000 PSI liquid and 2,600 PSI gas. Available in 1 pint, brush top cans.



Part No.	Product	Can Size	* Std. Pkg.
RS 17432	#7 Thread Sealant	1 Pt.	12

*** Extra 10% Discount If Ordered In Standard Packs.**

Tru-Blu™ Thread Sealant



Tru-Blu™ Lead-Free Thread Sealant includes PTFE to enhance thread lubrication during assembly and break out. Specially designed for high vibration and thermal expansion.

Can be used with lines carrying diluted acids, compressed air, ammonia, diluted caustics, oils, diesel, gasoline, jet fuel, kerosene, natural gas, Freon, solvents, soaps, steam and water. For use on threaded galvanized steel, iron, brass, copper, aluminum, stainless, polyethylene, fiberglass, PVC and CPVC. Brushable from +20° to +140° F. Available in 1-3/4 oz. tube or 1/2 pint with brush lid.



Part No.	Container	* Std. Pkg.
RS 31780	1-3/4 oz. Tube	24
RS 31551	1/2 Pt. Can	24

*** Extra 10% Discount If Ordered In Standard Packs.**