



QJ364

Nozzle Assemblies Less Caps

QJ360 Nozzle Assemblies for Wet or Dry Booms

Available in 3, 4 or 5 nozzle style with Viton® diaphragm. Pressures to 300 psi, opens at 10 psi. 2.25 GPM @ 5 PSI and 3.20 GPM at 10 PSI. Maximum Temperature is 125° F.

For wet pipe booms use either 3/4" or 1". For dry booms always use the 3/4NYB version and add the 1/2", 3/4" or 1" single or double hose connectors. For dry boom mounting use QJ Round or Square Vari-Spacing clamps on adjacent page.

Standard Check Pressure is 10 PSI. (2, 5, 8, 15 & 20 PSI also available)



QJ365



QJ363

CP38936NYB
CP38938NYB
CP38940NYB



CP38937NYB
CP38939NYB
CP38941NYB


Part No.	Size	Description
SS QJ363-34NYBVI	* 3/4"	3-Nozzle Assembly, Viton®, Less Connector.
SS QJ363-1NYBVI	1"	3-Nozzle Assembly, Viton®, Less Connector.
SS QJ364-34NYBVI	* 3/4"	4-Nozzle Assembly, Viton®, Less Connector.
SS QJ364-1NYBVI	1"	4-Nozzle Assembly, Viton®, Less Connector.
SS QJ365-34NYBVI	* 3/4"	5-Nozzle Assembly, Viton®, Less Connector.
SS QJ365-1NYBVI	1"	5-Nozzle Assembly, Viton®, Less Connector.
SS CP38936NYB	1/2"	Single Hose Connector w/ 3/8" Inlet Port
SS CP38938NYB	3/4"	Single Hose Connector w/ 3/8" Inlet Port
SS CP38940NYB	1"	Single Hose Connector w/ 3/8" Inlet Port
SS CP38937NYB	* 1/2"	Double Hose Connector w/ 3/8" Inlet Port....
SS CP38939NYB	3/4"	Double Hose Connector w/ 3/8" Inlet Port
SS CP38941NYB	1"	Double Hose Connector w/ 3/8" Inlet Port
SS 21953VI	-	Viton® Diaphragm
SS CP21953-EPR	-	EPDM Diaphragm
SS 58140	-	Manual Nozzle Shut-Off

* Use on Hose Fed Dry Booms & Add Connections.

Diaphragm Check Valves

- Side Style -

- Standard Check Pressure is 10 PSI. (2, 5, 8, 15 & 20 PSI also available)
- Viton® Diaphragm
- 300 PSI Maximum Pressure
- Max Temperature is 125° F.
- #8360 Flow Rate is 2.25 GPM @ 5 PSI Drop



QJ8360NYB
Check Valve Adapter
11/16/16F x QuickJet



QJ8360NYB
Diaphragm Check Valve



4241N-B121S
Diaphragm Check Valve


Shown with QuickJet Cap & Nozzle- Has 1/4" MPT

Part No.	Description
SS QJ8360NYB	Diaphragm Check Valve with 1/4" MPT Inlet
SS QJ8360NYB	Diaphragm Check Valve with 11/16"-16 Inlet
TW 4241N-B121S	Diaphragm Check Valve (EPDM) with 3/8" HB Inlet
SS 21953VI	Diaphragm (Viton®) for Check Valve.....
SS CP21953-EPR	Diaphragm (EPDM) for Check Valve.....
SS 19191EPR	Gasket for QJT as extra
SS 58140	Manual Nozzle Shut-Off

Note: 21950-2,5,8,15,20NYB End Caps Available.


Hose Shank Bodies

- 125 PSI -




18635-3/8
18638-1/2
18719-3/4

Single Hose Shank Body-1/2 or 3/4" Barb



18636-3/8
18639-1/2
18720-3/4

Double Hose Shank Body-1/2 or 3/4" Barbs



18637-3/8
18640-1/2
18721-3/4

Triple Hose Shank Body-1/2 or 3/4" Barbs

Maximum Temperature is 125° F.

Part No.	Description
SS 18635-3/8	Single Shank Body, 3/8", Hose
SS 18638-1/2	Single Shank Body, 1/2", Hose
SS 18719-3/4	Single Shank Body, 3/4", Hose
SS 18636-3/8	Double Shank Body, 3/8", Hose
SS 18639-1/2	Double Shank Body, 1/2", Hose
SS 18720-3/4	Double Shank Body, 3/4", Hose
SS 18637-3/8	Triple Shank Body, 3/8", Hose
SS 18640-1/2	Triple Shank Body, 1/2", Hose
SS 18721-3/4	Triple Shank Body, 3/4", Hose

Viton® is a registered trademark of DuPont Performance Elastomers

Diaphragm Check Valves

- Top Style -

Low profile design allows maximum protection against damage. Drip-Free shutoff. Opens at 10 PSI. Standard Viton® diaphragm. Pressure to 125 PSI. Standard check pressure is 10 PSI. (2, 5, 8, 15 & 20 PSI also available). 3.5 GPM @ 5 PSI. Maximum Temperature is 125° F.



22251

Diaphragm Check



22252

Diaphragm Check

Part No.	Description
SS 22251-3/8	Single Shank Check Valve, 3/8" Hose
SS 22251-1/2	Single Shank Check Valve, 1/2" Hose
SS 22251-3/4	Single Shank Check Valve, 3/4" Hose
SS 22252-3/8	Double Shank Check Valve, 3/8" Hose
SS 22252-1/2	Double Shank Check Valve, 1/2" Hose
SS 22252-3/4	Double Shank Check Valve, 3/4" Hose
SS 21953VI	Diaphragm (Viton®) for Check Valve
SS CP21953-EPR	Diaphragm (EPDM) for Check Valve
SS 58140	Manual Nozzle Shut-Off

Note: 21950-2,5,8,15,20NYB End Caps Available.

Check Valves - Side Style

19351 Triple Check Valve



19350 Double Check Valve



19349 Single Check Valve



- Standard Check Pressure is 10 PSI. (2, 5, 8, 15 & 20 PSI also available)
- Viton® Diaphragm
- 125 PSI Maximum Pressure
- Maximum Temperature is 125° F.

Part No.	Description
SS 19349-3/8	Single Shank Check Valve, 3/8" Hose
SS 19349-1/2	Single Shank Check Valve, 1/2" Hose
SS 19349-3/4	Single Shank Check Valve, 3/4" Hose
SS 19350-3/8	Double Shank Check Valve, 3/8" Hose
SS 19350-1/2	Double Shank Check Valve, 1/2" Hose
SS 19350-3/4	Double Shank Check Valve, 3/4" Hose
SS 19351-3/8	Triple Shank Check Valve, 3/8" Hose
SS 19351-1/2	Triple Shank Check Valve, 1/2" Hose
SS 19351-3/4	Triple Shank Check Valve, 3/4" Hose
SS 21953VI	Diaphragm (Viton®) for Check Valve
SS CP21953-EPR	Diaphragm (EPDM) for Check Valve
SS 58140	Manual Nozzle Shut-Off

Note: 21950-2,5,8,15,20NYB End Caps Available.


Split Eyelets

- Side Style & Top Style -



QJ17560

- 2.25 GPM
- Standard Check Pressure is 10 PSI. 2, 5, 8, 15 & 20 PSI are also available
- Viton® Diaphragm
- 300 PSI Maximum Pressure
- Requires 3/8" Hole in Pipe
- Caps, Nozzles, Gaskets Not Included (See other pages).



QJ22187

Part No.	Description
SS QJ17560-1/2	Split-Eyelet Check Valve for 1/2" Pipe
SS QJ17560-3/4	Split-Eyelet Check Valve for 3/4" Pipe
SS QJ17560-1	Split-Eyelet Check Valve for 1" Pipe
SS QJ22187-3/4	Split-Eyelet Check Valve for 3/4" Pipe
SS QJ22187-1	Split-Eyelet Check Valve for 1" Pipe
SS 21953VI	Diaphragm (Viton®)
SS CP21953-EPR	Diaphragm (EPDM)
SS 21950-2NYB	Diaphragm End Cap, 2 PSI, Black
SS 21950-5NYB	Diaphragm End Cap, 5 PSI, Black
SS 21950-8NYB	Diaphragm End Cap, 8 PSI, Black
SS 21950-8NYB-BL	Diaphragm End Cap, 8 PSI, Blue
SS 21950-10NYB	Diaphragm End Cap, 10 PSI, Black
SS CP25611	QuickJet Cap for 01-08 Orifices, Less Gasket
SS CP25609	QuickJet Cap for 10-20 Orifices, Less Gasket

CP25609
Nozzle Cap