

TIP COLOR	TIP NO. (Strainer Screen Size)		Liquid Pressure in PSI	Capacity 1 Nozzle in GPM	Drop Size		Gallon Per Acre 20" SPACING				Gallon Per Acre 30" SPACING			
	80° SERIES	110° SERIES			80°	110°	5 MPH	6 MPH	7 MPH	8 MPH	5 MPH	6 MPH	7 MPH	8 MPH
	Orange	XR8001 (100 Mesh)			XR1101VS (100 Mesh)	15 20 30 40 60	.06 .07 .09 .10 .12	F F F F VF	F F F F VF	3.6 4.2 5.1 5.9 7.3	3.0 3.5 4.3 5.0 6.1	2.6 2.6 3.7 4.2 4.6	2.3 2.6 3.2 3.7 4.6	2.4 2.8 3.4 4.0 4.9
Green	XR8001VS (100 Mesh)	XR110015VS (100 Mesh)	15 20 30 40 60	.09 .11 .13 .15 .18	M F F F F	F F F F F	5.5 6.3 7.7 8.9 10.9	4.5 5.3 6.4 7.4 9.1	3.9 4.5 5.5 6.4 7.8	3.4 3.9 4.8 5.6 6.8	3.6 4.2 5.1 5.9 7.3	3.0 3.5 4.3 5.0 6.1	2.6 2.6 3.2 3.7 4.6	2.3 2.6 3.2 3.7 4.6
Yellow	XR8002 (50 Mesh)	XR11002VS (50 Mesh)	15 20 30 40 60	.12 .14 .17 .20 .25	M M F F F	M F F F F	7.3 8.4 10.3 11.9 14.6	6.1 7.0 8.6 9.9 12.1	6.1 6.0 6.4 7.4 10.4	5.2 5.3 6.4 7.4 9.1	4.5 4.8 5.6 6.4 7.9	4.0 4.7 5.7 6.6 8.1	3.5 3.5 4.0 4.9 6.1	3.0 3.5 4.3 5.0 6.1
Blue	XR8003 (50 Mesh)	XR11003VS (50 Mesh)	15 20 30 40 60	.18 .21 .26 .30 .37	M M F F F	M M F F F	10.9 12.6 15.4 17.8 22	9.1 10.5 12.9 14.9 18.2	7.8 9.0 11.0 12.7 15.6	6.8 7.9 9.7 11.1 13.6	7.3 8.4 10.3 11.9 14.6	6.1 7.0 8.6 9.5 12.1	5.2 6.0 7.4 8.5 10.4	4.5 5.3 6.4 7.4 9.1
Red	XR8004 (50 Mesh)	XR11004VS (50 Mesh)	15 20 30 40 60	.24 .28 .35 .40 .49	C M M M F	M M M M F	14.5 16.8 21 24 29	12.1 14.0 17.2 19.8 24	10.4 12.0 14.7 17.0 21	9.1 10.5 12.9 14.9 18.2	9.7 11.2 13.7 15.8 19.4	8.1 9.3 11.4 13.2 16.2	6.9 8.0 9.8 11.3 13.9	6.1 7.0 8.6 9.9 12.1
Brown	XR8005 (50 Mesh)	XR11005VS (50 Mesh)	15 20 30 40 60	.31 .35 .43 .50 .61	C C M M F	M M M M F	18.2 21 26 30 36	15.2 17.5 21 25 30	13.0 15.0 18.4 21 26	11.4 13.1 16.1 18.6 23	12.1 14.0 17.2 19.8 24	10.1 11.7 14.3 16.5 20	8.7 10.0 12.3 14.1 17.3	7.6 8.8 10.7 12.4 15.2
Gray	XR8006 (50 Mesh)	XR11006VS (50 Mesh)	15 20 30 40 60	.37 .42 .52 .60 .74	C C M M F	C M M M F	22 25 31 36 44	19.2 21 26 30 36	15.6 18.0 22 25 31	13.6 15.8 19.3 22 27	14.5 16.8 21 24 29	12.1 14.0 17.2 19.8 24	10.4 12.0 14.7 17.0 21	9.1 10.5 12.9 14.9 18.2
White	XR8008 (50 Mesh)	XR11008VS (50 Mesh)	15 20 30 40 60	.49 .57 .69 .80 .98	VC VC M M M	C C M M M	29 34 41 48 58	24 28 34 40 49	21 24 29 34 42	18.2 21 26 30 36	19.4 22 27 32 39	16.2 18.7 23 26 32	13.9 16.0 19.6 23 28	12.1 14.0 17.2 19.8 24
Stainless Steel	XR8010SS (50 Mesh)	XR11010SS (50 Mesh)	15 20 30 40 60	.61 .71 .87 1.00 1.23	XC VC C C C	VC C C C M	36 42 51 59 73	30 35 43 49 61	26 30 37 42 52	23 26 32 37 45	24 28 34 40 49	20 23 29 33 40	17.3 20 25 28 35	15.2 17.5 21 25 30
Stainless Steel	XR8015SS (50 Mesh)	XR11015SS (50 Mesh)	15 20 30 40 60	.92 1.06 1.30 1.50 1.84	XC XC VC VC C	VC VC VC VC C	55 63 77 89 109	45 53 64 74 91	39 45 55 64 78	34 39 48 56 68	36 42 51 59 73	30 35 43 50 61	26 30 37 42 52	23 26 32 37 45
XRC Polymer	XR8102VP (20 Mesh)	XR11020VP (20 Mesh)	15 20 30 40 60	1.22 1.41 1.73 2.00 2.45	XC XC VC VC VC	XC VC VC VC VC	72 84 103 119 146	60 70 86 99 121	51 60 74 85 104	45 52 64 74 91	48 56 69 79 97	40 47 57 66 81	34 40 49 57 69	30 35 43 49 61

F = Fine VF = Very Fine M = Medium C = Coarse VC = Very Coarse XC = Extra Coarse - Larger Droplets for Best Drift Control

<b>Part No.</b>	<b>Pkg.</b>
SS XRC11001VS thru SS XRC11008VS	Nozzle/Cap Assembly with EPDM Gasket..... 25
SS XRC80015VS thru SS XRC8006VS	Nozzle/Cap Assembly with EPDM Gasket..... 25
SS XRC11002VK thru SS XRC11008VK	Ceramic Nozzle & Cap Assembly with EPDM Gasket 25
SS XRC11002VP thru SS XRC11020VP	Polymer Nozzle & Cap Assembly with EPDM Gasket 25

**TeeJet XR TeeJet®**

## Extended Range Flat Spray Tips

**Stainless • Ceramic • Polymer**

XR Extended Range TeeJets are the best selection for Pre-Emergence Surface Applied Herbicides at 20-30 psi or Post-Emergence Systemic Herbicides at 15-20 psi. Can also be used for Post Emergence Contact Herbicides at 30-60 psi or Pre-Plant incorporated products at 15-20 psi. Maximum temperature is 125° F.

At 15 PSI At 60 PSI

**XR Tips** have excellent pattern distribution at 15 to 60 psi. Drift is minimized at lower pressures and coverage is good at high pressure. Available in 80 or 110 degree patterns. **VS Tips:** Sizes 1 through 8 are color-coded with a stainless insert.

**XRC Nozzle Cap Assembly with Gasket**

**All Sizes Suitable with PWM Spray Systems**

**VK Tips:** Sizes 2 through 8 are color-coded with a ceramic insert. Larger sizes are all stainless.

**VSTips:** Color coded polymer with a stainless insert.

**VP Tips:** All polymer material.

<b>Part No.</b>	<b>XR Color Coded Tips</b>
SS XR8001VS thru SS XR8008VS	
SS XR8002VK thru SS XR8008VK	
SS XR11001VS thru SS XR11008VS	
SS XR11002VK thru SS XR11008VK	
<b>XR All Stainless Steel Tips</b>	
SS XR8010SS thru SS XR8015SS	
SS XR11010SS thru SS XR11015SS	
<b>XR All Polymer Tips</b>	
SS XR110015VP thru SS XR11008VP	

10% Quantity Discount on 50+ Of One Size

TIP COLOR	TIP NO. (Strainer Screen Size)		Liquid Pressure in PSI	Capacity 1 Nozzle in GPM	Drop Size		Gallon Per Acre 20" SPACING				Gallon Per Acre 30" SPACING			
	80° SERIES	110° SERIES			80°	110°	5 MPH	6 MPH	7 MPH	8 MPH	5 MPH	6 MPH	7 MPH	8 MPH
	Orange	8001VS (100 Mesh)			11001VS (100 Mesh)	30 35 40 45 60	.09 .09 .10 .11 .12	F F F VF VF	F F F VF VF	5.1 5.6 5.9 6.3 7.3	4.3 4.6 5.0 5.3 6.1	3.7 4.0 4.2 4.5 5.2	3.2 3.5 3.7 3.9 4.6	3.4 3.7 4.0 4.2 4.9
Green	80015VS (100 Mesh)	110015VS (100 Mesh)	30 35 40 45 60	.13 .14 .15 .16 .18	F F F F F	F F F F F	7.7 8.3 8.9 9.5 10.9	6.4 6.9 7.4 7.9 9.1	5.5 6.0 6.4 6.8 7.8	4.8 5.2 5.6 5.9 6.8	5.1 5.6 6.4 7.3 8.8	4.3 4.6 5.0 5.3 6.1	3.7 4.0 4.3 4.9 5.2	3.2 3.5 3.7 4.3 4.6
Yellow	8002VS (50 Mesh)	11002VS (50 Mesh)	30 35 40 45 60	.17 .19 .20 .21 .25	M M F F F	M F F F F	10.3 11.1 11.9 12.6 14.6	8.6 9.3 9.9 10.5 12.1	7.4 7.9 8.5 9.0 10.4	6.4 6.9 7.4 7.9 9.1	6.9 7.4 7.9 8.4 9.7	5.7 6.2 6.6 7.0 8.1	4.9 5.3 5.7 6.0 6.9	4.3 4.6 5.0 5.3 6.1
Blue	8003VS (50 Mesh)	11003VS (50 Mesh)	30 35 40 45 60	.26 .28 .30 .32 .37	M M M M F	M F F F F	15.4 16.7 17.8 18.9 22	12.9 13.9 14.9 15.8 18.2	11.0 11.9 12.7 13.5 15.6	9.7 10.4 11.1 11.8 13.6	10.3 11.1 11.9 12.6 14.6	8.6 9.3 9.9 10.5 12.1	6.9 7.9 8.5 9.0 10.4	6.4 6.9 7.4 7.9 9.1
Red	8004VS (50 Mesh)	11004VS (50 Mesh)	30 35 40 45 60	.35 .37 .40 .42 .49	M M M M F	M M M M F	21 22 24 25 29	17.2 18.5 19.8 21 24	14.7 15.9 17.0 18.0 21	12.9 13.9 14.9 15.8 18.2	13.7 14.8 15.8 16.8 19.4	11.4 12.3 13.2 14.0 16.2	9.8 10.6 11.3 12.0 13.9	8.6 9.3 9.9 10.5 12.1
Brown	8005VS (50 Mesh)	11005VS (50 Mesh)	30 35 40 45 60	.43 .47 .50 .53 .61	C M M M F	M M M M F	26 28 30 32 36	24 25 26 26 30	18.4 19.8 21 23 26	16.1 17.4 18.6 19.7 23	17.2 18.5 19.8 21 24	14.3 15.4 16.5 17.5 20	13.9 15.2 16.5 18.0 21.3	10.7 11.6 12.4 13.1 15.2
Gray	8006VS (50 Mesh)	11006VS (50 Mesh)	30 35 40 45 60	.52 .56 .60 .64 .74	C C C C C	M M M M M	31 33 36 38 44	26 28 30 32 36	22 24 25 27 31	19.3 21 22 24 27	21 22 24 25 29	17.2 18.5 19.8 21 24	14.7 15.9 17.0 18.0 21.3	12.9 13.9 14.9 15.8 18.2
White	8008VS (50 Mesh)	11008VS (50 Mesh)	30 35 40 45 60	.69 .75 .80 .85 .98	C C C C M	C C C C M	41 44 48 50 58	34 37 40 42 49	29 32 34 36 42	26 28 30 32 36	27 30 32 34 39	23 25 26 28 32	19.6 21 23 24 28	17.2 18.5 19.8 21 24

F = Fine VF = Very Fine M = Medium C = Coarse VC = Very Coarse - Larger Droplets for Best Drift Control

**VisiFlo TeeJet®**

## Color-Coded Flat Spray Tips

**VS Style - Stainless**

Flat Spray Tips are a good selection for pre-emergence surface applied herbicide at minimum pressure of 30 PSI to provide medium size droplets for good soil coverage. Good selection for post emergence contact herbicides at 40 PSI and higher to provide good canopy penetration and small droplets for better foliage coverage. Maximum temperature is 125° F.

These flat spray tips have a tapered edge flat spray pattern for uniform coverage in broadcast spraying. Available in VisiFlo Color-coded Stainless Steel in 80° spray angles in selected sizes. See Chart for Ordering.

**WHEN ORDERING SPECIFY TIP No.:**  
**Example:** 8002VS - Stainless Steel with VisiFlo color-coding

<b>Part No.</b>	<b>VisiFlo Spray Tips</b>
SS TP8001VS thru TP8008VS	Stainless
SS TP11001VS thru TP11008VS	Stainless
<b>TeeJet Packaged in 25's.</b>	
10% Quantity Discount on 50+ Of One Size	