

Turbo TeeJet™ Polymer Flat Spray Tips



TT Nozzle Combo with Tip, Cap & EPDM Gasket

- Tapered edge, wide angle flat pattern for uniform coverage in broadcast spraying.
- Large, round free passages to minimize clogging. 110° Spray pattern.
- Excellent resistance to corrosive solutions.
- Larger droplets for less drift.
- Automatic spray alignment with CP25611 Quick TeeJet® cap.
- Use CP114501 Cap for 10 & 12 Sizes.
- All sizes suitable with PWM Spray Systems.



TIP COLOR	TIP NO. Strainer Screen Size	Liquid Pressure in PSI	Capacity 1 Nozzle in GPM	Drop Size	GALLON PER ACRE 20' SPACING						GALLON PER ACRE 30' SPACING							
					5 MPH	6 MPH	7 MPH	8 MPH	5 MPH	6 MPH	7 MPH	8 MPH						
Orange	TT11001VP (100 Mesh)	15	0.061	C	3.6	3.0	2.6	2.3	2.4	2.0	1.7	1.5						
		20	0.071	C	4.2	3.5	3.0	2.6	2.8	2.3	2.0	1.8						
		30	0.087	M	5.2	4.3	3.7	3.2	3.4	2.9	2.5	2.2						
		40	0.10	M	5.9	5.0	4.2	3.7	4.0	3.3	2.8	2.5						
		50	0.11	M	6.5	5.4	4.7	4.1	4.4	3.6	3.1	2.7						
		60	0.12	F	7.1	5.9	5.1	4.5	4.8	4.0	3.4	3.0						
Green	TT110015VP (100 MESH)	15	0.09	VC	5.3	4.5	3.8	3.3	3.6	3.0	2.5	2.2						
		20	0.11	C	6.5	5.4	4.7	4.1	4.4	3.6	3.1	2.7						
		30	0.13	M	7.7	6.4	5.5	4.8	5.1	4.3	3.7	3.2						
		40	0.15	M	8.9	7.4	6.4	5.6	5.9	5.0	4.2	3.7						
		50	0.17	M	10.1	8.4	7.2	6.3	6.7	5.6	4.8	4.2						
		60	0.18	F	10.7	8.9	7.6	6.7	7.1	5.9	5.1	4.5						
Yellow	TT11002VP (50 MESH)	15	0.12	VC	7.1	5.9	5.1	4.5	4.8	4.0	3.4	3.0						
		20	0.14	C	8.3	6.9	5.9	5.2	5.5	4.6	4.0	3.5						
		30	0.17	M	10.1	8.4	7.2	6.3	6.7	5.6	4.8	4.2						
		40	0.20	M	11.9	9.9	8.5	7.4	7.9	6.6	5.7	5.0						
		50	0.22	M	13.1	10.9	9.3	8.2	8.7	7.3	6.2	5.4						
		60	0.25	M	14.9	12.4	10.6	9.3	9.9	8.3	7.1	6.2						
Violet	TT110025VP (50 MESH)	15	0.15	VC	8.9	7.4	6.4	5.6	5.9	5.0	4.2	3.7						
		20	0.17	C	10.7	8.9	7.6	6.7	7.1	5.9	5.1	4.5						
		30	0.22	M	13.1	10.9	9.3	8.2	8.7	7.3	6.2	5.4						
		40	0.25	M	14.9	12.4	10.6	9.3	9.9	8.3	7.1	6.2						
		50	0.28	M	16.6	13.9	11.9	10.4	11.1	9.2	7.9	6.9						
		60	0.31	M	18.4	15.3	13.2	11.5	12.3	10.2	8.8	7.7						
Blue	TT11003VP (50 MESH)	15	0.18	VC	10.7	8.9	7.6	6.7	7.1	5.9	5.1	4.5						
		20	0.21	C	12.5	10.4	8.9	7.8	8.3	6.9	5.9	5.2						
		30	0.26	M	15.4	12.9	11.0	9.7	10.3	8.6	7.4	6.4						
		40	0.30	M	17.8	14.9	12.7	11.1	11.9	9.9	8.5	7.4						
		50	0.34	M	20.2	16.8	14.4	12.6	13.5	11.2	9.6	8.4						
		60	0.37	M	22.0	18.3	15.7	13.7	14.7	12.2	10.5	9.2						
Red	TT11004VP (50 MESH)	15	0.24	XC	14.3	11.9	10.2	8.9	9.5	7.9	6.8	5.9						
		20	0.28	VC	16.6	13.9	11.9	10.4	11.1	9.2	7.9	6.9						
		30	0.35	C	20.8	17.3	14.9	13.0	13.9	11.6	9.9	8.7						
		40	0.40	M	23.8	19.8	17.0	14.9	15.8	13.2	11.3	9.9						
		50	0.45	M	26.7	22.3	19.1	16.7	17.8	14.9	12.7	11.1						
		60	0.49	M	29.1	24.3	20.8	18.2	19.4	16.2	13.9	12.1						
Brown	TT11005VP (50 MESH)	15	0.31	XC	18.4	15.3	13.2	11.5	12.3	10.2	8.8	7.7						
		20	0.35	VC	21.7	17.9	15.3	13.3	14.1	11.6	9.9	8.7						
		30	0.43	C	25.5	21.3	18.2	16.0	17.0	14.2	12.2	10.6						
		40	0.50	M	29.7	24.8	21.2	18.6	19.8	16.5	14.1	12.4						
		50	0.56	M	33.3	27.7	23.8	20.8	22.2	18.5	15.8	13.9						
		60	0.61	M	36.2	30.2	25.9	22.6	24.2	20.1	17.3	15.1						
Grey	TT11006VP (50 MESH)	15	0.37	XC	22.0	18.3	15.7	13.7	14.7	12.2	10.5	9.2						
		20	0.42	VC	25.0	21.0	17.8	15.6	16.6	13.9	11.9	10.4						
		30	0.52	C	31.0	26.0	22.0	19.3	20.6	17.2	14.7	12.9						
		40	0.60	M	36.0	30.0	25.0	22.0	23.6	19.8	17.0	14.9						
		50	0.67	M	40.0	33.0	28.0	25.0	26.5	22.1	19.0	16.6						
		60	0.73	M	43.0	36.0	31.0	27.0	28.5	24.1	20.5	18.1						
White	TT11008VP (50 MESH)	15	0.49	XC	29.0	24.0	21.0	18.2	19.4	16.2	13.9	12.1						
		20	0.57	VC	34.0	28.0	24.0	21.0	22.6	18.5	16.1	14.1						
		30	0.65	C	41.0	34.0	29.0	26.0	27.3	22.5	19.5	17.1						
		40	0.80	M	48.0	40.0	34.0	30.0	31.7	26.0	22.4	19.2	16.8					
		50	0.89	M	53.0	44.0	38.0	33.0	35.2	29.4	25.2	22.0						
		60	0.98	M	58.0	49.0	42.0	36.0	38.8	32.5	27.7	26.3						
LT. Blue	TT11010VP (50 MESH)	15	0.61	UC	36.0	30.0	26.0	23.0	24.0	20.0	17.3	15.1						
		20	0.71	VC	42.0	35.0	30.0	26.0	28.0	23.0	20.0	17.6						
		30	0.87	C	52.0	43.0	37.0	32.0	34.0	29.0	25.0	22.0						
		40	1.00	M	59.0	50.0	42.0	37.0	40.0	33.0	28.0	25.0						
		50	1.12	M	67.0	55.0	48.0	42.0	44.0	37.0	32.0	28.0						
		60	1.22	M	72.0	60.0	52.0	45.0	48.0	40.0	35.0	30.0						
Raspberry Red	TT11012VP (50 MESH)	15	0.73	UC	43.0	36.0	-	27.0	-	-	-	-						
		20	0.85	VC	50.0	42.0	-	32.0	-	-	-	-						
		30	1.04	C	62.0	51.0	-	39.0	-	-	-	-						
		40	1.20	M	71.0	59.0	-	45.0	-	-	-	-						
		50	1.34	M	80.0	66.0	-	50.0	-	-	-	-						
		60	1.47	M	87.0	73.0	-	55.0	-	-	-	-						

F = Fine VF = Very Fine M = Medium C = Coarse VC = Very Coarse XC = Extremely Coarse

Part No.	Pkg.
SS TT11001VP thru 11008VP Turbo TeeJet Tip Only. Use with Cap CP25611	25
SS TT11010VP thru 11012VP Turbo TeeJet Tip Only. Use with Cap CP114501xxx	25
SS TT11001-VP-CE thru 11008-VP-CE Nozzle Assembly, Tip, Cap & EPR Gasket	25
SS TT11010-VP-CE thru 11012-VP-CE Nozzle Assembly, Tip, Cap & EPR Gasket	25

10% Quantity Discount on 50+ Of One Size

Turbo TeeJet Induction Tips

TTI Features:

- All acetal construction for excellent chemical and wear resistance.
- Removable pre-orifice for fast and easy cleaning.
- Large, round passages to minimize plugging.
- Tapered flat 110° spray pattern.
- Large droplets are produced through a venturi air aspirator resulting in less drift.
- Pressure Range: 15-100 PSI.
- Use CP25597 Quick TeeJet® cap.
- Use CP114501 Cap for 08 & 10 Sizes.
- All sizes suitable with PWM Spray Systems.



TTI Nozzle Combo with Tip, Cap & EPDM Gasket

TIP COLOR	TIP NO. Strainer Screen Size	Liquid Pressure in PSI	Capacity 1 Nozzle in GPM	Drop Size	GALLON PER ACRE 20' SPACING						GALLON PER ACRE 30' SPACING						
					5 MPH	6 MPH	7 MPH	8 MPH	5 MPH	6 MPH	7 MPH	8 MPH					
Green	TT1110015VP (100 MESH)	15	0.09	UC	5.3	4.5	3.8	3.3	3.6	3.0	2.5	2.2					
		20	0.11	UC	6.5	5.4	4.7	4.1	4.4	3.6	3.1	2.7					
		30	0.13	UC	7.7	6.4	5.5	4.8	5.1	4.3	3.7	3.2					
		40	0.15	UC	8.9	7.4	6.4	5.6	5.9	5.0	4.2	3.7					
		50	0.17	UC	10.1	8.4	7.2	6.3	6.7	5.6	4.8	4.2					
		60	0.18	XC	10.7	8.9	7.6	6.7	7.1	5.9	5.1	4.5					
Yellow	TT111002VP (50 MESH)	15	0.12	UC	7.1	5.9	5.1	4.5	4.8	4.0	3.4	3.0					
		20	0.14	UC	8.3	6.9	5.9	5.2	5.5	4.6	4.0	3.5					
		30	0.17	UC	10.1	8.4	7.2	6.3	6.7	5.6	4.8	4.2			</		