


POL Filler Coupling

MALE POL	MALE NPT	LENGTH	TYPE NUMBER
Soft Nose	1/4"	6"	M390#

#Replacement O-ring T12945



Filler Valve Adapter



Allows methanol to be added through conventional designed double back check filler valves with a 1-3/4" male Acme filler connection

FILLER VALVE CONNECTION	OUTLET CONNECTION	TYPE NUMBER
1-3/4" F. Acme	3/4" FNPT	M450A

Part No.
ST M390 POL Filler Coupling
ST M450A Filler Valve Adapter

Hose Inserts



HOSE CONNECTION I.D.	OTHER CONNECTION	TYPE NUMBER
1/4"	MPOL	M364


POL CONNECTION	OTHER CONNECTION	LENGTH	TYPE NUMBER
Straight MPOL	1/4" MNPT	2-3/8"	M318
		2-3/8"	M318
		2-9/16"	M388#
Angle MPOL	9/16"-18 LH	2-3/8"	M320
	1/4" MNPT	3"	M345

#Soft nose. Replacement O-ring T12945

Part No.
ST M318
ST M320
ST M345

Part No.
ST M364
ST M388

Swivel POL Adapters



Dust Seals & Plugs

M178 Series



SIZE, M. ACME	DUST SEAL (PLASTIC)
1-1/4"	M178
1-3/4"	M179
2-1/4"	M180
3-1/4"	M181

Female ACME Caps




M108 or M109 M431 Series

SIZE, F. ACME	PLASTIC	BRASS
1-1/4"	M108	-
1-3/4"	M109	-
2-1/4"	-	M431
3-1/4"	-	M441

Single Piece POL Adapters


POL CONNECTION	OTHER CONNECTION	TYPE NUMBER
Female POL	1/4" FNPT	M301
	1/2" FNPT	M303
	1/4" MNPT	M284
	3/8" MNPT	M285
	1/2" MNPT	M286
Male POL	3/4" MNPT	M287
	1/2" FNPT	M357
	3/8" SAE Flare	M353
	1/2" SAE Flare	M355



Part No.
ST M108
ST M109
ST M178
ST M179
ST M180
ST M181
ST M284
ST M285
ST M286


Part No.
ST M287
ST M301
ST M303
ST M353
ST M355
ST M357
ST M431
ST M441

Quick Closing Couplings



These units are installed on LP-Gas motor fuel lines, especially lift truck systems, to provide a quick closing coupling in the fuel line. The M220M goes on the service valve outlet,

while the M220F connects to the motor fuel line. Both couplings have an internal check valve that opens by attaching the two units together. When disconnected, spring force and pressure close the checks. A unique spring clip in the M220M Acme washer helps retain the washer when disconnecting from the M220F.



INLET CONNECTION	OUTLET CONNECTION	TYPE NUMBER
3/8" FNPT	1-1/4" M. Acme	M220M
1-1/4" F. Acme	1/4" FNPT	M220F

RK220M Replacement O-ring gasket.

Part No.
ST M220M
ST M220F
ST RK220M

Internal Spring Relief Valves



- Designed for AMSE Domestic Tanks
- Discharge Setting is 250 PSI (275 PSI Available)
- Protective Raincaps Included

Part No.	Size	Maximum Tank Size
ST H225-250	3/4"	250 Gallon
ST H250-250	1"	500 Gallon
ST H275-250	1-1/4"	1000 Gallon
ST H284-250	* 2"	30,000 Gallon

* 4 Required on 30,000 Gallon Tanks in manifold.

Used on DOT and ASME containers and for hydrostatic relief between shutoff valves in piping and liquid hoses. All working internal parts of these valves are outside the container connection so they should be protected against mechanical damage.

External Relief Valves



Raincap

FISHER

H110 Series



CONTAINER TYPE	START-TO-DISCHARGE SETTING, PSIG	CONTAINER CONNECTION MNPT	TYPE NUMBER	FLOW CAPACITY, SCFM AIR		ACCESSORIES (Order Separately)	
				U.L.	ASME	Pipeaway Adaptor	Raincap
ASME	250	1/4"	H110	310	-	-	-
	250	1/2"	H135	605	490	-	P206
	250	3/4"	H160	605	-	-	-
	275	3/4"	H185	2,210	1,694	-	P145

Part No.
ST H110 1/4".. External Relief Valve
ST H135 1/2".. External Relief Valve
ST H185 3/4".. External Relief Valve
ST P145 Rain Cap for 3/4".....
ST P206 Rain Cap for 1/4" & 1/2"...

SERVICE & REPAIRS

Did you know? We can service almost every brand of pump we sell in our catalog.



Call us at **1-800-228-9666** (Omaha, NE) for a quote!