

SUPREME Tank Gauges

A VAPOR-TIGHT, AUTOMATIC GAUGE FOR ANY FLUID COMMONLY STORED IN HORIZONTAL AND VERTICAL STORAGE TANKS



No Vapor Loss

Accurate

Easy to Install

Prevents Accidents

The **Supreme Tank Gauge** with its enclosed weather-proof structure is a complete vapor seal. It has no mechanical seals to wear out or to obstruct tape function. The reel assembly is actuated by a trouble-free spring mechanism which eliminates all slack in the measuring tape as it moves up and down with the float. The tape and its graduations are clearly visible through a window in the reel housing. **Note:** Pipe and pipe fittings required for installation.

Part No.	For Tanks	Float Material	Float Size
EF 1030	Up to 25'	Metal.....4" Dia.	
EF 1040	* Up to 25'	Stainless Steel.....4" Dia.	
EF 1130	25' to 35'	Metal.....4" Dia.	
EF 1140	* 25' to 35'	Stainless Steel.....4" Dia.	
EF RK25	Repair Kit for 1000 Series Gauges		
EF RK35	Repair Kit for 1100 Series Gauges		

* Use Stainless Float for corrosive liquids.

Golden Gauge

Top Mount Fuel Tank Gauge that has leak-proof construction. Dual threaded body will fit 1-1/2" or 2" female opening. Gauge reads in inches and will fit up to 72" diameter tank. **Note:** For tanks smaller than 72", adjust float to correct length. **Not for gasoline — Oil or Diesel Only.**



72GG

Part No.	Description
HS 72GG	72" Top Mount Gauge

Econ-O-Gauges

Models	Description
No. 7148	48"
No. 7164	64"



Top Mount Fuel Gauge that reads 1/4 - 1/2 - 3/4 - Full. Has dual threader body that will fit 1-1/2" or 2" female opening for either 48" or 64" diameter tank. **Note:** Other sizes also available.

Part No.	Tank Diameter
HS 7148	48"
HS 7164	64"
HS 7165	Plastic Gauge Vial

Magnetic Liquid-Level Gauges for Farm Tanks

These Lever Action Gauges are designed primarily for use in stationary horizontal cylindrical farm tanks or tanks with flat heads. They are to be mounted on the centerline in the middle of the head. 1-1/2" MNPT. Will fit tanks up to 64" in diameter. The float and assembly are shipped unassembled. The float rod is cut to the proper length for each size tank, notched, then inserted into the sleeve attached to the short section of lever rod, and crimped for firm retention.



Part No.	Description
HS F7183	1-1/2" ROTARY GAUGE For 300, 520 & 1000 Gallon Tanks..
HS 5-605	Replacement Dial for rotary gauge..

Elevated Fuel Tanks



ET14 Fitting & Hose Carton For Elevated Tanks Include:

- 2" Hinged Filler Cap
- 1" x 12' Farm Fuel Hose
- 1" Nozzle
- 1" Locking Valve
- 1-1/2" Black Pipe Plug

Elevated Fuel Tanks have a threaded opening in the center of the head for a Magnetic Fuel Gauge, which is optional at extra cost. The bottom of the tank is 84" above the ground. Tank has 1"-2" Fitting for fill. **PAINTED RED.**

Part No.	Description
HS 300P	TANKS ONLY 300-Gallon, 14 Gauge, 38" x 61"
HS 520P	520-Gallon, 14 Gauge, 50" x 61"
HS 84-300	STANDS ONLY For 300-Gallon Tank
HS 84-520	For 520-Gallon Tank
HS ET14	FITTING & HOSE CARTON For 300, 520, 1,000 Gallon Units

CALL for CURRENT PRICING

Clock Gauges

For measuring liquid level in above ground tanks. Gauge mounts on top of tank and is activated by a float connected to a cable. Readout is on a 12 hour clock face. Small hand = feet, large hand = inches. Maximum measurement is 12 feet.



Standard Features: Swivel 360° for desired orientation • High level / low level decals for application on lens cover • Standard float fits through a 2" schedule 40 pipe nipple • Body is aluminum with 2" NPT male connection • Float and cable are stainless steel with plexiglass cover. **Note:** All 818's have "wetted" stainless steel internals for chemical use.

Part No.	Description
MB 818	Clock Gauge.....
MB 818T	Clock Gauge, Teflon Coated for "DEF"

Clock Gauge Alarms



Can Locate 200 ft. Apart

Utilizes No. 818 style clock gauge with a built-in high level warning alarm. Contains a battery powered, intrinsically safe, alarm unit that is mounted remote from gauge. Alarm is set for desired level during installation and can be reset at any time for a change in alarm level requirements. Maximum height measurement is 12'.

Note: All 918's have Stainless Steel internals for chemical use.

Gauge Unit: No. 818 Clock Gauge. Alarm dial is accessible on the clock face. Electrical junction box and lead wires for remote mounting are also included.

Alarm Unit: Plastic weatherproof housing. 90 decibel high pitched "Beep" cycle alarm. Features an on/off test switch. Powered by two lithium batteries (included).

MORRISON BROS. CO.

Part No.	Description
MB 918-0100AG	Clock Gauge Alarm
MB 918T	Clock Gauge Alarm, Teflon Coated for "DEF"