



Pre-Vent Caps **FILL-RITE**

- For Above-Ground Storage Tanks
- Gasoline and Diesel Fuel
- Used as a Fill Cap
- Convenient to Lock (K408A)



2" Male Pipe Thread

STOPS or REDUCES:

- Evaporation Loss
- Water Condensation
- Gasoline Weathering
- Loss of starting quality
- Loss of delivered Octane Rating
- Gum Formation
- Crankcase Oil Dilution

Gasoline stored in above ground tanks equipped with open vent caps can cost you many dollars in evaporated gasoline. You can reduce such loss by installing a PreVent cap. PreVent maintains about 2.5 PSI in the storage tank, preventing vapors from leaving the tank. Diesel fuel presents another problem - water condensation inside the tank. The PreVent cap will reduce such condensation. Relieves vacuum for pump out rates to 30 GPM.


Part No.		Std. Pkg.
CI K408	Prevent Cap Assembly, 2" MPT	6
CI K408A	Prevent Cap Assembly with Anti-Theft Arm	
CI 50C	Replacement Cap Only	12
FR FRTCB	Fillrite Prevent Cap Assembly, 2" MPT	
FR FRTC	Fillrite Replacement Cap Only	

5% Discount on Standard Package.



180M

Locking Caps



The **180M Locking Cap** incorporates a patented spinning technology when in the locked position; basically the cap will free spin, making it impossible to remove. To remove the cap, simply use the included key and unlock the cap. These caps can be used on 2" male or female threads.

Part No.	
MB 180M-2100	2" Locking Cap, #1 Key Configuration.....
MB 180M-2400	2" Locking Cap, #4 Key Configuration.....

Caps & Adapters for Storage Tanks

405C LEVER CAP

Constructed of K-9 aluminum and has a fused epoxy coating with Buna-N Gasket. Side Seal "T" Lever Cap is for use with side seal adapters, such as 267A.



Part No.	Description
MB 405-4	4" Adapter
MB 405C-4	4" Fill Cap



Waste Oil Drain Model 312



Automotive Lift Drain for use with 120 pound full open head drum. Includes removable galvanized bowl, extension tube and drum cover with cam lock. Adjusts to a total height of 67 inches.


Part No.		Wt.
NS 312	Waste Oil Drain	11 lbs.



Portable Waste Oil Drain Model 309

Eight Gallon Automotive Lift Drain. Black Polyethylene body without wheels. Spout & hand grips on top and bottom for easy evacuation. Adjusts to a total height of 67-1/2 inches.

Part No.		Wt.
NS 309	Portable Waste Oil Drain	30 lbs.



155

Double Outlet Vents Threaded Style



Part No.	Connection
MB 155-3/4	3/4" FPT
MB 155-1	1" FPT
MB 155-1-1/4	1-1/4" FPT
MB 155-1-1/2	1-1/2" FPT
MB 155-2	2" FPT
MB 155-3	3" FPT

CONSTRUCTION DETAILS

Body: Aluminum
Screen: Aluminum

354

Updraft Vents

CONSTRUCTION DETAILS

Body Hood: Aluminum
Cap Hood: Aluminum



Part No.	Updraft Vent	Wt.
MB 354-1-1/2	For 1-1/2" Pipe	3/4 lbs.
MB 354-2	For 2" Pipe	3/4 lbs.



178

Watertite Fill Caps

CONSTRUCTION DETAILS

Body: Brass • Cap: Brass



- All Aluminum Available -

Part No.	Threaded	Wt.
MB 178-2	2" FPT	2 lbs.
MB 178-3	3" FPT	4 lbs.
MB 178-4	4" FPT	7 lbs.

CONSTRUCTION DETAILS

Body: Aluminum
Cap: Aluminum



179

Fill Caps

Part No.	Threaded
MB 179M-2	2" Male
MB 179-2	2" Female
MB 179-3	3" Female
MB 179-4	4" Female




285

Line Strainers - Bottom Cleanout

CONSTRUCTION DETAILS

Body: Cast Iron
Cap: Cast Iron
Screen: Stainless Steel
Yoke: Malleable Iron
Gasket: Buna or Nitrile Composite (Teflon also available)



Part No.	Port Size	Stainless Screen	Wt. Lbs.
MB 285-1-1/2	1-1/2" FPT	20-Mesh	10
MB 285-2	2" FPT	20-Mesh	14
MB 285-3	3" FPT	20-Mesh	27
MB 285-4	4" FPT	14-Mesh	42

286

Line Strainers Top Cleanout



CONSTRUCTION DETAILS

Body: Cast Iron
Cap: Cast Iron
Gasket: Nitrile Composite, Buna
Strainer: Brass
Yoke: Malleable Iron

Part No.	Port Size	Brass Screen	Wt. Lbs.
MB 286-2	2" FPT	20-Mesh	17
MB 286-3	3" FPT	20-Mesh	38

