

331



Union Check Valve

CONSTRUCTION DETAILS:

Body: Brass Spring: Brass Disc: Viton®

Part No. **Wt.**
 MB 331-1-1/2 1-1/2" Union Check Valve .5 lbs.


246-A Swing Check Valves

Threaded Ends



CONSTRUCTION DETAILS:

Body: Brass Cap: Brass
 Swing Arm: Brass Gasket: Nitrile Composite
 Poppet: Brass



Part No. **Ports** **Wt.**
 MB 246A-1-1/2 1-1/2" FPT 4 lbs.
 MB 246A-2 2" FPT 5 lbs.
 MB 246A-3 3" FPT 8 lbs.

OPERATING CONDITIONS:
 Cold non-shock pressure limit of 200 PSI W.O.G.



Monitoring Well Manhole

318XA **CONSTRUCTION DETAILS:**
 Cover & Ring: Cast Iron • Skirt: Galv.

Part No. **Size** **Wt.**
 MB 318XA-9 9" 13 lbs.

334 Single Poppet Foot Valves

CONSTRUCTION DETAILS:

Body: Brass Seat: Brass
 Poppet: Brass Screen: Brass

OPERATING CONDITIONS:
 Cold non-shock pressure limit of 200 PSI W.O.G.



Part No. **Ports**
 MB 334-3/4 3/4" FPT
 MB 334-1 1" FPT

Universal Drum Plug Wrenches

For Standard Bung Nuts on 55 or 30 Gallon Drums.



Part No. **Length**
 EV DPW Drum Wrench-Bronze 11-3/4"
 NS 169 Drum Wrench-Aluminum 12-1/2"

Steel Drum Lifter

Easy-to-Use With Forklift Or Hook

DL1 Drum Lifter is designed for no-tilt lifting of open or closed head drums with or without tops in place. This self-adjusting lifter instantly adapts to individual drum loads with its unique compressing action. The heavier the drum, the tighter the lifter will grip.



For one-man operation with any overhead lifting system, including forklift - with up to 5" tine or with a hook attachment. **Capacity** 3,000 lbs. **Weight:** 45 lbs.



Part No.
 MC DL1

2" Steel Weld-In Bung Fitting



Part No.
 HS 8770 2" Steel Weld-In Bung Fitting

Quick Opening Gate Valves

External Spring



OPERATING CONDITIONS:

Cold non-shock pressure limit of 200 PSI W.O.G.

For Petroleum

CONSTRUCTION DETAILS:
 Body: Brass Cap: Brass
 Discs: Brass Gasket: Nitrile Comp.
 Handle: Malleable Iron

Part No. **Size**
 MB 238-1-1/4 1-1/4"

235

Gate Valves

Rising Stem

OPERATING CONDITIONS:
 Cold non-shock pressure limit of 200 PSI W.O.G.

CONSTRUCTION DETAILS:
 Body: Brass Bonnet: Brass
 Discs: Brass Stem: Brass
 Gasket: Nitrile Composite



Part No. **Ports** **Wt.**
 MB 235-1-1/2 1-1/2" FPT 5.5 lbs.
 MB 235-2 2" FPT 8 lbs.
 MB 235-3 3" FPT 16 lbs.

235

235-B Locking Type

Gate Valves

Rising Stem

OPERATING CONDITIONS:
 Cold non-shock pressure limit of 200 PSI W.O.G.

CONSTRUCTION DETAILS:
 Body: Brass Bonnet: Brass
 Discs: Brass Stem: Brass
 Gasket: Nitrile Composite



235B

Part No. **Ports** **Wt.**
 MB 235B-2 2" FPT 9 lbs.
 MB 235B-3 3" FPT 18 lbs.

535 & 535B Gate Valves with Expansion Relief

Rising Stem



Built-in Expansion Relief Port to relieve excessive pressure from thermal expansion to other side of closed valve. "B" Models are locking type.

CONSTRUCTION DETAILS:
OPERATING CONDITIONS: Body: Brass Bonnet: Brass
 Cold non-shock pressure limit Discs: Brass Stem: Brass
 of 200 PSI W.O.G. Gasket: Nitrile Composite

Part No. **Ports** **Wt.** **Locking**
 MB 535-2 2" FPT 8.8 lbs. No
 MB 535B-2 3" FPT 17.5 lbs. Yes
 MB 535-3 3" FPT 17.5 lbs. No
 MB 535B-3 3" FPT 17.5 lbs. Yes



535

128 Series Frost Proof Drain Valve



Used on above ground storage tanks for draining condensation or water from the bottom of the tank. The lock bonnet doubles as the opening mechanism.

CONSTRUCTION DETAILS:
 Body: Brass Lock Bonnet: Brass
 Cap: Brass Stem: Brass

Part No. **Wt.**
 MB 128 1" Frost-Proof Drain Valve 1.8 lbs.

Viton® is a registered trademark of DuPont Performance Elastomers