

331



Union Check Valve

CONSTRUCTION DETAILS:

Body: Brass Spring: Brass Disc: Viton®

Part No.
MB 331-1-1/2 1-1/2" Union Check Valve .5 lbs.


246-A Swing Check Valves

Threaded Ends



CONSTRUCTION DETAILS:

Body: Brass Cap: Brass
Swing Arm: Brass Gasket: Nitrile Composite
Poppet: Brass



Part No.	Ports	Wt.
MB 246A-1-1/2	1-1/2" FPT	4 lbs.
MB 246A-2	2" FPT	5 lbs.
MB 246A-3	3" FPT	8 lbs.

OPERATING CONDITIONS:
Cold non-shock pressure limit of 200 PSI W.O.G.



Monitoring Well Manhole

318XA

CONSTRUCTION DETAILS:
Cover & Ring: Cast Iron • Skirt: Galv.


Part No.	Size	Wt.
MB 318XA-9	9"	13 lbs.

334 Single Poppet Foot Valves

CONSTRUCTION DETAILS:

Body: Brass Seat: Brass
Poppet: Brass Screen: Brass

OPERATING CONDITIONS:
Cold non-shock pressure limit of 200 PSI W.O.G.



Part No.	Ports
MB 334-3/4	3/4" FPT
MB 334-1	1" FPT

Universal Drum Plug Wrenches

For Standard Bung Nuts on 55 or 30 Gallon Drums.



Part No.	Length
EV DPW Drum Wrench-Bronze	11-3/4"
NS 169 Drum Wrench-Aluminum	12-1/2"

Steel Drum Lifter

Easy-to-Use With Forklift Or Hook

DL1 Drum Lifter is designed for no-tilt lifting of open or closed head drums with or without tops in place. This self-adjusting lifter instantly adapts to individual drum loads with its unique compressing action. The heavier the drum, the tighter the lifter will grip.



For one-man operation with any overhead lifting system, including forklift - with up to 5" tine or with a hook attachment. **Capacity** 3,000 lbs. **Weight:** 45 lbs.

Part No.
MC DL1



2" Steel Weld-In Bung Fitting



Part No.
HS 8770 2" Steel Weld-In Bung Fitting

Quick Opening Gate Valves

External Spring



OPERATING CONDITIONS:

Cold non-shock pressure limit of 200 PSI W.O.G.

For Petroleum

CONSTRUCTION DETAILS:
Body: Brass Cap: Brass
Discs: Brass Gasket: Nitrile Comp.
Handle: Malleable Iron

Part No.	Size
MB 238-1-1/4	1-1/4"
MB 238-1-1/2	1-1/2"



235

Gate Valves

Rising Stem

OPERATING CONDITIONS:
Cold non-shock pressure limit of 200 PSI W.O.G.

CONSTRUCTION DETAILS:
Body: Brass Bonnet: Brass
Discs: Brass Stem: Brass
Gasket: Nitrile Composite

Part No.	Ports	Wt.
MB 235-1-1/2	1-1/2" FPT	5.5 lbs.
MB 235-2	2" FPT	8 lbs.
MB 235-3	3" FPT	16 lbs.



235-B Locking Type

Gate Valves

Rising Stem

OPERATING CONDITIONS:
Cold non-shock pressure limit of 200 PSI W.O.G.

CONSTRUCTION DETAILS:
Body: Brass Bonnet: Brass
Discs: Brass Stem: Brass
Gasket: Nitrile Composite

Part No.	Ports	Wt.
MB 235B-2	2" FPT	9 lbs.
MB 235B-3	3" FPT	18 lbs.

535 & 535B Gate Valves with Expansion Relief


Rising Stem



Built-in Expansion Relief Port to relieve excessive pressure from thermal expansion to other side of closed valve. "B" Models are locking type.

CONSTRUCTION DETAILS:
OPERATING CONDITIONS: Body: Brass Bonnet: Brass
Cold non-shock pressure limit of 200 PSI W.O.G. Discs: Brass Stem: Brass
Gasket: Nitrile Composite

Part No.	Ports	Wt.	Locking
MB 535-2	2" FPT	8.8 lbs.	No
MB 535B-2	3" FPT	17.5 lbs.	Yes
MB 535-3	3" FPT	17.5 lbs.	No
MB 535B-3	3" FPT	17.5 lbs.	Yes



128 Series Frost Proof Drain Valve

Used on above ground storage tanks for draining condensation or water from the bottom of the tank. The lock bonnet doubles as the opening mechanism.

CONSTRUCTION DETAILS:
Body: Brass Lock Bonnet: Brass
Cap: Brass Stem: Brass



Part No.	Wt.
MB 128 1" Frost-Proof Drain Valve	1.8 lbs.

Viton® is a registered trademark of DuPont Performance Elastomers