

**American Padlocks**



**Solid Steel Padlocks** from American Lock. Chrome-plated, case hardened construction with Boron shackles. 5-Pin tumbler is standard. (Keyed Different, Keyed Alike also available).

**A5260 Series Square Padlocks** are 2" wide x 3/4" thick. Shackle diameter is 3/8". Horizontal shackle clearance is 3/4". Vertical shackle clearance is either 1-1/8", 2" or 3" as shown.

**A700 Series Round Padlocks** are 2-1/2" wide x 1-1/8" thick. Shackle diameter is 7/16". Horizontal shackle clearance is 15/16". Vertical shackle clearance is 1-1/16", or 2" as shown.



A5260

A700



A = Shackle Diameter  
B = Vertical Clearance  
C = Horizontal Clearance

Part No.	Width	Vertical Clearance
MR A5260	2"	1-1/8"
MR A5261	2"	2"
MR A5262	2"	3"
MR A700	2-1/2"	1-1/16"
MR A701	2-1/2"	2"

**Solid Brass Padlocks**

**Brass Padlocks** from Master Lock. Stylish and strong solid brass bodies. Standard with hardened steel shackles and 4-pin lock cylinders. Available in 3 different sizes. Keyed alike.



**120KAD:** Width is 3/4" • Shackle diameter is 5/32" • Vertical clearance is 7/16" • Horizontal clearance is 1/4".


**140KAD:** Width is 1-9/16" • Shackle diameter is 1/4" • Vertical clearance is 7/8" • Horizontal clearance is 13/16".

Part No.	Width
MR 120KAD	3/4"
MR 140KAD	1-9/16"



**Pallet Puller**

Will pull any pallet to within a forklift's reach. Designed to bite into pallet stringers up to 4-1/2" thick. All steel construction. Includes chain.



Part No.	Wt.
GN 2A093	21 lbs.




**DULTMEIER SALES**  
Experts in Delivering Fluid Handling Solutions  
"We Know Flow!"

**Water Sandblast Kit**

**For Suction-Fed Injection of Sand Into the Water Stream for Abrasive Cleaning**



**Water Sandblast Kits** are designed for suction-fed injection of sand into downstream line of common pressure washers. Ideal for abrasive cleaning and removal of paint, rubber, metal scale and rust from a variety of surfaces. Rated from 1500 PSI to 5,000 PSI and 3 GPM to 10 GPM. Maximum temperature is 200° F. Kit includes sand nozzle, mixing head, nozzle holder, sand probe and 10' of supply hose.



**Note:** High pressure, zero degree nozzle is not included and must be matched to pressure washer flow and PSI. Can ship with kit but is billed separately.

Part No.	Flow Range	Pressure Range	Wt.
IP DWSDBTk	3 GPM - 10 GPM	1,500 to 5,000 PSI	10 lbs.



**Order from our entire inventory online!**

- Current Pricing
- Web Specials
- Closeout Items
- Current Flyers
- Order Status
- Parts Schematics

**Scan our QR Code**



[www.dultmeier.com](http://www.dultmeier.com)

WE APPRECIATE YOUR

**BUSINESS!**