



Bulk Wash Hose Smooth Cover

Clean Master Wash Down Hose from Gates is designed for hot water and cold water pressure cleaning in car/truck wash, pressure wash, carpet cleaning, industrial cleaning, food processing and other applications where heavy-duty service is required. Special compound smooth cover is abrasion and ozone resistant. Available in black, blue and gray. Blue and gray hose is "non-marking". Available in 1 or 2 wire construction as shown. Rated from -40° to +250° F. Sold by the foot cut to length in 5' increments or in 300' reels. Can be used with crimp or reusable fittings. **(Note: All reels have a maximum of 3 pieces none shorter than 50' except 8BL-3/8 which is a 300' continuous length).**



Clean Master



NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY


Part No.	Pressure	Hose Type	I.D.	O.D.	* Std Pkg.
GA PC-1/4	4000 PSI	Black, 1-Wire	1/4"	.53"	300'
GA PC-3/8	4000 PSI	Black, 1-Wire	3/8"	.67"	300'
GA PC4-3/8	5000 PSI	Black, 2-Wire	3/8"	.74"	300'
GA PC-1/2	3000 PSI	Black, 1-Wire	1/2"	.79"	300'
GA 6BL-1/4	4000 PSI	Blue, 1-Wire	1/4"	.53"	300'
GA 6BL-3/8	4000 PSI	Blue, 1-Wire	3/8"	.67"	300'
GA 8BL-3/8	*4000 PSI	Blue, 1-Wire	3/8"	.68"	300'
GA 6GY-3/8	4000 PSI	Gray, 1-Wire	3/8"	.67"	300'
GA 6GY-1/2	4000 PSI	Gray, 1-Wire	1/2"	.80"	300'

* Imported, Not Gates Brand, Features Continuous Length for this Part Only.

*** 10% Discount for Standard Pack Purchase**

T146 Hot Water Mining Washdown Spray Hose 1,000 PSI

An ideal choice for plant wash down. Rated to 1000 PSI constant pressure. I.D. Maximum temperatures to 200° F. Cover is Yellow SBR/NBR blend that is abrasion, ozone, hydrocarbon and fire resistant - pin pricked. High tensile braided steel wire reinforcement. Tube is black extruded SBR/NBR blend - oil mist resistant. **T146** specifications. **Note: We can supply 3/4" and 1", 50ft. and 100ft. coupled hose assemblies with GLX hydraulic fittings. If field assembled, you must use GLX or Bandit clamp connections. Do Not Use worm drive clamps.**




Part No.	I.D.	O.D.	Std. Pkg.	Wt. Per Pkg.
TF T136A7-075X50	3/4"	1.10"	50	22 lbs.
TF T136A7	3/4"	1.10"	100	44 lbs.
TF T136A10-100X50	1"	1.34"	50	29 lbs.
TF T136A10	1"	1.34"	100	58 lbs.
TF T136AK150	1-1/2"	1.93"	50	54 lbs.
TF T136AK-150X100	1-1/2"	1.93"	100	108 lbs.
TF T136AK200	2"	2.48"	50	74 lbs.
TF T136AK-200X100	2"	2.48"	100	148 lbs.

Standard Package Only - All Sizes - No Cuts.

Stainless Hose Hanger

Wall Mount Hose Hanger. Polished stainless construction. Food grade rated. Holds up to 175' of 3/8" hose, 120' of 1/2" hose or 90' of 3/4" hose. Dimensions are 13-3/4" W x 6" H x 7-3/4" D.



Part No.	Wt.
NP 11006 Stainless Hose Hanger	2 lbs.

Bulk Wash Hose Wrapped Cover

Wrapped Cover Hose offers superior wear resistance to smooth rubber hose. Great choice for hot or cold water cleaning applications. Oil resistant tube and cover. One or two wire construction in 1/4", 3/8" and 1/2" I.D. Can be crimped on site with permanent or reusable fittings matched to hose O.D. Quantity discount for full reel purchases. Rated to 250° F.



1SN & 2SN

1SN (1 Wire) and 2SN (2 Wire) Series hose feature a standard "wrapped" cover for added performance and wear life compared to smooth cover hose.



Highest Abrasion Resistance

5RM (2 Wire) Series hose features a standard "wrapped" cover but with the addition of a "polyethylene coating" that is impregnated into the cover. This gives maximum wear and abrasion resistance compared to any other wrapped or smooth cover rubber hoses.

Part No.		I.D.	O.D.	PSI	Max. * Std. Pkg.
GA 1SN-1/4	Black Wrapped, 1-Wire	1/4"	.48"	3250	800'
GA 1SN-3/8	Black Wrapped, 1-Wire	3/8"	.65"	4000	300'
GA 2SN-3/8	Black Wrapped, 2-Wire	3/8"	.70"	6000	300'
GA 2SN-1/2	Black Wrapped, 2-Wire	1/2"	.84"	4000	250'
GA 5RM-3/8	Black Wrapped with Poly, 2-Wire	3/8"	.72"	5500	500'
GA 5RM-1/2	Black Wrapped with Poly, 2-Wire	1/2"	.84"	4300	250'

*** 10% Discount if ordered in Standard Pack Reels. Reel Lengths are Approximate and May Vary. Non Continuous Lengths, May be Up to 3 lengths Per Reel with No Length Less than 50 Ft.**



Hurricane Pressure Washer Hose Wrapped Cover - 1 Wire

Bulk Pressure Washer Hose from Parker. Ideal for use with hot or cold water pressure washers in plant wash down or car/truck wash applications. **Made in the USA.**

Single wire, wrapped cover hose rated to 3,000 PSI. Available with either standard black or non-marking blue covers. Tube and cover are Neoprene construction. Temperature ratings from -40° to +250° F. Can be coupled with reusable couplings and or crimp style fittings. **(Note: Not intended for carpet cleaning applications!)**



Part No.		I.D.	O.D.	Max. PSI	Std. Pkg.
PA 7258-1/4	Black Hose, Bulk	1/4"	.500"	3000	500'
PA 7258-3/8	Black Hose, Bulk	3/8"	.625"	3000	500'
PA 7258-3/8B	Blue Hose, Bulk	3/8"	.625"	3000	500'

*** 10% Discount if ordered in Standard Pack Reels. Reel Lengths are Approximate and May Vary. Non Continuous Lengths, May be Up to 3 lengths Per Reel with No Size Less than 50 Ft.**

thank you!

WE APPRECIATE YOUR BUSINESS

Please remember there are No Returns on customer specified cut lengths of hose.