

Quick Couplers

Imported

Straight-Through "Quick-Detach" Couplers and Plugs are available in brass, steel or stainless steel construction. Standard with Buna-N o-rings, (Viton® also available). Available with Male MPT or Female FPT threads.

Coupler Sockets

Part No.	Size	Material	Max. PSI
KH B14F	1/4" FPT	Brass	5000
KH B14M	1/4" MPT	Brass	5000
KH B38F	3/8" FPT	Brass	4000
KH B38M	3/8" MPT	Brass	4000
KH B12F	1/2" FPT	Brass	3600
KH B12M	1/2" MPT	Brass	3600



B14F

KH S14F	1/4" FPT	Stainless	5000
KH S14M	1/4" MPT	Stainless	5000
KH S38F	3/8" FPT	Stainless	5000
KH S38M	3/8" MPT	Stainless	5000
KH S12F	1/2" FPT	Stainless	5000
KH S12M	1/2" MPT	Stainless	5000



S14M

Plug Nipples

Part No.	Size	Material	Max. PSI
KH 14PF	1/4" FPT	Steel	5000
KH 14PM	1/4" MPT	Steel	5000
KH 38PF	3/8" FPT	Steel	4000
KH 38PM	3/8" MPT	Steel	4000
KH 12PF	1/2" FPT	Steel	3600
KH 12PM	1/2" MPT	Steel	3600



38PM

KH 14SF	1/4" FPT	Stainless	5000
KH 14SM	1/4" MPT	Stainless	5000
KH 38SF	3/8" FPT	Stainless	4000
KH 38SM	3/8" MPT	Stainless	4000
KH 12SF	1/2" FPT	Stainless	5000
KH 12SM	1/2" MPT	Stainless	5000



14SF

10% Discount on 50w or More - Not Assorted

Insulated Quick Couplers



14044 14042
14045 14043

Nickel Plated Quick Couplers with Molded Insulator Grips. Straight-Through design is compatible with most any straight through nipple plugs on the market. Available in 1/4" and 3/8" sizes and with male or female threads. Grips allow couplers to stay cool to the touch even when used with hot water. Standard with Buna-N seals.

Part No.	Size	Material	Max. PSI
KH 14044	1/4" FPT	Brass	5200
KH 14045	1/4" MPT	Brass	5200
KH 14042	3/8" FPT	Brass	3700
KH 14043	3/8" MPT	Brass	3700



HANSEN

Double Shut-Off Style



Double Shut-Off Couplers & Plugs: Spring-loaded valves in each coupling half seal immediately for positive shut-off to prevent loss of fluid or air when the coupling is disconnected. Ideal for water, hydraulics and chemical applications. Buna seal is standard, but other options are available.

Standard Features Include: Hardened construction to assure long service life • High flow capacity • High pressure seal design • Captive valve seal assures "bubble tight" poppet sealing • Durable ball locking mechanism for reliable connections • Temperature range is -40° F. to +180° F. • Available in either brass or 303 Stainless steel construction.

Part No.	Size	Material	Max. PSI	Max. GPM
KH BH2-60	1/4" FPT	Brass	2700	4.0
KH SH2-62	1/4" FPT	Stainless	3700	4.0
KH BH3-60	3/8" FPT	Brass	2200	6.0
KH SH3-62	3/8" FPT	Stainless	3700	6.0
KH BH4-60	1/2" FPT	Brass	2200	10
KH SH4-62	1/2" FPT	Stainless	4200	10
KH BH6-60	3/4" FPT	Brass	2000	25
KH SH6-62	3/4" FPT	Stainless	3000	25
KH B8HP36	1" FPT	Brass	1500	35
KH B10-H41	1-1/4" FPT	Brass	1200	45

Couplers



Plugs



Part No.	Size	Material	Max. PSI	Max. GPM
KH BH2-61	1/4" FPT	Brass	2700	4.0
KH SH2-63	1/4" MPT	Stainless	3700	4.0
KH BH3-61	3/8" FPT	Brass	2200	6.0
KH SH3-63	3/8" MPT	Stainless	3700	6.0
KH BH4-61	1/2" FPT	Brass	2200	10
KH SH4-63	1/2" MPT	Stainless	4200	10
KH BH6-61	3/4" FPT	Brass	2000	25
KH SH6-63	3/4" MPT	Stainless	3000	25
KH B8KP36	1" FPT	Brass	1500	35
KH B10-K41	1-1/4" FPT	Brass	1200	45



HANSEN

Quick Couplers



Straight Through Style

Straight-Through "Quick-Detach" Couplers and Plugs: Smooth, unrestricted bore permits full flow of fluids. (Rated to 180° F).

Designed for use with liquids, hydraulic service, compressed air, gases, water and vacuum. Available in Brass, Stainless Steel, Zinc-Plated or Steel construction. Buna seals are standard (Viton®, Teflon and EPDM are optional). Straight-Through design means there is no positive shut-off after disconnect. (For positive shut-off see Double-Shut couplers below).

Female Straight-Through Couplers

Part No.	Size	Material	Max. PSI	Max. GPM
KH BST1	1/8" FPT	Brass	2800	2.7
KH SST1	1/8" FPT	Stainless	4200	2.7
AA BST2	1/4" FPT	Brass	5200	5.6
KH LL2S16	1/4" FPT	Stainless	7500	5.6
AA BST3	3/8" FPT	Brass	2800	15
KH LL3S21	3/8" FPT	Stainless	6300	15
AA BST4	1/2" FPT	Brass	2200	22
KH LL4S26	1/2" FPT	Stainless	3600	22
KH BST6	3/4" FPT	Brass	1700	66
KH LL6S31	3/4" FPT	Stainless	3000	66
KH 8S36	1" FPT	Brass	1300	140
KH LL8S36	1" FPT	Stainless	2000	140
KH 10S41	1-1/4" FPT	* Brass	1700	184
KH LL10S41	1-1/4" FPT	Stainless	2200	184
KH 12S46	1-1/2" FPT	* Brass	1400	297
KH LL12S46	1-1/2" FPT	Stainless	2500	297

* Brass Construction with Steel Sleeve.



Couplers



Female (FPT)

Male Straight-Through Couplers

Part No.	Size	Material	Max. PSI	Max. GPM
AA BST2M	1/4" MPT	Brass	5200	5.6
KH LL2S15	1/4" MPT	Stainless	7500	5.6
AA BST3M	3/8" MPT	Brass	2800	15
KH LL3S20	3/8" MPT	Stainless	6300	15
AA BST4M	1/2" MPT	Brass	2200	22
KH LL4S25	1/2" MPT	Stainless	3600	22
KH BST6M	3/4" MPT	Brass	1700	66
KH LL6S30	3/4" MPT	Stainless	3000	66
KH 8S35	1" MPT	Brass	1300	140



Male (MPT)

O-Rings

Part No.	Description
KH 0101	O-Ring, BUNA for 1/8" Couplers.....
KH 125B	O-Ring, BUNA for 1/4" Couplers.....
KH 125V	O-Ring, VITON® for 1/4" Couplers.....
KH 250B	O-Ring, BUNA for 3/8" Couplers.....
KH 250V	O-Ring, VITON® for 3/8" Couplers.....
KH 114	O-Ring, BUNA for 1/2" Couplers.....
KH 114V	O-Ring, VITON® for 1/2" Couplers.....
KH 212	O-Ring, BUNA for 3/4" Couplers.....



Female Straight-Through Plugs

Part No.	Size	Material	Max. PSI	Max. GPM
KH BSTN1	1/8" FPT	Brass	2800	2.7
KH 1T11	1/8" FPT	Steel	3400	2.7
KH LL1T11	1/8" FPT	Stainless	4200	2.7
AA BSTN2	1/4" FPT	Brass	5200	5.6
KH 2T16	1/4" FPT	Steel	5500	5.6
AA 7187	1/4" FPT	Stainless	7500	5.6
AA BSTN3	3/8" FPT	Brass	2800	15
KH 3T21	3/8" FPT	Steel	4200	15
AA 7206	3/8" FPT	Stainless	6300	15
AA BSTN4	1/2" FPT	Brass	2200	22
KH 4T26	1/2" FPT	Steel	3500	22
KH LL4T26	1/2" FPT	Stainless	3600	22
KH BSTN6	3/4" FPT	Brass	1700	66
KH 6T31	3/4" FPT	Steel	2100	66
KH LL6T31	3/4" FPT	Stainless	3000	66
KH B8T36	1" FPT	Brass	1300	140
KH 8T36	1" FPT	Steel	2000	140
KH LL8T36	1" FPT	Stainless	2000	140
KH B10T41	1-1/4" FPT	Brass	1700	184
KH 10T41	1-1/4" FPT	Steel	2700	184
KH LL10T41	1-1/4" FPT	Stainless	2200	184
KH B12T46	1-1/2" FPT	Brass	1400	297
KH 12T46	1-1/2" FPT	Steel	2100	297
KH LL12T46	1-1/2" FPT	Stainless	2500	297



Plugs



Female (FPT)

Male Straight-Through Plugs

Part No.	Size	Material	Max. PSI	Max. GPM
KH B1T10	1/8" MPT	Brass	2800	2.7
KH 1T10	1/8" MPT	Steel	3400	2.7
KH LL1T10	1/8" MPT	Stainless	5500	2.7
KH B2T15	1/4" MPT	Brass	5200	5.6
KH 2T15	1/4" MPT	Steel	5500	5.6
KH LL2T15	1/4" MPT	Stainless	7500	5.6
KH B3T20	3/8" MPT	Brass	2800	15
KH 3T20	3/8" MPT	Steel	4200	15
KH LL3T20	3/8" MPT	Stainless	6300	15
KH B4T25	1/2" MPT	Brass	2200	22
KH 4T25	1/2" MPT	Steel	3500	22
KH LL4T25	1/2" MPT	Stainless	3600	22
KH B6T30	3/4" MPT	Brass	1700	66
KH 6T30	3/4" MPT	Steel	2100	66
KH LL6T30	3/4" MPT	Stainless	3000	66
KH B8T35	1" MPT	Brass	1300	184
KH 8T35	1" MPT	Steel	2000	184
KH LL8T35	1" MPT	Stainless	2000	184

Plugs



Male (MPT)

Viton® is a registered trademark of DuPont Performance Elastomers