



MV Trigger Guns

Great Choice for car wash, truck wash or pressure wash applications. Available in weep or non-weep versions. Contour design and easy trigger pull for ease of use. Exact replacements for many of the popular spray guns on the market today. Brass 3/8" FPT inlet and 1/4" FPT outlet. Rated to 300° F.



925 & 925W
(8 GPM)



951
(10 GPM)

Part No.	Seat	Flow	Max. PSI
MV 925W	Weep Style	8 GPM	4500
MV 925	Zero Leak	8 GPM	4500
MV 951	Zero Leak	11 GPM	5100

Pressure Wash Spray Wands

Non Slip Grip



2002



ML956

Designed for the pressure washer and truck wash industry. Heavy duty, unique gun features a soft, non-slip rubber grip for ease of use. Zero Leak design. Rated to 12 GPM, 5000 PSI and 320° F. Standard with 3/8" FPT inlet and 1/4" FPT outlet. Brass or Stainless construction.

Part No.	Ports	Max. PSI	Max. GPM
MV 2002	Brass	5800	10.5
MV ML956	Stainless	5000	10.5



Trigger Wand Assemblies



Complete Trigger Wand Assemblies. Ready to hook up to your pressure washer. Assemblies include: Trigger gun, 36" extension with molded grip, 3/8" inlet quick nipple, 1/4" quick coupler outlet. Rated to 7 GPM, 4000 PSI and 250° F. (Nozzles are not included).

Part No.	Description
MV 430029	Complete Trigger Wand Assembly.....
MV M407A	Trigger Gun Only.....

SUTTNER Break-Away Gun Fittings

Mounts between hose and gun or between gun and extension, designed to break before damage to gun or wand. Available in 1/4" or 3/8". Rated to 4,000 PSI.



Part No.	Size
AA 5068	1/4" MPT x FPT
AA 5069	3/8" MPT x FPT



Easy Pull Trigger Guns

Heavy-Duty, Trigger Guns from MTM Hydro. Light trigger pull means less hand fatigue. Ideal for car/truck wash, mobile cleaning, pressure wash and industrial cleaning. **SG35A** can be used for all applications listed above but is also rated for acid solutions. All wands have 3/8" FPT inlet x 1/4" FPT outlet. Rated to 320° F. except M407A which is 250° F. Zero leak seats. **SG28** features easy grip handle.

SG35 & SG35A



SG28 & M407A



SG40

Part No.	Max. PSI	Max. Flow
MV M407A	4000	7 GPM
MV SG28	4000	12 GPM
MV SG35	5000	12 GPM
MV SG35A	* 5000	12 GPM
MV SG35SB	5000	12 GPM
MV SG40	5800	8 GPM

* Can Be Used for Acid Solutions.

High Flow Trigger Wands

High Flow Trigger Wands are ideal for hydro excavation and high gpm flow requirements. Ergonomic design minimizes fatigue.

Regular Models are rated to 195° F. **Inline Models** are rated to 250° F.

YG2527S & YG4032S
Inline



YG1732
YG2953B
ML210
RL84



Part No.	Max. Flow	Max. PSI	Ports
MV RL84	21 GPM	8100 PSI	1/2" FPT
IP YG1732	32 GPM	1750 PSI	1/2" FPT
IP YG2953B	53 GPM	2900 PSI	3/4" FPT
MV ML210	53 GPM	3200 PSI	3/4" FPT
IP YG2527S	* 27 GPM	2500 PSI	1/2" FPT
IP YG4032S	* 32 GPM	4000 PSI	1/2" FPT
IP 680267	1/2" MPT x 36" Long, 304SS Wand/Lance ..		
IP 680268	1/2" MPT x 48" Long, 304SS Wand/Lance ..		
IP 680269	1/2" MPT x 60" Long, 304SS Wand/Lance ..		
IP 680270	1/2" MPT x 72" Long, 304SS Wand/Lance ..		

* Straight Inline Design.

Inline Spray Wand

Food Grade Inline Spray Wand. Ideal for foaming or rinse applications. Stainless steel construction with plastic cover. Ergonomic design reduces trigger pull by 40% and holding force by 90%. Can be locked in open position for extended use. 1/2" FPT swivel inlet x 1/2" FPT solid outlet.



Rated to 31 GPM & 870 PSI. Maximum temperature is 212° F.



Can Be Locked in Opened Position

Part No.	Flow	Pressure	Wt.	
NP ST3225	Inline Spray Wand	31 GPM	870 PSI	1.6 lbs.

Viton® is a registered trademark of DuPont Performance Elastomers