




N47-25

Shown with  
Optional TR  
Position



## Spring Rewind Reel & Hose Units

**Hannay Spring Rewind Hose Reels** feature narrow frame and compact mounting base. Heavy-duty spring provides self-contained rewind power. Ideal for air and water, lubrication, maintenance operations, service stations and many other industrial uses. 10 Gauge and 14 gauge steel construction with enamel finish. All reels come with hose type and length shown along with hose stop and hose roller assembly. Model SR roller position is standard but other positions are available.

### AIR & WATER REELS - LOW PRESSURE

Part No.	Description	Hose		PSI	Wt.
		Size	Length		
HN 47-24	N716-19-20J Series Spring Rewind with single textile braid reinforced synthetic rubber hose, and HS-3 hose stop installed.....	1/2"	50'	300	100 lbs.

### AIR, WATER & LUBE OIL REELS - MEDIUM PRESSURE

Part No.	Description	Hose		PSI	Wt.
		Size	Length		
HN 47-25	N716-19-20J Series Spring Rewind with SAE 100 R1 Type AT hose, and HS-3 hose stop installed.....	3/8"	50'	2250	99 lbs.
HN 47-26	N716-19-20J Series Spring Rewind with SAE 100 R1 Type AT hose, and HS-3 hose stop installed.....	1/2"	50'	2000	102 lbs.
HN 47-45	N716-25-26B Series Spring Rewind with SAE 100 R1 Type AT hose, and HS-3 hose stop installed *.....	3/8"	75'	2250	145 lbs.
HN 47-46	N716-25-26B Series Spring Rewind with SAE 100 R1 Type AT hose, and HS-3 hose stop installed *.....	1/2"	75'	2000	150 lbs.

### AIR, WATER & LUBE OIL REELS - HIGH PRESSURE

Part No.	Description	Hose		PSI	Wt.
		Size	Length		
HN 47-27	N716-19-20J H5M Series Spring Rewind with SAE 100 R16 Type AT hose, and HS-3 hose stop installed.....	3/8"	50'	4000	102 lbs.
HN 47-28	N716-19-20J H5M Series Spring Rewind with SAE 100 R16 Type AT hose, and HS-3 hose stop installed.....	1/2"	50'	3500	105 lbs.

### GREASE REELS

Part No.	Description	Hose		PSI	Wt.
		Size	Length		
HN 45-11	N515-19-20J H10M Series Spring Rewind with SAE 100 R2 Type AT hose, and HS-3 hose stop installed.....	1/4"	50'	5000	98 lbs.
HN 45-13	N515-19-20J H8M Series Spring Rewind with SAE 100 R16 Type AT hose, and HS-3 hose stop installed.....	3/8"	50'	4000	99 lbs.

\* Not UPS shippable.



## Controlled Return Hose Reel



**ReelSafe Spring Rewind Hose Reels** from **Reelcraft** feature a unique system that pays out hose like a traditional reel, but retracts back into the reel at average walking speed. Safely protects personnel and equipment. Decelerates hose retraction up to 83% vs standard reels. Low pressure models are ideal for air or water applications. Medium pressure reels can be used for oil transfer. High pressure reels can be used for grease applications.

### Standard Features:

- Retracts Hose at 2 Miles Per Hour, Matches Average Walking Speed
- Constant Retraction Regardless of Fluid or Environmental Temperatures
- No Field Adjustment Required
- 7 Position Hose Arm Guide Allows for Multiple Mounting Options
- All Models Include Hose As Noted
- All Models Have 1/2" FPT Inlet
- Made in the USA
- All Reels Can Be Ordered "Without" Hose If Needed



Part No.	Hose & End Fitting	Pressure	Wt.
RF RS7650OLP	3/8" x 50', 1/4" MPT	300 PSI	46 lbs.
RF RS7850OLP	1/2" x 50', 3/8" MPT	300 PSI	50 lbs.
RF RS7650OMP	3/8" x 50', 3/8" MPT	2600 PSI	58 lbs.
RF RS7850OMP	1/2" x 50', 1/2" MPT	3000 PSI	60 lbs.
RF RS7450OHP	1/4" x 50', 1/4" MPT	5000 PSI	58 lbs.
RF RS7650OHP	3/8" x 50', 1/4" MPT	4800 PSI	63 lbs.

