



High Temperature, Run-Dry Capabilities

PEHT
Platinum & ESS
Platinum/316SS



EPHT Series
(3.3 - 3.9 GPM)



HTS Series
(4.0 - 5.6 GPM)



HTCK Series
(21 - 36 GPM)



The quality that you have learned to expect from *General Pumps*, but now with the new *Emperor* line, which can withstand temperatures to 185° F. and can even run dry for several hours. Nickel-plated forged brass or stainless manifolds provide corrosion resistant operation. High temperature, run-dry seals. New Patent-Pending valve design. Wide range of flow and pressure ranges. Rails included with some models.

EPHT Series, Nickel Plated, Brass Manifolds

| Part No. | GPM | Max. PSI | RPM | Shaft | Wt. |
|--------------|-----|----------|------|-------|------|
| | | | | Size | Lbs. |
| IP EPHT1810S | 3.3 | 2465 | 1750 | 24mm | 18 |
| IP EPHT1812S | 3.9 | 2465 | 1750 | 24mm | 18 |

PEHT Series, Nickel-Plated Stainless Manifolds

| Part No. | GPM | Max. PSI | RPM | Shaft | Wt. |
|--------------|---------|----------|-----------|-------|------|
| | | | | Size | Lbs. |
| IP PEHT2010S | 3.4 | 3000 | 1450 | 24mm | 21 |
| IP PEHT2012S | 4.0/4.8 | 3000 | 1450/1750 | 24mm | 21 |
| IP PEHT2213S | 5.6 | 3000 | 1450 | 24mm | 21 |

ESS Series, 316 Stainless Manifolds

| Part No. | GPM | Max. PSI | RPM | Shaft | Wt. |
|--------------|-----|----------|------|-------|------|
| | | | | Size | Lbs. |
| IP ESS2010SS | 4.0 | 3000 | 1750 | 24mm | 22 |
| IP ESS2213SS | 5.5 | 3000 | 1450 | 24mm | 22 |

HTS Series, Nickel-Plated Brass Manifolds

| Part No. | GPM | Max. PSI | RPM | Shaft | Wt. |
|-------------|-----|----------|------|-------|------|
| | | | | Size | Lbs. |
| IP HTS2210S | 4.0 | 2300 | 1450 | 24mm | 32 |
| IP HTS2215S | 5.0 | 2300 | 1200 | 24mm | 32 |
| IP HTS2016S | 5.6 | 3000 | 1450 | 24mm | 32 |

HTF Series, Nickel-Plated Brass Manifolds

| Part No. | GPM | Max. PSI | RPM | Shaft | Wt. |
|-------------|-----|----------|------|-------|------|
| | | | | Size | Lbs. |
| IP HTF2019S | 7.5 | 3600 | 1750 | 24mm | 41 |
| IP HTF2221S | 10 | 3000 | 1750 | 24mm | 41 |
| IP HTF2421S | 12 | 2500 | 1750 | 24mm | 41 |

HTCK Series, Nickel-Plated Brass Manifolds

| Part No. | GPM | Max. PSI | RPM | Shaft | Wt. |
|---------------|---------|-----------|-----------|-------|------|
| | | | | Size | Lbs. |
| IP HTCK3623S | 18/25 | 1500/1300 | 1000/1350 | 30mm | 80 |
| IP PHTCK3623S | * 18/25 | 1500/1300 | 1000/1350 | 30mm | 80 |
| IP HTCK4050S | 40/45 | 1500 | 800/900 | 40mm | 157 |
| IP PHTCK4050S | * 40/45 | 1500 | 800/900 | 40mm | 157 |

* Rated to 140° F. Best for Use With Poor Water Quality Conditions.