



Remco Soft Wash Pumps



SmoothFlo Pumps from Remco are a popular choice for the rigors of soft wash and bleach applications. Also an ideal choice for industrial and agricultural chemical spraying and truck wash applications.

Professional grade pumps are rated to open flows of 5.3 or 7.0 GPM and up to 100 PSI. Standard with Viton® valves and Santoprene diaphragms.

Heavy-duty 12VDC sealed motors have 12" lead wires.

Self-priming to 14Ft and capable of being run dry.

Pressure controls feature FLO-IQ Demand/Bypass technology that eliminates rapid cycling and hammer.

Quick attach 3/4" fittings are included with each pump.

Rated for liquids to 140° F. Made in USA. 110 volt and 24VDC also available.



Part No.	Flow @ 80 PSI	Motor
AQ 591763B-SB	2.5 GPM	12VDC
AQ 591894A-SB	3.5 GPM	12VDC

HYPRO® 12-Volt Aqua Tiger Pumps



FEATURES:

- 12-Volt DC Centrifugal Pumps
- 3/4" Ports/Viton® Seal
- Low Flow/Pressure
5 GPM @ 9 PSI
Maximum Flow 18 GPM
- Bronze Body & Impeller or
316 Stainless Body/Impeller
- Maximum temperature is 140° F.

Part No.	Voltage	Description	Wt.
HY 9700B	12 Volt DC	Bronze Centrifugal Pump	5 lbs.

Little Giant Transfer Pumps

"Your Solution Innovator"

Pony Transfer Pumps are lightweight, non-submersible and portable. Can be used for transfer and dewatering at low pressure (10 PSI). Rated for intermittent duty (15 minutes on, 45 minutes off). Self-priming up to 6'. Plated brass bodies. Dual ports with 3/4" male garden hose x 3/8" FPT. 1/10 H.P. 12-Volt units come with 6" lead wires. 110-volt comes with 5' power cord.



Part No.	Voltage	GPM	Wt.
GJ PP1	115 Volt	6.0	5.5 lbs.
GJ PP12	12 Volt	5.0	4.2 lbs.



Remote On/Off Switches (For 12- and 24-Volt Remco Pumps)



- Provides remote on/off power control up to 75 ft.
- Heavy-duty 12-gauge wire
- Standard SAE 2-pin connections
- LED power indication light
- Key Fob Remote & Lanyard Included



Part No.	Description
AQ 901-RC01-R	12V Remote On/Off Switch, 20 Amps
AQ 901-RC02-R	12/24V Remote On/Off Switch, 40 Amps

Viton® is a registered trademark of DuPont Performance Elastomers

12 Volt & 115 Volt Diaphragm Pumps (5.3 GPM)

HD 5500 Series

For Use with a Wide Variety of Applications

- 5.3 GPM Max; 3.8 GPM @ 40 PSI
- "Demand Style" Pressure Switch; cut in 45 PSI; cut out 60 PSI
- "By-Pass" Style Also Available
- 12-Volt DC or 115V AC
- 1/2" FPT Or 3/4" Quick Attach Ports
- 5 Chamber Diaphragms
- Polypropylene Housing, Viton® Valves, Santoprene Diaphragm (Select Geolast Diaphragms for Diesel, Transmission Fluid, Light Oils & Anti-Freeze - Not for Flammable Liquids)
- Amp Draw at 0 PSI = 5.5
Amp Draw at 60 PSI = 18.0 (water)



Part No.	Max. GPM	Ports	Control	Voltage
AQ 550	5.3	1/2" FPT	Demand	12V
AQ 550-110V	5.3	1/2" FPT	Demand	115V
AQ 550-GEO	5.3	1/2" FPT **	Demand	12V
AQ 550-HB	5.3	3/4" QA *	Bypass	12V
AQ 551	5.3	1/2" FPT	Bypass	12V
AQ 551-HB	5.3	3/4" QA *	Bypass	12V
AQ 551-110V	5.3	1/2" FPT	Bypass	115V

* Requires use of Quick Attach hose barb connectors. ** GEO includes Geolast diaphragms for diesel & other petroleum base liquids (Not for flammable liquids).

"FatBoy"



12-Volt Pumps (7.0 GPM)

- Not for Transfer Applications -



FatBoy Diaphragm Pumps feature self-priming design with priming capacity to 14'. Available in either Demand or Bypass styles. Polypropylene housing with Viton® valves and Santoprene diaphragms for added chemical compatibility. 7 GPM at 0 PSI; 4.4 GPM at 60 PSI. Motors are 12VDC, totally enclosed, non-vented. Maximum temperatures to 140° F. Lead wires are 14AWG, 12" long. Ports are 1/2" FPT or 3/4" Quick Attach.

19 Amps Draw at 60 PSI (water)
15 Amps Draw at 40 PSI (water)

Note: FatBoy pumps should not be operated below 25 PSI to avoid strain.

Part No.	Control	Max. PSI	Max. GPM	Flow @ 60 PSI	Wt.
AQ 770	Demand	60	7.0	4.4 GPM	8 lbs.
AQ 771	Bypass	60	7.0	4.4 GPM	8 lbs.
AQ 773	* Demand	60	7.0	4.4 GPM	8 lbs.

AQ 901-013-R 8' Heavy-Duty Wiring Harness & Switch, 12 AWG
* Requires 3/4" Quick-Attach Hose Barbs - See Right for Options.



Quick Attach Fittings with O-Rings for Remco Pumps



FQ5S
Straight Hose Barb with O-Ring



RM35C-K
Manifold Kit

Part No.	Description
AQ FQ5S-12	3/4" Straight QA x 1/2" Hose Barb Fitting.....
AQ FQ5E-12	3/4" Elbow QA x 1/2" Hose Barb Fitting.....
AQ FQ5S-34	3/4" Straight QA x 3/4" Hose Barb Fitting.....
AQ FQ5E-34	3/4" Elbow QA x 3/4" Hose Barb Fitting.....
AQ RM35C-K	3/4" Quick-Attach Manifold Kit.....