

When You Want the Best Use SnowEx® !

SnowEx® products are the ideal choice for spreading salt and ice melt products for winter maintenance control. Heavy-duty polyethylene hoppers and powder-coated frames protect against corrosion. Powered by 12-volt electric motors. Variable speed controllers. Simple design does not use sprockets, gears or belts. When you want the best, use SnowEx®.

SNOWEX Tailgate Spreaders

Heavy-Duty Tailgate Spreaders for deicing applications. Ideal for the commercial contractor or private operator for applying deicing products to parking lots, driveways, roadways and recreational paths. Single or two stage models. Designed for use with pickup trucks, SUV's, tractors, skid loaders and utility vehicles with variety of mounting kits and options.



SP575X-1 Single Stage Spreader with variable speed spinner control and 2" receiver mount. Designed to apply **bagged rock salt and calcium flakes** (pelletized materials can be applied with GAK020 gate kit). Rated to 5.75 cubic feet (460 lbs.). Spreading width up to 40'. (TLR175 Trailer kit, DRM175 or UTM175 utility vehicle kits and SSH175 Skid steer kit are optional if needed).

SP1075X-1 Single Stage Spreader has all of the features as the SP575X-1 above, but does not include a receiver or mounting kit as many options are available: PMT175 Pivot receiver hitch, RHM175 2" Receiver hitch, TPM275 3-Point hitch and SSH175 Skid steer hitch are all available for this model. Rated 10.75 cubic ft. (860 lbs.). Spreading width up to 40'.



SP1575-1 Two-Stage Spreader with direct drive auger, vibrator and cab mounted control for spinner and auger speeds. Includes 2" receiver / 3-point mount frame. Designed to apply **bagged rock salt, bulk salt, 50/50 sand/salt mix**. (Bagged ice melt products, calcium chloride pellets and calcium flakes can be applied with optional TRK175 control tube). Rated to 5.25 cubic ft. (420 lbs.). Spreading width to 40'.

SP1875-1 Two Stage Spreader has all of the features as the SP1575-1 above, but with more capacity. (TRK185 Control tube is required if bagged ice melt products, calcium chloride or calcium flakes will be applied). Choose from TPM275 3-Point mount, RHT380 and RHT085 2" Receiver mount or PMT Universal pivotmount kits. Rated to 9 cubic ft. (720 lbs.). Spreading width to 40'.



SP1575-1

Part No.	Description	Capacity	Wt.
TZ SP575X-1	One Stage Spreader, 2" Hitch	5.75 cu. ft.	106 lbs.
TZ SP1075X-1	One Stage Spreader, No Hitch	10.75 cu. ft.	141 lbs.
TZ SP1575-1	Two Stage Spreader, 2" Hitch	5.25 cu. ft.	160 lbs.
TZ SP1875-1	Two Stage Spreader, No Hitch	9.0 cu. ft.	180 lbs.
TZ RHT380	2" Receiver Hitch, 1075X/1875.....		84 lbs.
TZ RHT075	Adapter for RHT380 with 1875.....		34 lbs.
TZ PMT175	Pivot Mount Kit, 1075X/1875.....		87 lbs.
TZ DRM175	Drop Kit for SP575X & Utility Vehicles.....		42 lbs.
TZ SSH175	Skid Steer Mount Kit, SP575X.....		80 lbs.
TZ TPM275	3-Point Mount Kit, SP1075/SP1875.....		38 lbs.

SNOWEX Utility Spreaders

These spreaders are the perfect choice for use with small pickups, SUV's, utility vehicles or small tractors. Designed for use with bagged ice melters, calcium chloride pellets and bagged rock salt as noted for each model. All spreaders are standard with 2" receiver hitch and 12-volt control switches. (3-Point, drop utility or trailer mounting kits are also available).

SR210 is the only utility spreader designed with a **wireless on/off** and 2-speed spinner control. Includes high flow auger for use with **bagged rock salt**. Capacity is 3 cubic feet (240 lbs.). Spread width up to 25'.



SP125 is designed for **pelletized ice products** (not rock salt). Electric, on/off spinner switch with manual gate control. Capacity is 3 cubic feet (240 lbs.). Spread width up to 20'. (Optional variable speed control is available).

SP225 is designed for **bagged rock salt**. Electric, on/off spinner switch with manual gate control. Capacity is 3 cubic feet (240 lbs.). Spread width up to 25'. (Optional variable speed control is available).

SP325 is designed for **bagged rock salt**. Cab mounted, on/off variable speed control is included. Manual gate control. Capacity is 3.25 cubic feet (260 lbs.). Comes with fitted hopper cover. Spread width up to 20'.

SP100 is designed for **pelletized ice melt products** (not rock salt). Cab mounted, on/off variable speed control, electric gate control and clear plastic hopper cover are included. Capacity is 3 cubic feet (240 lbs.). Spread width up to 20'.



SR210



Part No.	Description	Capacity	Wt.
TZ SR210	Utility Spreader, Wireless Control	3.00 cu. ft.	68 lbs.
TZ SP125	Utility Spreader, 12V On/Off Switch	3.00 cu. ft.	65 lbs.
TZ SP225	Utility Spreader, 12V On/Off Switch	3.00 cu. ft.	68 lbs.
TZ SP325	Utility Spreader, 12V Variable Speed Control	3.25 cu. ft.	79 lbs.
TZ SP100	Utility Spreader, 12V Variable Speed Control & Gate Control.....	3.00 cu. ft.	75 lbs.
TZ VAR020	Optional Speed Control for SP125/SP225.....		3 lbs.
TZ EXC020	Optional Hopper Cover for SP125/SP225/SR210.....		1 lbs.