


## Parker Mini Ball Valves

**Polypropylene Ball Valves with Push-In Fittings** can be used with a wide variety of plastic tubing. Molded-All-Plastic design is leak-free and corrosion-resistant. Polypropylene bodies with EPDM o-rings offer wide chemical resistance. Bidirectional, full flow design. Ball valves rated from 0° to 225° F. and pressures to 150 PSI. These ball valves meet all FDA and NSF-51 requirements.

### Model VME Angle Valves (Tube x MPT)



Part No.	Tube O.D.	MPT
PA 4VME4	1/4"	1/4"
PA 4VME6	1/4"	3/8"
PA 6VME4	3/8"	1/4"
PA 6VME6	3/8"	3/8"
PA 6VME8	3/8"	1/2"

10% Discount on Packs of 10


### Model VME Angle Valves (MPT x HB)

Part No.	Hose Barb	MPT
PA 4VME4HB	1/4"	1/4"
PA 6VME6HB	3/8"	3/8"

10% Discount on Packs of 10



### Model VFE Angle Valves (Tube x FPT)



Part No.	Tube O.D.	FPT
PA 4VFE4	1/4"	1/4"
PA 4VFE6	1/4"	3/8"
PA 6VFE4	3/8"	1/4"
PA 6VFE6	3/8"	3/8"

10% Discount on Packs of 10

### Model VFE Angle Valves (FPT x HB)

Part No.	Hose Barb	FPT
PA 6VFE4HB	3/8"	1/4"
PA 6VFE6HB	3/8"	3/8"

10% Discount on Packs of 10



### Model VUC Inline Valves (Tube x Tube)




Part No.	Tube O.D.	Tube O.D.
PA 4VUC4	1/4"	1/4"
PA 4VUC6	1/4"	3/8"
PA 6VUC6	3/8"	3/8"

10% Discount on Packs of 10


### Model VUC Inline Valves (Hose x Hose)

Part No.	Hose Barbs
PA 4VUC4HB	1/4"
PA 6VUC6HB	3/8"
PA 8VUC8HB	1/2"

10% Discount on Packs of 10



### Model VUCP Inline Valves (Tube x HB)



Part No.	Hose Barb	Tube O.D.
PA 4VUCPB4	1/4"	1/4"
PA 6VUCPB6	3/8"	3/8"

10% Discount on Packs of 10

### Model VMC Inline Valves (Tube x MPT)




Part No.	Tube O.D.	MPT
PA 4VMC4	1/4"	1/4"
PA 4VMC6	1/4"	3/8"
PA 6VMC4	3/8"	1/4"
PA 6VMC6	3/8"	3/8"

10% Discount on Packs of 10

### Model VMC Inline Valves (Hose x MPT)

Part No.	Hose Barb	MPT
PA 4VMC4HB	1/4"	1/4"
PA 6VMC6HB	3/8"	3/8"

10% Discount on Packs of 10



### Model VFC Inline Valves (Tube x FPT)



Part No.	Tube O.D.	FPT
PA 4VFC4	1/4"	1/4"
PA 4VFC6	3/8"	1/4"
PA 6VFC4	3/8"	1/4"
PA 6VFC6	3/8"	3/8"

10% Discount on Packs of 10

### Model VFC Inline Valves (Hose x FPT)

Part No.	Hose Barb	FPT
PA 4VFC4HB	1/4"	1/4"
PA 6VFC6HB	3/8"	3/8"

10% Discount on Packs of 10



### Model VEU Elbow Union Valves (Tube x Tube)



Part No.	#1	#2
	Tube O.D.	Tube O.D.
PA 4VEU4	1/4"	1/4"
PA 6VEU4	3/8"	1/4"
PA 6VEU6	3/8"	3/8"

10% Discount on Packs of 10

### Push True-Seal™ Check Valves



**Push-to-Connect Check Valves** ensure protection against reverse flow. Can be used with thermoplastic or soft metal tubings. Acetal body and EPDM o-ring are designed for liquids only. Rated for +34° F. to 150° F. and up to 150 PSI. Cracking pressure is 1/3 PSI.

Part No.	Tube	Tube
PA A4VC4	1/4"	1/4"
PA A6VC6	3/8"	3/8"

10% Discount on Packs of 25