

Black EPDM Hose In Reels

EPDM for Ag Chemicals

EPDM tube and cover for most all agricultural products and NH3 applicator lines. EB numbers are packaged on a UPSable reel - 2 piece, 50' minimum. One braid, 200 PSI (2 braid, 250 PSI on 3/4") Temperatures to 150° F. Same as 1B hose (below), but in black. **Cut Lengths Sold in 5' Increments Only.**



Part No.	Color	Hose I.D.	Reel Size Ft.	Hose O.D.	Per Reel Discount	Sold By
Sold Per Foot (Can Be Cut)						
GA 3204EB-1/4	Black	† 1/4"	500'	0.50"	25%	Per Ft.
GA 3204EB-3/8	Black	† 3/8"	500'	0.66"	25%	Per Ft.
GA 3204-1413	Black	1/2"	500'	0.81"	25%	Per Ft.
GA 3204-1425	Black	3/4"	500'	1.11"	25%	Per Ft.
GA 3204-1431	Black	1"	400'	1.40"	25%	Per Ft.
SOLD IN UPSABLE REELS ONLY						
GA 3204EB-1/2	Black	* 1/2"	250'	0.81"	-	Per Ft.
* GA 3204EB-3/4X200	Black	* 3/4"	200'	1.11"	-	Per Ft.
GA 3204EB-1	Black	* 1"	125'	1.40"	-	Per Ft.


* Note: These package sizes are UPSable & Sold In Reels Only. † Also UPSable.

** Note: Possibly 2 pcs in a reel - no less than 50' per pc.



Red/Black ADAPTAFLEX Hose

— Plant Master —



Red EPDM General Purpose Hose for air, water and agricultural chemicals. Same as 3204 above but with red cover, except on 1-1/4" and 1-1/2". Good resistance to weather and abrasion. *These sizes are UPSable packages on reels. Not recommended for oils. For oils use 3205R Gates Premoflex.

Temperature Range: 0 to 150 degrees F.

NUMBER	Size	Braid	Working Press. P.S.I.	Color	WT. PER 100'	Suction In HG
* 1B-3/8x2	3/8"	2	200	Red	14	30
* 1B-1/2x2	1/2"	2	200	Red	20	25
* 1B-5/8x2	5/8"	2	200	Red	23	20
* 1B-3/4x2	3/4"	2	200	Red	30	15
* 1B-1x2	1"	2	200	Red	55	10
6B-2	2"	2	200	Red	128	4
1B-1-1/4x2	1-1/4"	2	250	Black	70	10
1B-1-1/2x2	1-1/2"	2	200	Black	80	10
1B-2x2	2"	2	200	Black	128	4

NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY

* These sizes available in UPSable reels.

Part No.	Color	Hose I.D.	Reel Size Ft.	O.D.	Per Reel Discount	Sold By
Sold Per Foot (Can Be Cut)						
GA 1B-3/8x2	Red	† 3/8"	400'	0.66"	25%	Per Ft.
GA 1B-5/8x2	Red	† 5/8"	250'	0.97"	25%	Per Ft.
GA 3204-1328	Red	1/2"	500'	0.81"	25%	Per Ft.
GA 3204-1346	Red	3/4"	500'	1.11"	25%	Per Ft.
GA 3204-1361	Red	1"	400'	1.40"	25%	Per Ft.
GA 6B-2	Red	2"	100'	2.56"	25%	Per Ft.
GA 1B-1-1/4x2	Black	1-1/4"	200'	1.73"	25%	Per Ft.
GA 1B-1-1/2x2	Black	1-1/2"	200'	1.98"	25%	Per Ft.
GA 1B-2x2	** Black	2"	100'	2.56"	25%	Per Ft.
Sold In UPSABLE Reels Only						
GA 1B-1/2x2	Red	* 1/2"	250'	0.81"	-	Per Ft.
GA 1B-3/4x2	Red	* 3/4"	200'	1.11"	-	Per Ft.
GA 1B-1x2	Red	* 1"	125'	1.40"	-	Per Ft.

* Note: These package sizes are UPSable & Sold In Reels Only. † Also UPSable.

** 2" Black Hose can be branded as Plant Master or Dura Master. 2" Size is Much Stiffer.

* 25% Discount if ordered in Standard Pack Reels. Reel Lengths are Approximate and May Vary. Non Continuous Lengths, May Be Up to 3 lengths Per Reel with No Size Less than 50 Ft.



DURO FLEX Hose — Plant Master —

GATES DUROFLEX HOSE has a red EPDM cover and black tube. A general purpose hose compounded for good flexibility, air, water, abrasions and ozone. B1 Tube is an EPDM mix with proprietary materials to provide some oil resistance for intermittent use. For oil use 3205R Gates Premoflex.



Hose No.	I.D.	Braids	Max. PSI	Vacuum (in./Hg.)	Temp. Range F.	Bend Radius	Wt. 100-Ft.	Approx. Reel Size
3200R-3/8	3/8"	2	250	30	-40-200°	3"	14 lbs.	500'-700'
3200R-1/2	1/2"	2	250	25	-40-200°	5"	19 lbs.	500'-700'
3200R-3/4	3/4"	2	250	15	-40-200°	6"	34 lbs.	500'-700'
3200R-1	1"	2	250	10	-40-200°	8"	54 lbs.	300'-400'
3200R-1-1/2	1-1/2"	2	250	10	-40-200°	12"	79 lbs.	200'

Part No.	Hose I.D.	Hose O.D.	Full Reel Discount
GA 3200R-3/8	3/8"	0.66"	25%
GA 3200R-1/2	1/2"	0.81"	25%
GA 3200R-3/4	3/4"	1.15"	25%
GA 3200R-1	1"	1.47"	25%
GA 3200R-1-1/2*	1-1/2"	1.98"	-

* Sold in Full Reel Only

NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY

Parker General Service Hose

- Good Choice for Air & Water Service
- EPDM Tube & Cover
- Good Resistance to Chemicals, Heat, Sunlight, Ozone & Weathering
- **NOT SUITABLE** for Petroleum Products
- Excellent Kink Resistance
- Rated to 200 PSI
- Temperature Rating: -40° to +212° F



NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY

Parker GST 11 General Purpose Hose is an ideal choice for air and water service as well as being compatible with a wide variety of chemical products including water based agricultural sprays. EPDM tube and cover with textile reinforcement is standard. This hose design has a good resistance to heat, sunlight, ozone and weathering. Not suitable for transfer of petroleum products. Rated to 200 PSI working pressure. Excellent kink resistance. Temperature rating is from -40° to +212° F.

Hose No.	I.D.	Reinf. Spirals	O.D.	Max. Rec. WP	Bend Radius	Wt. 100-Ft.	Reel Size
7093-38	3/8"	2	0.656"	200	3.5	14 lbs.	700'
7093-12	1/2"	2	0.813"	200	4.5	21 lbs.	550'
7093-34	3/4"	2	1.109"	200	6.0	32 lbs.	400'
7093-1	1"	2	1.406"	200	7.0	44 lbs.	300'
7093-112	1-1/2"	2	2.03"	200	10.0	86 lbs.	200'

Part No.	I.D.	O.D.	Max. PSI	* Reel Size
PA 7093-38	3/8"	0.656"	200	700'
PA 7093-12	1/2"	0.813"	200	550'
PA 7093-34	3/4"	1.109"	200	400'
PA 7093-1	1"	1.406"	200	300'
PA 7093-112	1-1/2"	2.03"	200	200'

* 25% Discount if ordered in Standard Pack Reels. Reel Lengths are Approximate and May Vary. Non Continuous Lengths, May Be Up to 3 lengths Per Reel with No Size Less than 50 Ft.



Ultra Lightweight, Ultra Flexible PVC Hose

An excellent general purpose hose for water, air, lubricated air, light chemicals, anti-freeze and some acids. Standard with a blue cover.

- Exceptionally Flexible & Lightweight
- PVC Cover is Non-Marking with Excellent Abrasion & Tear-Resistance
- PVC Tube with Two-Spiral Polyester Yarn for Strength
- Highly Resistant to UV Rays & Ozone
- Non-Conductive & Flame Retardant
- Temperature Range: -15° F. to +150° F.

NOTE: CUT LENGTHS SOLD IN 5' INCREMENTS ONLY



Hose No.	I.D.	Reinf. Spirals	O.D.	Vacuum Rating	Max. PSI	Bend Radius	Wt. 100-Ft.	Reel Size
GPH-38	3/8"	2	0.64"	23	300	1"	12.3 lbs.	500'
GPH-12	1/2"	2	0.80"	17	300	1-1/2"	17.6 lbs.	500'

Part No.	Hose I.D.	Hose O.D.	Full Reel Discount
PA GPH-38	3/8"	0.64"	25%
PA GPH-12	1/2"	0.80"	25%

Please remember there are No Returns on customer specified cut lengths of hose.