



Plunger Pumps

High Flow Models (7 to 100 GPM)



REPAIR SERVICE AVAILABLE


Triplex Plunger Pumps from CAT PUMPS® are designed to deliver smooth, low pulsation flows at a wide variety of pressures and flow rates. Widely used in continuous-duty, high pressure applications including Car/Truck Wash, Industrial Cleaning, Pressure Washing, Reverse Osmosis, Water Misting and many more.

CAT PUMPS® are the "Pumps with Nine Lives". **Standard Features include:** High pressure seals that are lubricated and cooled by the solution being pumped • Oil-bath crankcase • Heat treated valves and seats • Forged brass or stainless steel manifolds • Solid ceramic plungers • Exclusive high pressure seal design • Rated from 140° to 160° F. depending on the model. Seal options up to 180° F. available • Wet ends can be serviced without entering the crankcase • Pumps are rated to 50 micron particles and 5-9 ph. **Note: Mounting rails are not included and must be ordered separately except for 67 and 68 Series).**

High Flow Pumps are rated from 7 to 75 GPM. See previous page for low flow models.

Part No.	GPM	PSI	RPM	Inlet	Outlet	Shaft	Wt.	Mounting Rails Req'd
CC 650	7	3000	1000	3/4"	1/2"	30mm	44 lbs.	30613
CC 5CP6120	7.4/6.0	1200/1600	1750/1400	1/2"	3/8"	20mm	20 lbs.	30660*30611
CC 5CP6180CSS	8	1500	1750	1/2"	3/8"	20mm	20 lbs.	30611
CC 56	8	2500	1210	1/2"	3/8"	20mm	20 lbs.	30660*30611
CC 56HS	8	3000	1760	1/2"	3/8"	24mm	39 lbs.	*30611
CC 7CP6165CS	8	3500	1320	3/4"	1/2"	24mm	31 lbs.	*30613
CC 1560	9	4000	1280	3/4"	1/2"	30mm	63 lbs.	*30613
CC 5CP6190	10	1200	1750	1/2"	3/8"	20mm	22 lbs.	30611
CC 1050	12/10	1800/2200	1150/960	3/4"	1/2"	30mm	44 lbs.	30613
CC 660	10	3000	1430	3/4"	1/2"	30mm	44 lbs.	30613
CC 660.3400†	10	3000	1430	3/4"	1/2"	30mm	44 lbs.	30613
CC 3507	10	5000	915	1-1/2"	3/4"	35mm	152 lbs.	92674
CC 3550	10	6000	940	3/4"	1/2"	35mm	124 lbs.	92674
CC 6810 **	10	10,000	600	1"	1/2"	45mm	377 lbs.	126604
CC 7CP6110	10.5	2000	1725	1/2"	1/2"	24mm	40 lbs.	30613
CC 7CP6110.3400 †	10.5	2000	1750	1/2"	1/2"	24mm	40 lbs.	30613
CC 7CP6170	11	2000	1450	3/4"	3/8"	24mm	30 lbs.	30613
CC 1051**	12	1800	1150	3/4"	1/2"	30mm	44 lbs.	30613
CC 1580	12	3000	1180	3/4"	1/2"	30mm	60 lbs.	30613
CC 1530	15.5	1500	1450	1"	3/4"	30mm	55 lbs.	30613
CC 1730	15.8	1500	1750	1"	3/4"	30mm	55 lbs.	30613
CC 1731**	15.8	1500	1750	1"	3/4"	30mm	55 lbs.	30613
CC 2560	16	3000	1510	1-1/4"	3/4"	30mm	95 lbs.	30614
CC 1540E	18	1200	1100	1"	1-1/4"	45mm	43 lbs.	30613
CC 2510	20	2000	1450	1-1/4"	3/4"	30mm	79 lbs.	30614
CC 2565	20	2500	1450	1-1/4"	3/4"	30mm	95 lbs.	30614
CC 3560	20	4000	1160	1-1/2"	1"	35mm	139 lbs.	92674
CC 3520	25	2000	870	1-1/2"	1"	35mm	139 lbs.	92674
CC 2530	25	1200	1025	1-1/4"	3/4"	30mm	79 lbs.	30614
CC 3570	30	2500	1080	1-1/2"	1"	35mm	139 lbs.	92674
CC 3535	36	1200	800	1-1/2"	1"	35mm	139 lbs.	92674
CC 3531DHS**	36	1200	800	1-1/2"	1"	35mm	139 lbs.	92674
CC 6835	40	3000	625	1-1/2"	1"	45mm	355 lbs.	Included
CC 3545	45	1000	765	1-1/2"	1"	35mm	139 lbs.	92674
CC 6747	48	2000	615	2"	1-1/2"	45mm	335 lbs.	Included
CC 67070	50	2000	850	2"	1-1/4"	45mm	340 lbs.	Included
CC 6760	60	1200	520	2"	1-1/4"	45mm	335 lbs.	Included
CC 6775	75	1200	650	2"	1-1/4"	45mm	335 lbs.	Included
CC 67102	100	1000	680	2-1/2"	2"	45mm	364 lbs.	Included

** Features Stainless Steel Manifolds. † Rated to 200° F., Run Dry Feature.



Portable Toilet Cleaning Units

12 or 24 Volt DC

To increase cleaning effectiveness and shorten cleaning time, many service trucks are now fitted with high-pressure cleaning units. Commonly operating at 500 – 700 psi, this pressure range provides enough cleaning power to effectively sanitize surfaces in a shorter amount of time. Cat Pumps has the products to keep it clean!



1.50 gpm, 700 psi Pump
Model 4D17FK28 - 1hp 12v Motor
Model 4DX30EUI Pump Only