



Walk Behind Spreaders

Walk Behind Spreaders for applying ice melt products for sidewalks and driveways. Available in Granular Broadcast, Granular Drop or Liquid models. Polyethylene hoppers and powder coated or stainless frames for added corrosion resistance.

SP65 Broadcast Spreader is designed for bagged rock salt and calcium chloride products. Rated to 100 lb. capacity. Powder coated frame. Up to 25' spread width.

SP85 Broadcast Spreader is designed for bagged rock salt and calcium chloride products. Rated to 160 lb. capacity. Powder coated or stainless steel frames. Up to 25' spread width.



SP85SS Broadcast Spreader

Broadcast Spreaders

Part No.	Frame	Capacity	Wt.
TZ SP65	Powder Coat	100 lbs.	25 lbs.
TZ SP85	Powder Coat	160 lbs.	42 lbs.
TZ SP85SS	Stainless	160 lbs.	42 lbs.

SD95 Drop Style Spreader is designed for bagged rock salt and bagged ice melt products. Narrow 28" coverage is ideal for sidewalks and areas where overthrow is not desired. Powder coated or stainless frames.



SD95 Drop Spreader



Drop Spreaders

Part No.	Frame	Capacity	Wt.
TZ SD95	Powder Coat	160 lbs.	55 lbs.
TZ SD95SS	Stainless	160 lbs.	55 lbs.

SL80 Liquid Walk Behind Unit. Rated to 1 GPM flow and 12 gallon capacity. 12-Volt rechargeable electric pump. Adjustable boomless nozzle and spray wand allow for optimal coverage. Powder coated or stainless frame. Up to 48" spray coverage.



SL80 Liquid Walk Behind

Liquid Walk Behind

Part No.	Frame	Capacity	Wt.
TZ SL80	Powder Coat	12 Gallon	60 lbs.
TZ SL80SS	Stainless	12 Gallon	60 lbs.



Sidewalk Spreaders

Sidewalk Spreaders are designed for sidewalks, driveways, parking structures and many other deicing applications. Capable of spreading almost any type of rock salt, ice melters and sand/salt mixes. Straight down drop design for control of coverage on **SD Models** and variable rotary coverage on **SP1675**. Gate-free material disbursement, polyethylene hopper, 12-volt sealed transmission, variable speed, digital controller.



SD600

SD600 Drop Pro Spreader is rated to 6 cu. ft. (480 lb.) capacity. **TPR020** 2" receiver mount or **TPD020** utility bed mount must be ordered separately.

SD1400 Drop Pro Spreader is rated to 14 cu. ft. (1120 lbs.) capacity. Standard with 3-point mounting frame.



SD1400 Sidewalk Spreader



Part No.	Capacity	Wt.
TZ SD600 Sidewalk Spreader *	6 cu. ft.	175 lbs.
TZ SD1400 Sidewalk Spreader w/3 Pt. Mt.	14 cu. ft.	375 lbs.
TZ TPR020 2" Receiver Mount, SD600		
TZ TPD020 3 Point Mount Kit, SD600		
TZ UBM175 Utility Vehicle Kit, SD600		

* Requires Mounting Kit as Noted Above.



SP1675 Sidewalk Spreader

SD1675 Precision Pro is a rotary sidewalk spreader with coverage from 4' to 12'. This adjustable spread pattern allows for narrow coverage like walks to wider coverage like roadways. Capacity is 6 cu. ft. (480 lbs.). Features vibrating material flow facilitator.

*Note: 3-Point mount is standard. 2" Receiver (TPR020) or utility bed mount (UBM175) must be ordered separately as required.



Part No.	Capacity	Wt.
TZ SP1675 Sidewalk Spreader *	6 cu. ft.	290 lbs.
TZ TPR020 2" Receiver Mount		
TZ UBM175 Utility Vehicle Mount Kit		
TZ TPD020 3-Point Mount Kit		

* Requires Mounting Kit as Noted Above.

To Deliver the Best Possible Service to Our Customers, Dultmeier Sales Strives to Live Up to A Set of Core Values, One of Which is to Be "Customer Focused"

