

Spraying Systems Wash Down Spray Guns

These popular wash down guns are used in a variety of industries for clean up and disinfecting. Variable spray from solid stream to 50 degree pattern is controlled at the trigger. **Rated to temperatures up to 200° F.** and pressures to 150 PSI. Body is aluminum and is covered by a replaceable **White**, Nitrile rubber grip. Trigger is stainless steel. Available in 10, 16 or 22 GPM units. Inlet port is 1/2" female pipe thread.



TeeJet

Rated to Temperatures up to 200° F.

Part No.	Rating
SS CU1501	10 GPM
SS CU1502	16 GPM
SS CU1503	22 GPM

Wash Down Spray Guns



Maximum Temperatures to 190° F.

Suttner Industrial Spray Guns are an ideal choice for plant or bay washdown. Spray pattern is adjustable. Thick, rubber sheathing protects against heat, cold and impact. Rated to 350 PSI and flows to 27 GPM. **Maximum temperatures to 190° F.** Inlet port is 1/2" FPT. Weight is 28 oz.



Part No.	Rating
NP ST1200 Wash Down Gun, Brass	27 GPM
NP ST1200SS Wash Down Gun, Stainless *	27 GPM

* Food Grade.

Wash Down Spray Gun



Adjustable Pattern Wash Down Gun is rated to 195° F. Flows to 16 GPM and pressures to 350 PSI. Discharge cone is adjustable for wide to narrow patterns. Inlet is 1/2" FPT. Weight is 2.1 lbs.

Part No.	Rating
IP YG1635N Wash Down Gun	16 GPM

Box Type Spray Wands & Extensions

Spray Gun / Extensions Units for replacements on box store pressure washers. Gun extension outlets are 22mm and designed for **AL248** spray lances. Gun inlet is either 3/8" FPT or 22mm to match up to 22mm or 3/8" MPT hose assemblies.




BT105

BT105 Spray wand has 22mm inlet x 22mm extension outlet. Extension is 19" long. Rated to 8 GPM, 3000 PSI and 212° F.



AL12

AL12 Spray wand has 3/8" FPT inlet x 22mm extension outlet. Extension is 19" long. Rated to 8 GPM, 3000 PSI and 140° F.



AL248 & AL248C

AL248 Spray lance is designed with 22mm inlet to match to wands above. Outlet is 1/4" MPT. Length is 24". Rated to 10 GPM, 5000 PSI and 300° F. Zinc construction.

AL248C Spray lance is designed with 22mm inlet to match wands above. Outlet is 1/4" female quick coupler. Length is 24". Rated to 10 GPM, 5000 PSI and 300° F. Zinc construction.

Part No.	Description	Inlet	Outlet
AR BT105	Spray Gun with Extension...	22mm	22mm
AR AL12	Spray Gun with Extension...	3/8" FPT	22mm
AR AL248	24" Lance	22mm	1/4" MPT
AR AL248C	24" Lance	22mm	1/4" QC

Nozzle Protectors

Designed to protect vehicle surfaces from scratching and damage. Nozzles are completely surrounded by protector guards. Different style designs are shown below.

ST007 Nozzle Protectors feature a Soft outer edge to protect surfaces and a Hard Plastic Base for added wear life. Inlet port is 1/4" FPT Stainless steel. Rated to 5,000 PSI and 300° F. Designed for 1/4" MPT nozzles. Overall length is 2".

ST107



Part No.	Inlet	Nozzle Type	Color
NP ST107	1/4" FPT	1/4"	Black/Red



ST004



ST004 Nozzle Protectors feature a two piece design where the tough, plastic outer cover threads on to a plastic base. Zinc-plated, 1/4" FPT inlet fitting is housed in the base. Available for either 1/8" or 1/4" MPT nozzles. Rated to 5,000 PSI and 210° F. Overall length is 2-1/2".

Part No.	Inlet	Nozzle Type	Color
NP ST004-D42	1/4" FPT	1/8" MPT	Black/Gray
NP ST004-D44	1/4" FPT	1/4" MPT	Black/Gray

1830 Nozzle Protectors features a 1/4" FPT plated inlet. Heavy wall, plastic construction is standard. Rated to 5100 PSI and 320° F. Designed for 1/4" MPT nozzles. Overall length is 2".



Part No.	Inlet	Nozzle Type	Color
MV 1830	1/4" FPT	1/4" MPT	Black



ST10
ST15

ST10/ST15 Nozzle Protectors feature a brass, 1/4" FPT inlet and hard plastic upper cover. Designed for any 1/4" wand extensions **including spring type flex extensions.** Overall length is 1-1/4". Rated to 2000.

Part No.	Inlet	Nozzle Type	Color
GS ST10	1/4" FPT	1/8" MPT	Black
GS ST15	1/4" FPT	1/4" MPT	Black

140 Nozzle Protectors are made of a heavy plastic and are held in place by the nozzle and wand. The base acts like a washer to hold both together. Overall Length is 2-1/8". Available in blue, red or black. One-piece design. Also commonly used on triple foam wands.



Part No.	Inlet	Nozzle Type	Color
BC 140	-	1/8" or 1/4" MPT	Blue
BC 140B	-	1/8" or 1/4" MPT	Black
BC 140R	-	1/8" or 1/4" MPT	Red



22002



22005

2200 Series Nozzle Protectors are made of heavy but flexible plastic and are held in place by the nozzle like the 140 series above. Overall length is 2-1/4". Available in blue or black. One-piece design.

Part No.	Inlet	Nozzle Type	Color
GS 22002	-	1/8" or 1/4" MPT	Blue
GS 22005	-	1/8" or 1/4" MPT	Black

Nozzle Protector



26110-PUR Nozzle Protector

1/8MEG or 1/4MEG WashJet Nozzle

Durable and abrasion resistant polyurethane nozzle protectors. Shields the spray surface from damaging contact during use and at shut-off.



CP26110-PUR

Also protects the nozzle & extends wear life. One size fits both 1/8" & 1/4" MEG nozzles up to #20 orifice. Maintains shape and durability from below freezing to 250° F.

Part No.	Description
SS CP26110-PUR	Nozzle Protector

