

E1005 Storage • Poly Cone-Bottom & PCO Tanks



Ace Roto-Mold

A DIVISION OF DEN HARTOG INDUSTRIES, INC.

Slim Line Storage Tanks, 250 Gallons thru 1000 Gallons

Slim Line Storage Tanks are the perfect choice when it is necessary to have chemical storage in narrow installations or placement through existing doors. Constructed of medium-density, polyethylene with UV inhibitors. Translucent white walls allow for level viewing and feature gallonage indicators. Available in 250 to 1,000 gallon capacities. Standard with 16" lids and outlet fittings as noted. 5 year warranty.



SPO400UT & SPO250UT

SPO1000UT & SPO750UT

Part No.	Gallons	W x L x H	Fitting	Wt.
RT SPO130UT	130	56" x 20" x 43"	2"	79 lbs.
RT SPO250UT	250	62" x 29" x 42"	1-1/2"	115 lbs.
RT SPO300UT	300	62" x 29" x 53"	1-1/2"	159 lbs.
RT SPO400UT	400	62" x 29" x 66"	2"	209 lbs.
RT SPO500UT	500	74" x 31" x 70"	2"	223 lbs.
RT SPO750UT	750	82" x 35" x 86"	2"	318 lbs.
RT SP1000UT	1000	40" x 92" x 89"	2"	407 lbs.



Storage Utility Tanks

— Slim Line Style —

Slim Line Storage Tank. Polyethylene tank designed for narrow installations. Standard with polypropylene fitting and EPDM gasket. 18" vented manway lid for easy clean-out. Built-in gallonage indicators are molded into each end of the tank. Rated to a 1.50 Specific Gravity. Color is translucent (off-white).



Part No.	Description	Dimensions
SN 44330-I	300 Gallon Tank, 1-1/4" Outlet Fitting	66"L x 49"H x 29"D
SN 43856-I	400 Gallon Tank, 1-1/4" Outlet Fitting	66"L x 70"H x 29"D
SN 43616-I	500 Gallon Tank, 1-1/4" Outlet Fitting	74"L x 70"H x 29"D
SN 44310-I	750 Gallon Tank, 2" Outlet Fitting	82"L x 85"H x 35"D
SN 44045-I	1000 Gallon Tank, 2" Outlet Fitting	92"L x 89"H x 40"D

Slosh Guard Utility Tanks

50 – 200 Gallons • Flat Bottom



• Used for lawn care, pest control, construction, mobile cleaning, and outdoor recreation • Inverted slosh guard fillwell design to eliminate sloshing and spillage • Premium polyethylene construction with ultra-violet inhibitors for protection against sunlight • Fitting flats located on one side and one end of tank; standard with 1" or 2" fittings end installed (tanks without fittings also available) • Recessed ribs designed to accept optional tie-down straps up to 2" width • Molded-in gallonage markers & 8" threaded lids • Rated for handling liquids up to 12lbs./gal • **3-Year Warranty**



Part No.	Gallons	Bulkhead Fitting	W x L x H	Wt.
RV 43292	50	1"	19" x 38" x 21"	40
RV 43294	100	1"	27" x 42" x 28"	50
RV 43296	150	1"	36" x 48" x 28"	60
RV 43298	200	2"	36" x 48" x 37"	80

Note: Fittings are installed on end of tank.



Ace Roto-Mold

A DIVISION OF DEN HARTOG INDUSTRIES, INC.

Pest Control Operator (PCO) Tanks

Rectangular PCO tanks include many desirable features for a wide variety of applications. 5 year warranty.

- Use for stationary or transportable (*non-D.O.T. regulated*) applications: indoors & outdoors.
- Tanks have a rounded bottom for best liquid drainage and optional 2" deep x wide sump.
- Constructed of medium-density polyethylene with U.V. inhibitors: rated to 14 lbs./gal.
- 300 Gallon tanks include an internal baffle for support & liquid control.
- Securely anchor for use in transport applications; use powder coated steel bands shown.
- Translucent white color is standard; gallonage markers included.
- "Notched" recess at top in 4 places so bands hold tank more securely from sliding.



PCO Tanks

Part No.	Description	Dimensions	Lid	Fitting	Wt.
RT PC035	35 Gallon No Sump	16"x35"x21"H	5"	1"	26 lbs.
RT PC050	50 Gallon No Sump	19"x38"x23"H	8"	1"	27 lbs.
RT PC050S	50 Gallon With Sump	19"x38"x23"H	8"	1"	27 lbs.
RT PC0100	100 Gallon No Sump	30"x38"x29"H	8"	1"	52 lbs.
RT PC0100S	100 Gallon With Sump	30"x38"x29"H	8"	1"	52 lbs.
RT PC0150	150 Gallon No Sump	37"x48"x29"H	12"	1-1/4"	63 lbs.
RT PC0150S	150 Gallon With Sump	37"x48"x29"H	12"	1-1/4"	63 lbs.
RT PC0200	200 Gallon No Sump	37"x48"x38"H	12"	1-1/4"	84 lbs.
RT PC0200S	200 Gallon With Sump	37"x48"x38"H	12"	1-1/4"	84 lbs.
RT PC0300	300 Gallon No Sump	37"x69"x40"H	16"	2"	160 lbs.
RT PC0300S	300 Gallon With Sump	37"x69"x40"H	16"	2"	160 lbs.

Band Pairs (Powder Coated Silver):

Part No.	Description	Dimensions	Wt.
RT PC035SB	*One Pair - 35 Gallon Tank	2" x 50.5"	3 lbs.
RT PC050SB	One Pair - 50 Gallon Tank	2.5" x 57.5"	6 lbs.
RT PC0100SB	One Pair - 100 Gallon Tank	2.5" x 76"	10 lbs.
RT PC0150SB	One Pair - 150 Gallon Tank	3.5" x 82"	15 lbs.
RT PC0200SB	One Pair - 200 Gallon Tank	3.5" x 98"	18 lbs.
RT PC0300SB	One Pair - 300 Gallon Tank	4" x 100"	20 lbs.

* Bands for 35 Gallon Tank are Stainless Steel.

Cone Bottom Storage Tanks with Poly Stands

— 175 - 3000 Gallons —



- Heavy-duty polyethylene with ultra-violet inhibitors for protection against sunlight • Rugged polyethylene stands molded to fit securely to tank – sold as complete unit • Off-set fill opening and self-venting, slosh-proof lid; Sidewall flat for recirculation • Ideal for highly corrosive environments • Top-edge molded-in slots for safe, secure tie down • Molded-in graduated gallonage indicators

White tanks – **3-Year Warranty**

Part No.	Gallons	Cone Slope	Diameter x Height	Bulkhead Fitting	Lid
White Tanks – 12lbs./gal					
RV 60113	175	30°	43" x 49"	2"	16"
RV 62343	300	30°	49" x 61"	2"	16"
RV 62441	310	30°	43" x 72"	2"	8"
RV 40289	500	30°	49" x 87"	2"	16"
RV 40809	750	20°	73" x 67"	2"	16"
RV 40359	1050	20°	73" x 86"	2"	16"
RV 40813	1600	30°	89" x 96"	2"	16"