

DEF "Easy Caddy" Pumping System

For 135 Gallon DEF Tanks



Pumping System Contains:

- 10+ GPM High Flow Dura-Pump™
- Coupler is MicroMatic RPV (Poly)
- 3/4" x 20' DEF Discharge Hose
- 3/4" x 1.5" Suction Hose
- SS Automatic Nozzle
- All Hose Clamps & Fittings Included
- Optional Meter is DEF Dura-Meter™



Part No.	Description
DP 2512-AE	DEF "Easy Caddy" System, 12 Volt, Less Tank, Less Meter
DP 2515-AE	DEF "Easy Caddy" System, 115 Volt Less Tank, Less Meter
DP 2512-AE-135	DEF "Easy Caddy" System, 12 Volt With 135 Gallon Tank, Less Meter
DP 2515-AE-135	DEF "Easy Caddy" System, 115 Volt With 135 Gallon Tank, Less Meter
DP 3000D	1" Dura-Meter for DEF

FILL-RITE DEF/AdBlue® Pump Systems

Features:

- 8 GPM Flow Rate
- Rugged Multi-Diaphragm Technology
- Integral Pulsation Damper
- 30-Minute Duty Cycle
- Self-Priming to 6 Feet
- EPDM Seals
- Stainless Steel Exterior Hardware



Component Details:

Cage Bracket: Stainless steel, hangs on many types of caged totes, high capacity hose bracket up to 20'.
Nozzle Boot: Keeps nozzle clean, removable boot for easy clean-up and multiple secure mounting configurations. **Hose:** 3/4" EPDM x 20' and 5' suction. **Automatic Nozzle, Turbine Meter:** (Some models only). +/- 1% accuracy, 4-digit display: ounces, pints, quarts, liters or gallons, replaceable AA batteries. **Micro Matic™ RPV Coupler** for use with either RSV or RPV 4-key container valve.

	DF120N	DF012N
Flow Rate	8 gpm	
Max. Bypass	38 psi	
Voltage	120V AC	12V DC
Wetted Construction	Nylon, EPDM, Santoprene®, SS	
Duty Cycle	30 Min. ON / 30 Min. OFF	
Compatible Fluids	Water, Diesel Exhaust Fluid	
Connections Kit (included)	(2) 1" BSPP x 3/4" hose barb 90° elbows, (2) 1" BSPP x 3/4" hose barb straight fittings, (4) Worm gear hose clamps	

Part No.	Description
FR DF012-PO	12 Volt DEF Pump ONLY
FR DF012	12 Volt DEF Pump/Meter System with Auto Nozzle & RPV Coupler. For Cage Tanks
FR DF012-LM	Same As Above - Less Meter
FR DF120-PO	120 Volt DEF Pump ONLY
FR DF120	120 Volt DEF Pump/Meter System with Auto Nozzle & RPV Coupler. For Cage Tanks
FR DF120-LM	Same As Above - Less Meter

CT6 Style DEF Transfer Pumps



CT6-DEF

The **CT6 DEF Diaphragm Pump** is a non-UL rated transfer pump. Specifically designed for DEF. 12 volt or 115 volt electric motors with 30-minute duty cycles. Flow rate is 8-10 GPM. EPDM seals.



CT6-DEFE with Micromatic Coupler

2" MPT tank connection and 1" FPT discharge port. 20 ft. cord with battery clamps included on 12 volt models. 20 ft. cord with plug included on 115 volt models.

Part No.	Description	Wt.
SI CT6-DEF	12V DEF Pump ONLY	12 lbs.
SI CT6-DEFA	115 Volt DEF Pump ONLY	12 lbs.
SI CT6-DEFB	12 Volt DEF Pump with Suction Tube & 2" x 2" x 1" Bung Adapter.....	15 lbs.
SI CT6-DEFC	115 Volt DEF Pump with Suction Tube & 2" x 2" x 1" Bung Adapter.....	15 lbs.
SI CT6-DEFD	12 Volt DEF Pump with Micromatic Coupler.....	17 lbs.
SI CT6-DEFE	115 Volt DEF Pump with Micromatic Coupler.....	17 lbs.

DEF Tote Pumping Systems for 275 Gallon DEF Tanks - Top Mount -

DEF Tote Pumping Systems are designed to top mount directly to DEF tanks or drums that have a *Micromatic* adapter/suction tube in the tank.

Kits Include: 12 volt or 115 volt poly DEF pump (see above for pump details) with stainless Micromatic coupler, 3/4" x 12' DEF hose assembly (with SS fitted ends & 1" x 3/4" poly reducer bushing) and 3/4" stainless automatic DEF nozzle.



3/4" Stainless Automatic Nozzle



CT6-DEFE with Micromatic Coupler

Part No.	Description
DU DEFK-12V	12 Volt DEF Pump Kit
DU DEFK-115V	115 Volt DEF Pump Kit