

PVC Union Style Ball Valves

- Import -

PVC Union Valves feature easy installation with hand tighten union nuts that allows for line break down if needed. Full port design means minimum flow restrictions. Mounting pads can accept electric or pneumatic actuators. Socket and threaded ends included to meet plumbing needs. Seat is teflon. O-rings are Viton®. Schedule 80 PVC. 150 Psi W.O.G. Has both Slip and FPT ports.



Part No.	FPT & Slip Ports
JO 210-543	1/2"
JO 210-544	3/4"
JO 210-545	1"
JO 210-546	1-1/4"
JO 210-547	1-1/2"
JO 210-548	2"
JO 210-550	3"
JO 210-551	4"

PVC Ball Valves - Import -

Economical PVC Ball Valves for a wide variety of applications. Corrosion-resistant schedule 80 PVC with EPDM seats and o-rings. Rated to 150 PSI W.O.G. Threaded female ports. NSF approved.

Part No.	FPT Ports
JO 210-203	1/2"
JO 210-204	3/4"
JO 210-205	1"
JO 210-206	1-1/4"
JO 210-207	1-1/2"
JO 210-208	2"
JO 210-210	3"
JO 210-211	4"



Polypropylene Ball Valves

V150 VALVE
Straight thru
1-1/2" pipe size




BANJO Ball Valves are straight thru type in pipe sizes. Precision molded in polypropylene reinforced with fiberglass. Spherically perfect precision ground self-aligning ball moves freely against Teflon seats. Viton® "O" ring stem seal. Teflon self-lubrication stem bushings and seats can not stick or bind. Stainless steel nuts are used with zinc-plated steel bolts. Easily serviced. Maximum operating pressure is 150 PSI up to 2" and 3" is rated to 75 PSI.

Part No.	Valve or Nozzle Type	Diameter	*Std. Pkg.
TK V075	3/4" Full Flow Valve	3/4"	24
TK V100FP	1" Full Flow Valve	1"	24
TK V125	1-1/4" Valve	1"	24
TK V150	1-1/2" Full Flow Valve	1-1/2"	24
TK V200	2" Valve	1-1/2"	24
TK V200FP	2" Full Flow Valve	2"	8
TK V300	3" Valve	2-1/2"	8
TK V300FP	3" Full Flow Valve	3"	6

*5% Discount If Ordered in Standard Package

Brass Gate Valves


Brass Gate Valve with non-rising stem, screwed bonnet, solid wedge disc and full port flow. Up to 200 PSI non-shock cold water, oil or gas lines.



Part No.	FPT Ports	Max. PSI
TW GV-1/2	1/2"	200
TW GV-3/4	3/4"	200
TW GV-1	1"	200
TW GV-1-1/4	1-1/4"	200
TW GV-1-1/2	1-1/2"	150
TW GV-2	2"	150
TW GV-2-1/2	2-1/2"	125
TW GV-3	3"	125
TW GV-4	4"	125

QUANTITY DISCOUNTS AVAILABLE

Stainless FPT Gate Valves



- Investment Cast Stainless Body, 316SS
- Non-Rising Stem
- Solid Wedge Disc; Screwed Bonnet
- PTFE (Teflon) Stem Packing & Seal
- Aluminum Handwheel
- 200 PSI Working Pressure (WOG)
- Maximum Temperature is 350° F.

Part No.	Description
EV SSGV50	1/2" FPT Stainless Gate Valve
EV SSGV75	3/4" FPT Stainless Gate Valve
EV SSGV100	1" FPT Stainless Gate Valve
EV SSGV125	1-1/4" FPT Stainless Gate Valve
EV SSGV150	1-1/2" FPT Stainless Gate Valve
EV SSGV200	2" FPT Stainless Gate Valve
EV SSGV300	3" FPT Stainless Gate Valve



"ECONOMY"

Single Union Poly Ball Valves

- Glass-Filled Polypropylene
- EPDM "O"-Rings
- Full Port
- 100 PSI W.P.

SUV Style - Can Turn Handle Both Ways



Part No.	Ports	Flow Dia.	Std. Pkg.
TK UV050FP	1/2"	1/2"	24
TK UV075FP	3/4"	3/4"	24
TK UV100FP	1"	1"	24
TK MSUV100FP	* 1"	1"	24
TK UV125FP	1-1/4"	1-1/4"	24
TK UV150FP	1-1/2"	1-1/2"	24
TK UV200FP	2"	2"	18

* Male x Male 1" Flanged.

5% Discount on Standard Pkg.

Thermometers



Back Mount



B1B5H

Industrial thermometers for checking temperatures in tanks, plumbing lines, vessels, etc. 304 Stainless Steel welded construction for corrosion resistance to most chemicals. Rustproof, dust proof, leakproof. Extra heavy glass lens.

Available in either back mount or adjustable styles (*back or bottom*). Mounting ports are MPT. Many other stem lengths are available if required. Stem diameter is 1/4".

B1B5H Pocket Thermometer is designed for easy spot checks of temperatures. 1" dial face with 5" probe. Comes with handy pocket case. Range is 0° to 220° F. Stainless construction.

Part No.	Temperature Range:	Dial Face	MPT Port	Mount Type	Stem
ST J701	-40° - 160° F.	2"	1/4"	Back	6"
ST LN250	0° - 250° F.	3"	1/2"	Back	2-1/2"

Viton® is a registered trademark of DuPont Performance Elastomers