



# Super Speedfit® Plumbing Fittings

LARGE QUANTITY DISCOUNTS: LESS 15% For Purchases in Bags of 10 Not Assorted - 20% On 100 Assorted Fittings in Bags of 10 - 30% on 1000 Assorted Fittings in Bags of 10.

## JG Cross


Gray Acetal / Nitrile



Part No.	Tube O.D.	Type	Discount Pkg/10	No Match!
LM CR38	3/8" X4"	Gray	15%	\$ 6.70

## Bulkhead Unions

Gray Acetal / Nitrile • Black/White Poly/EPDM



Part No.	Tube O.D.	Tube O.D.	Type	Discount Pkg/10
LM BU1414	1/4"	1/4"	Gray	15%
LM BU3814	3/8"	1/4"	Gray	15%
LM BU3838	3/8"	3/8"	Gray	15%
LM BU1212	1/2"	1/2"	Gray	15%
LM TU1414	1/4"	1/4"	White	15%
LM TU3838	3/8"	3/8"	White	15%
LM TU1212	1/2"	1/2"	White	15%
LM BUB14	1/4"	1/4"	Black	15%
LM BUB38	3/8"	3/8"	Black	15%

## JG Shut-Off Valves (Tube x Tube)

John Guest Shut-Off Valves are manufactured in white polypropylene or black polypropylene with EPDM seals for chemicals or water, (not for compressed air) or gray acetal with nitrile for use with water and compressed air. Rated to 150 PSI at 70° F.

### Inline Valve, Tube x Tube




Part No.	Tube O.D.	Tube O.D.	Type	Discount Pkg/50
LM PSV5	1/4"	1/4"	White	10%
LM PSV10	3/8"	3/8"	White	10%
LM PSV04	* 3/8"	3/8"	Gray	10%
LM PSV06	* 1/2"	1/2"	Gray	10%
LM BVS14	1/4"	1/4"	Black	10%
LM BVS38	3/8"	3/8"	Black	10%

\* Rated for use with compressed air.

### Inline Valve, Tube x MPT

Poly / EPDM



Part No.	Tube O.D.	MPT	Type	Discount Pkg/50
LM PSV20	1/4"	1/4"	White	10%
LM PSV35	3/8"	3/8"	White	10%

## JG Inline Valve, Female x Tube



Part No.	Tube O.D.	FPT	Type	Discount Pkg/50
LM PSV40	1/4"	1/4"	White	10%
LM PSV55	3/8"	1/4"	White	10%

## Push-Fit Check Valves (Inline Tube x Tube)

Allows flow in only one direction. White or Black Acetal bodies. Liquids only, not for compressed air. Rated to 150psi @65° F. For water or chemicals rated for bodies and O-rings.



Part No.	Tube O.D.	Body & O-ring	Cracking PSI	Discount Pkg/10
LM SCV14	1/4"	White, Buna	1/3 PSI	15%
LM NC2718	1/4"	White, Buna	5 PSI	15%
LM NC2718E	1/4"	Black, Buna	5 PSI	15%
LM SCV38	3/8"	White, Epdm	1/3 PSI	15%
LM SCV12	1/2"	White, Buna	1/3 PSI	15%

## DMfit® Push-Lock Filter/Strainer

Inline Filter/Strainers with push-lock design for hard wall tubing. Plastic construction is rated to 150 PSI and 150° F. 100 Mesh screen is standard. Easy-to-service and clean. Gray acetal/nitrile.



Part No.	Tube O.D.
LM ADMF0404	1/4"
LM ADMF0606	3/8"
LM ADMF0707	1/2"

## Locking Clips

Secures the Collet in its Position



Part No.	Tube O.D.
LM PIC1808R	1/4"
LM PIC1812R	3/8"
LM PIC1816R	1/2"

Secures the collet in its position to prevent an accidental disconnection of the tube. Can be removed if required.

## Push Lock Check Valve



- Buna Seals • 1/2" x 1/2" Acetal Body, Nitrile Seal
- Push Tube Connect



Part No.	Size
LM ACHV0707	1/2" x 1/2"

## Polypropylene Check Valves

Push Lock

- Viton® Seals • 316SS Spring & Ball
- Tube x Tube



Part No.	Tube O.D.	Opening Pressure (PSI)
BU CV1101-P14	1/4"	1.0
BU CV1101-P56	5/16"	1.0
BU CV1101-P38	3/8"	1.0
BU CV1103-P14	1/4"	3.0
BU CV1103-P38	3/8"	3.0

WE APPRECIATE YOUR

# BUSINESS!