



Slosh Guard Utility Tanks

50 – 200 Gallons • Flat Bottom



- Used for lawn care, pest control, construction, mobile cleaning, and outdoor recreation • Inverted slosh guard fillwell design to eliminate sloshing and spillage • Premium polyethylene construction with ultra-violet inhibitors for protection against sunlight • Fitting flats located on one side and one end of tank; standard with 1" or 2" fittings end installed (*tanks without fittings also available*) • Recessed ribs designed to accept optional tie-down straps up to 2" width • Molded-in gallonage markers & 8" threaded lids • Rated for handling liquids up to 12lbs./gal • **3-Year Warranty**



Part No.	Gallons	Bulkhead Fitting	W x L x H	Wt.
RV 43292	50	1"	19" x 38" x 21"	40
RV 43294	100	1"	27" x 42" x 28"	50
RV 43296	150	1"	36" x 48" x 28"	60
RV 43298	200	2"	36" x 48" x 37"	80

Note: Fittings are installed on end of tank.

Freshwater Tank



A **9-Gallon Freshwater Tank** with a hinged lid over a recess in the tank which can be used to store items required by **EPA's Worker Protection Standard (40 CFR170)**.

The tank is designed so it can be mounted on spraying applicators or other equipment involved in the handling and application of pesticides. Tank is a white polyethylene to show level indicators and ensure compliance with FDA regulations. For mounting, 4-5/16" nuts are molded into the tanks side and bottom. Includes 3/4" FPT port for D1050 spigot valve.

Size: 10"W, 14"H, 20"L

Note: Tank should be flushed and refilled on a regular basis.



Part No.	Description
RV 47036	Safety Tank with Storage Compartment
RV 5461R	Screw On Lid for #26676.....

Call Toll Free For Prices

Polyethylene Round Pallet Paks

— Forkliftable —



VT110



VT210

Bottom Outlet Fitting can be added. Rated to 1.7 S.G. (14 lbs/Gallon)

Part No.	Capacity	Lid	Top Outlet	Diameter	Base
RT VT110	110 Gallon	5"	2"	33"	Square
RT VT0210-PP	210 Gallon	5"	2"	41"	Round

Call Toll Free For Prices

40 & 60 Gallon Blow-Molded Poly Tanks

Constructed of blow-molded low density polyethylene with UV inhibitors for economy and lightweight. Both tanks include molded-in legs with black anchor feet, end sump with 3/4" drain cap, 5" lid with lanyard, band locator grooves and 4X10-24 brass inserts for pump mounting, and hose warp "horns". Translucent with gallonage indicators. Rated for 14 lb./gal. liquids. Standard white color (*Yellow available*).



Part No.	Capacity	Lid	Length	Width	Height	Wt.
RT SB40	40 Gallon	5"	36"	24"	19"	17.5 lbs.
RT SB60	60 Gallon	5"	36"	24"	26"	21.0 lbs.
RT 12499	Replacement 5" Lid with Lanyard (Drilled Hole Vent).....					
RT 13696	Replacement 5" Lid with Lanyard (Spring Loaded Vent in Lid).....					

* 30 Gallon Includes Spring Loaded Vent in Lid (RT 13696)

CALL for CURRENT PRICING



Dual Containment Tanks

The **Dual Containment Tank (DCT)** from Snyder Industries is one of their latest product innovations. These double wall containment tanks range from 35 gallon capacity up to 1500 gallon capacity. This product provides end users with a secondary containment solution in one integral space saving unit. While the **Captor Containment System** is Snyder Industries' work horse, the DCT product line is an ideal solution for commercial "Day" tank system requirements.

- **DCT Systems** use bolted double wall flanged fittings (*recommended*) or a bulkhead-style fitting
- All primary tanks come with noted specific gravity while all secondary tanks are made from HDLPE, 1.9 S.G. Rated, Natural resin
- **DCT** sidewall fitting locations are at 0°, 90°, 180°, 270° only – see *CPT systems for more versatility in fitting configurations*



Call for Pricing & Availability On Your Specific Configuration Needs!

Viton® is a registered trademark of DuPont Performance Elastomers