




## Fuel Oil Hose - Fuel Master -

**For Fuel Oil, Diesel, Commercial Gasolines  
Bio-Diesel to B20 & Ethanol to E15**

A Premium Quality Hose for transfer of fuel oils, diesel fuel and commercial gasolines, including E10 and E15 as well as B20 bio-diesel. Flexible to -20° F. High oil resistant tube. Red, non marking cover provides for superior abrasion-resistance. Working pressures to 200 PSI. Sold by the foot (*minimum of 10'*), in bulk lengths or in fitted assemblies as shown. All fitted assemblies are crimped with brass MPT fittings. (*Other fitted lengths available.*)



**NOTE: CUT LENGTHS SOLD  
IN 10' INCREMENTS ONLY**



| Bulk Hose       |                 | I.D.   | O.D.  | Pkg. | Std. Pkg. Discount |
|-----------------|-----------------|--------|-------|------|--------------------|
| Part No.        |                 |        |       |      |                    |
| GA 3221WM-1     | Fuel Hose, Bulk | 1"     | 1.50" | 100' | 25%                |
| GA 3221WM-1-1/4 | Fuel Hose, Bulk | 1-1/4" | 1.75" | 100' | 25%                |
| GA 3221WM-1-1/2 | Fuel Hose, Bulk | 1-1/2" | 2.08" | 100' | 25%                |

**Fitted Assemblies**



| Fitted Hose        |                    | I.D.   | Length           | Wt.     |
|--------------------|--------------------|--------|------------------|---------|
| Part No.           |                    |        |                  |         |
| GA 3221WM-1x25     | Fuel Hose Assembly | 1"     | 25'              | 18 lbs. |
| GA 3221WM-1x30     | Fuel Hose Assembly | 1"     | 30'              | 22 lbs. |
| GA 3221WM-1x35     | Fuel Hose Assembly | 1"     | 35'              | 25 lbs. |
| GA 3221WM-1x50     | Fuel Hose Assembly | 1"     | 50'              | 33 lbs. |
| GA 3221WM-1-1/2x20 | Fuel Hose Assembly | 1-1/2" | 20'              | 23 lbs. |
| GA 3221WM-1-1/2x25 | Fuel Hose Assembly | 1-1/2" | 25'              | 28 lbs. |
| GA 3221WM-1-1/2x35 | Fuel Hose Assembly | 1-1/2" | 35'              | 33 lbs. |
| GA 3221-1X         | Fuel Hose Assembly | 1"     | Specify 0.58/Ft. |         |
| GA 3221-1.5X       | Fuel Hose Assembly | 1.5"   | Specify 0.95/Ft. |         |

## Parker "TITANFLEX"

**Corrugated Ultra Flexible Petroleum Hose**  
For "Constant Contact" • Biofuel Compatible • 1:1 Bend Radius



**TITANFLEX Petroleum®** Hose is designed for petroleum suction and discharge applications where full vacuum, higher working pressures, extreme flexibility and easier handling are required.

**Features:** For constant contact with commercial gasolines, diesel & fuel oils (including Biodiesel & Ethanol) • Extreme Flexibility • Unique non-kinking design • Lightweight, easy to lift • Abrasion, oil & ozone resistant cover. **Maximum Working Pressure** - See chart below. **Temperature Range** is -40° F. to +180° F. **Tube:** Seamless high grade Nitrile. 60% aromatics, Class A RMA. **Cover:** Black corrugated specially compounded Nitrile. **Reinforcement:** Multiple plies of polyester yarn with dual wire helix. Black color standard (*Red available.*)

**NOTE: CUT LENGTHS SOLD  
IN 5' INCREMENTS ONLY**

### SPECIFICATIONS

| TI-NO.       | I.D.   | O.D.     | Bend Radius | Working Press. | Wt. /Ft. | Vacuum Rating |
|--------------|--------|----------|-------------|----------------|----------|---------------|
| SWC609-1-1/2 | 1-1/2" | 2-1/16"  | 1-1/2"      | 250            | .72      | Full          |
| SWC609-2     | 2"     | 2-9/16"  | 2"          | 250            | .92      | Full          |
| SWC609-3     | 3"     | 3-11/16" | 3"          | 200            | 1.66     | Full          |
| SWC609-4     | 4"     | 4-5/8"   | 4"          | 150            | 2.26     | Full          |

| Part No.        | I.D.   | O.D.    | Std. Pkg. | Std. Pkg. DISCOUNT |
|-----------------|--------|---------|-----------|--------------------|
| TI SWC609-1-1/2 | 1-1/2" | 1.50"   | 100'      | 10%                |
| TI SWC609-2     | 2"     | 2.5625" | 100'      | 10%                |
| TI SWC609-3     | 3"     | 3.6875" | 100'      | 10%                |
| TI SWC609-4     | 4"     | 4.625"  | 100'      | 10%                |

**Please remember there are No Returns on customer specified cut lengths of hose.**



## Petroleum Transfer Hose

For "Constant Contact" • Biofuel Compatible • Corrugated

**Fuel Master™ Xtreme™ 150SD MegaFlex** is a premium petroleum hose designed for "constant contact" with gasoline, diesel, biodiesel, bio-diesel blends, ethanol, ethanol blends, and oils. Ideal for tank truck loading, drop hoses, in-plant operations, and oilfield service truck use where a super flexible, maximum kink-resistant fuel transfer hose is required. Larger sizes available - **Call for Details.**



**Tube:** Type C (Nitrile), Black.

**Reinforcement:** Synthetic, high-tensile textile dual helix wire.

**Cover:** Type C2 (Modified Nitrile). Red Corrugated with Black Stripe, 150 PSI W.P.

**Temperature Range:** -30° F. to 180° F.

| Part No.         | I.D.   | O.D.  | Bend Radius | 100' Std. Pkg. Disc. |
|------------------|--------|-------|-------------|----------------------|
| GA 4688AC-1      | * 1"   | 1.50" | 1"          | 25%                  |
| GA 4688AC-1-1/2† | 1-1/2" | 2.02" | 1.50"       | 25%                  |
| GA 4688AC-2      | 2"     | 2.45" | 2"          | 25%                  |
| GA 4688AC-3      | * 3"   | 3.44" | 3"          | 25%                  |


\* Must Order Full Reel of 100'. † Min Buy of 400Ft.

— 250 PSI —



## Oil Resistant Hose

— Plant Master —



**GATES Premoflex** is a premium grade spiral hose with maximum resistance to air, water, petroleum and lubricating oils to 212° F. Recommended for gasoline, kerosene and fuel oil transfer to 120° F. Approved for breathing apparatus with air supplied respirators. Black nitrile tube, Red C2 nitrile cover. Working pressure to 250 PSI. Continuous service from -40° to 212° F. Best selection for air hoses with oil lubricators. Available in coupled assemblies with male/female ends. For field install use with GLX crimp couplings through 1". Hose and couplings are correct for OSHA required air hoses.

**Sold In 5' Increments Only.**


| Part No.     | I.D. | O.D.  | *Reel Size | Wt. Per Ft. | *Std. Pkg. Discount |
|--------------|------|-------|------------|-------------|---------------------|
| GA 3205R-1/2 | 1/2" | .85"  | 500'       | .22 lbs.    | 25%                 |
| GA 3205R-3/4 | 3/4" | 1.15" | 500'       | .36 lbs.    | 25%                 |
| GA 3205R-1   | 1"   | 1.47" | 400'       | .54 lbs.    | 25%                 |

\* Available in 1/4" - 1-1/2"



## Kuriyama Tank Truck Drop Hose

**NDH TigerDrop Hose** is designed for gravity drop fuel transfer. Standard with nitrile rubber tube, fabric reinforced cover and embedded grounding wire. Lightweight, yet greater flexibility than conventional rubber drop hoses. Rated for use with gasoline, diesel, ethanol and biodiesel. Rigid helix design protects from wear. Phthalate-Free. Rated from -10° to +150° F. Vacuum rating 27 hg. **5 ft. minimum purchase.** Made in the USA.



| Part No.  | I.D. | O.D.  | Rating @ 68° F. | Bend Radius | *Std. Pkg. |
|-----------|------|-------|-----------------|-------------|------------|
| TF NDH202 | 2"   | 2.60" | 75 PSI          | 5"          | 100'       |
| TF NDH303 | 3"   | 3.69" | 70 PSI          | 6"          | 100'       |
| TF NDH404 | 4"   | 4.78" | 65 PSI          | 8"          | 100'       |

## TigerFlex Polyurethane HD Oil Suction Hose



OV Series

**OV TigerFlex Hose** handles fuels and oils. Excellent resistance to gasoline, diesel, ethanol to E30 and B100 Biodiesel. Solid polyurethane tube "see through" construction, service temperatures to -40° F. to +150° F. PVC helix, smooth outer cover for ease in banding end connections. Full vacuum at 68° F.

**SOLD IN FULL 100 FT.  
PACKAGES ONLY**



| Part No. | I.D.   | O.D.  | PSI@ 68° F. | Lb./Ft. | Std. Pkg. | Std. Pkg. Discount |
|----------|--------|-------|-------------|---------|-----------|--------------------|
| TF OV100 | 1"     | 1.26" | 85          | .23     | 100       | 25%                |
| TF OV125 | 1-1/4" | 1.49" | 85          | .30     | 100       | 25%                |
| TF OV150 | 1-1/2" | 1.76" | 70          | .35     | 100       | 25%                |
| TF OV200 | 2"     | 2.32" | 65          | .55     | 100       | 25%                |