

TeeJet TTI TwinJet® Twin Flat Induction Tips

The TTI60 TeeJet Air Induction Twin Flat Spray Tip provides extremely large droplets for maximum drift control along with the improved coverage of a twin spray. The single piece tip and cap design allows for fast, easy installation and, unlike some other twin sprays, has a very compact size. The TTI60 is ideal for the application of systemic, post-emerge herbicides.



Features:

- TTI60 produces two 110° wide angle, flat spray patterns for uniform coverage in broadcast applications.
- 60° Angle between leading & trailing patterns for increased canopy penetration & leaf coverage.
- All in one molded nozzle and Quick TeeJet® cap design provides automatic spray alignment.
- Extremely large drift resistant droplets are produced through the use of a venturi air aspirator.
- Provides excellent drift control & produces minimal driftable fines - less than 1.5%.
- Acetal construction for excellent chemical & wear resistance.
- Removable pre-orifice allows for disassembly & cleaning.
- Suggested spray pressure range of 20-100 PSI.
- All sizes suitable with PWM Spray Systems.



Part No. SS TTI6011002VP thru 11006VP Twin Flat Air Induction Tips/Caps/Gaskets Pkg. 25

10% Quantity Discount on 50+ Of One Size

TIPO	PSI	DROP SIZE	CAPACITY ONE NOZZLE IN GPM	CAPACITY ONE NOZZLE IN OZ./MIN.	20°							
					GPA							
					4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH
TTI60-11002VP (50)	20	UC	0.14	18	10.4	8.3	6.9	5.2	4.2	3.5	2.8	2.1
	30	UC	0.17	22	12.6	10.1	8.4	6.3	5.0	4.2	3.4	2.5
	40	XC	0.20	26	14.9	11.9	9.9	7.4	5.9	5.0	4.0	3.0
	50	XC	0.22	29	16.3	13.1	10.9	8.2	6.5	5.4	4.4	3.3
	60	VC	0.24	31	17.8	14.3	11.9	8.9	7.1	5.9	4.8	3.6
TTI60-110025VP (50)	20	UC	0.18	23	13.4	10.7	8.9	6.7	5.3	4.5	3.6	2.7
	30	UC	0.22	28	16.3	13.1	10.9	8.2	6.5	5.4	4.4	3.3
	40	XC	0.25	32	18.6	14.9	12.4	9.3	7.4	6.2	5.0	3.7
	50	VC	0.28	36	21	16.6	13.9	10.4	8.3	6.9	5.5	4.2
	60	VC	0.31	40	23	18.4	15.3	11.5	9.2	7.7	6.1	4.6
TTI60-11003VP (50)	20	UC	0.21	27	15.6	12.5	10.4	7.8	6.2	5.2	4.2	3.1
	30	UC	0.26	33	19.3	15.4	12.9	9.7	7.7	6.4	5.1	3.9
	40	UC	0.30	38	22	17.8	14.9	11.1	8.9	7.4	5.9	4.5
	50	UC	0.34	44	25	20	16.8	12.6	10.1	8.4	6.7	5.0
	60	XC	0.37	47	27	22	18.3	13.7	11.0	9.2	7.3	5.5
TTI60-11004VP (50)	20	UC	0.28	36	21	16.6	13.9	10.4	8.3	6.9	5.5	4.2
	30	UC	0.35	45	26	21	17.3	13.0	10.4	8.7	6.9	5.2
	40	UC	0.40	51	30	24	19.8	14.9	11.9	9.9	7.9	5.9
	50	UC	0.45	58	33	27	22	16.7	13.4	11.1	8.9	6.7
	60	XC	0.49	63	36	29	24	18.2	14.6	12.1	9.7	7.3
TTI60-11005VP (50)	20	UC	0.35	45	26	21	17.3	13.0	10.4	8.7	6.9	5.2
	30	UC	0.42	55	32	26	21	16.0	12.8	10.6	8.5	6.4
	40	UC	0.50	64	37	30	25	18.6	14.9	12.4	9.9	7.4
	50	UC	0.56	72	42	33	28	21	16.6	13.9	11.1	8.3
	60	XC	0.61	78	45	36	30	23	18.3	15.1	12.1	9.1
TTI60-11006VP (50)	20	UC	0.42	54	31	25	21	15.6	12.5	10.4	8.3	6.2
	30	UC	0.52	67	39	31	26	19.3	15.4	12.9	10.3	7.7
	40	UC	0.60	77	45	36	30	22	17.8	14.9	11.9	8.9
	50	UC	0.67	86	50	40	33	25	19.9	16.6	13.3	9.9
	60	XC	0.73	93	54	43	36	27	22	18.1	14.5	10.8
TTI60-11008VP (50)	20	UC	0.57	73	42	34	28	21	16.9	14.1	11.3	8.5
	30	UC	0.69	88	51	41	34	26	20	17.1	13.7	10.2
	40	UC	0.80	102	59	48	40	30	24	19.8	15.8	11.9
	50	UC	0.89	114	66	53	44	33	26	22	17.6	13.2
	60	UC	0.98	125	73	58	49	36	29	24	19.4	14.6

M = Medium C = Coarse VC = Very Coarse XC = Extremely Coarse UC = Ultra Coarse

Off-Center Flat Spray Tips - for Smaller Capacities -



TeeJet Off-Center Flat Spray Tips are commonly installed in double or single swivel nozzle bodies. Because these bodies are adjustable for angular position, a wide spray swath is easily obtained.

Part No. Description
 SS OC02 thru OC16 Brass Off-Center Tip
 SS OCSS02 thru OCSS16 Stainless Off-Center Tip.....



TIPO	PSI	Capacity 1 Nozzle in GPM	"W" in inches	"H" = 18"			
				GPA			
				3 mph	4 mph	5 mph	6 mph
OC-02	30	0.17	68	5.0	3.7	3.0	2.5
	40	0.20	70	5.7	4.2	3.4	2.8
	60	0.24	72	6.6	5.0	4.0	3.3
OC-03	30	0.26	77	6.7	5.0	4.0	3.3
	40	0.30	80	7.4	5.6	4.5	3.7
	60	0.37	82	8.9	6.7	5.4	4.5
OC-04	30	0.35	91	7.6	5.7	4.6	3.8
	40	0.40	93	8.5	6.4	5.1	4.3
	60	0.49	94	10.3	7.7	6.2	5.2
OC-06	30	0.52	99	10.4	7.8	6.2	5.2
	40	0.60	101	11.8	8.8	7.1	5.9
	60	0.73	102	14.2	10.6	8.5	7.1
OC-08	30	0.69	100	13.7	10.2	8.2	6.8
	40	0.80	102	15.5	11.6	9.3	7.8
	60	0.98	104	18.7	14.0	11.2	9.3
OC-12	30	1.04	102	20	15.1	12.1	10.1
	40	1.20	104	23	17.1	13.7	11.4
	60	1.47	105	28	21	16.6	13.9
OC-16	30	1.39	132	21	15.6	12.5	10.4
	40	1.60	138	23	17.2	13.8	11.5
	60	1.96	143	27	20	16.3	13.6