


KZ VALVE ZIPVALVES

A more durable and reliable option than solenoid or plunger valves, the motorized ZIPValve is designed with extreme precision in mind. The 1/4" and 3/8" 2-way, standard-port nylon (*stainless steel available*) valves feature NEMA 6P/IP67 rated waterproof EH8 series actuators and stainless steel balls for prolonged life. Instantaneous On/Off control with LED indication in a compact valve design allows you to place the valve in the optimal position to provide the best possible liquid or air control. Available in 12 and 24 VDC with an open-to-close time of 0.2 seconds. Individual row control not a problem! Valves designed with either Deutsch receptacles. **Power supply cables required and sold separately.**



NPZB28-1CEBS-D01



S2C28-1CEBS-D01



1/4" ZIPVALVE 2-way ball valves available with 1/4" and 3/8" dual O-ring push-to-connect fittings with a max PSI of 150 PSI at 70° F or 1/4" MPT fittings with a maximum PSI of 300 @ 70° F. They have a flow rate of 3.2 GPM (@5 PSI drop).

3/8" ZIPVALVE 2-way ball valves available with 1/2" dual O-ring push-to-connect and/or QD fork fitting connections. They have a flow rate of 11.2 GPM (@5 PSI drop) and a maximum PSI of 150 @ 70° F. 3/8" Stainless steel valves include 3/8" FPT ends and a maximum PSI of 600. Valves come standard with positive at close feedback.



Mounting Brackets Shown are Not Included

Part No.	Port Size/ Type	Valve Size / Type	Connector	Volts
KZ NPZB28-1CEBS-D01	3/8" Push-Connect	1/4" Nylon	Deutsch	12/24
KZ NAZC28-1CEBS-D01	Male QD	3/8" Nylon	Deutsch	12/24
KZ NQZC28-1CEBS-D01	1/2" Push-Connect	3/8" Nylon	Deutsch	12/24
KZ S2C28-1CEBS-D01	3/8" FPT	3/8" Stainless	Deutsch	12/24
KZ 398-0276	Power Cable for Deutsch Zip Valves, 18" Long			
KZ 511-0154	Bottom Mount Bracket Kit			
KZ 511-0156	Nylon Base Mount Bracket Kit			

*Note: All Valves/Actuators are On-Off with 0.2 Second Close. * Valve features M12 with (1) Connector Dust Capped.*

KZ VALVE TX2 Series

KZVALVE TX2 Series electric 1/2" ball valves offer exceptional precision flow control in a lightweight, compact design. The innovative design enables both stand-alone and manifold applications for the most versatile valve configuration options yet. The 1/2" full-port polypropylene valves are available in 2- and 3-way options, and feature 1" Banjo flange (M100) and/or male QD end connections. Available in 12-volt On/Off or regulating models with 0.5 second close times. Mounting bosses molded into the valve body reduces mounting time and provides long-lasting, consistent performance. Waterproof EH7 nylon actuators rated NEMA 6P. Valve manifolds available in 1 to 5 valve sections. Rated to 150 maximum PSI at 70° F. *Single valve with actuator weighs only 20 ounces. Valve fittings sold separately!*



C2D37-10DK0-P01



Part No.	Port Size/ Type	Valve Size / Type	On-Off or Regulating
KZ C2D37-10DK0-P01	1" Flanged *	2-Way Ball Valve	On-Off
KZ H2D37-10DK0-P01	QD	2-Way Ball Valve	On-Off
KZ 21CA7-10DK0-P31	1" Flange x QD *	3-Way Single Valve Manifold	On-Off
KZ 10DK0-P01	—	EH7 Actuator, 2-Way	On-Off
KZ 10DK0-P31	—	EH7 Actuator, 3-Way	On-Off
KZ 511-0156	TX Series Mounting Bracket Kit		

Note: All Valves/Actuators Operate at 12VDC with 0.5 Second Close. Fittings Sold Separately.

** Flanged Models Comparable to Banjo M100 Series Manifold Flanges.*

KZ VALVE TX2 & ZIPVALVE Fitting Kits & Adapters

We offer a wide selection of TX2 & ZIPVALVE fitting kits - from 90° and straight hose barbs, to FPT hairpin fittings and flanged connectors - designed for countless plumbing solutions. Give us a call with your unique needs!



Part No.	Description
KZ 511-0010	Fitting Kit, 1/2" QD End Cap
KZ 511-0012	Fitting Kit, 3/4" Straight Hose Barb x QD
KZ 511-0014	Fitting Kit, 3/4" 90° Hose Barb x QD
KZ 511-0016	Fitting Kit, 3/4" FPT x QD
KZ 511-0019	Fitting Kit, 1/2" FPT x QD
KZ 511-0023	Fitting Kit, 1/2" QD Manifold Tee
KZ 106-0018	Quick Release Hairpin Only
KZ 398-0507	ZIP Harness, Deutsch to WeatherPak Tower ...