

To Connect
Push tubing into fitting



Pull on the tube to check that it is secure. Test the system before use.



To Disconnect
Make sure that the system is depressurized, then push the collet square against the fitting. With the collet held in this position, the tube can be removed.

John Guest® Cross
Gray Acetal Nitrile



Part No.	Tube O.D.	Type	Discount Pkg/10
LM CR38	3/8" x 4"	Gray	15%

John Guest® Bulkhead Unions
Gray Acetal Nitrile • Black/White Poly EPDM

Part No.	Tube O.D.	Tube O.D.	Type	Discount Pkg/10
LM BU1414	1/4"	1/4"	Gray	15%
LM BU3814	3/8"	1/4"	Gray	15%
LM BU3838	3/8"	3/8"	Gray	15%
LM BU1212	1/2"	1/2"	Gray	15%
LM TU1414	1/4"	1/4"	White	15%
LM TU3838	3/8"	3/8"	White	15%
LM TU1212	1/2"	1/2"	White	15%
LM BUB14	1/4"	1/4"	Black	15%
LM BUB38	3/8"	3/8"	Black	15%

DMfit® Push-Lock Filter/Strainer

Inline Filter/Strainers with push-lock design for hard wall tubing. Plastic construction is rated to 150 PSI and 150° F. 100 Mesh screen is standard. Easy-to-service and clean. Grey acetal nitrile.



Part No.	Tube O.D.
LM ADMF0404	1/4"
LM ADMF0606	3/8"
LM ADMF0707	1/2"

Locking Clips



John Guest®

Secures the Collet in its Position

Secures the collet in its position to prevent an accidental disconnection of the tube. Can be removed if required.

Part No.	TUBE O.D.
LM PIC1808R	1/4"
LM PIC1812R	3/8"
LM PIC1816R	1/2"
LM ICLT/2	Collet Release Tool

John Guest® Tubing Cutter

TSNIP Tubing Cutter. Handy for cutting tubing square without burrs. Can be used for up to 1/2" O.D. tubing. Just pinch & rotate to cut.



TSNIP



Part No.	Tube O.D.
LM TSNIP	Tubing Cutter.....

John Guest® John Guest Service Kits

Service and Repair Kits from John Guest are a great way to have the most popular Push-Lok fittings ready-to-use. Assorted combinations of connectors, tees, elbows, unions and other fittings in 1/4" through 1/2" sizes. All kits include a handy tube cutter and sturdy carry case that allows for ease of storage and transportation. For chemicals, solutions or water compatible with material and O-Rings as shown. All kit fittings are rated to 150 PSI at 70° F. or 60 PSI at 140° F. **Note:** Black and White kit fittings are not suitable for compressed air.

Kits Come In 3 Different Styles:

Black Polypropylene with UV stabilizers and EPDM O-Rings, 1/4", 3/8", 1/2". 101 Piece assortment.

White Polypropylene with EPDM O-Rings, 1/4", 3/8", 1/2". 92 Piece assortment.

Gray Acetal fittings with Nitrile O-Ring, 1/4", 5/16", 3/8", 1/2". 92 Piece assortment.



Part No.	Fitting Type	Kit Size	Net Ea.
LM ISRKE	Black Polypropylene	101 Pcs. + Case	\$ 249.00
LM ISRK	White Polypropylene	92 Pcs. + Case	275.00
LM IRSKA	Grey Acetal	92 Pcs. + Case	322.00

2-Way Dividers


Gray Acetal Nitrile, White Black Poly EPDM



Part No.	Tube O.D.	Type	Discount Pkg/10
LM DV14	1/4"	Gray	15%
LM DV38	3/8"	Gray	15%
LM DV38P	3/8"	White	15%
LM DV12	1/2"	Gray	15%
LM BV14	1/4"	Black	15%

3-Way Reducer Dividers

Gray Acetal Nitrile
White Poly EPDM



Part No.	(1) O.D.	(3) Outlet	Type	Discount Pkg/10
LM TD38	3/8"	1/4"	White	15%
LM TD12	1/2"	3/8"	Gray	15%




Unequal Divider

Poly / EPDM

Part No.	(1) Tube O.D.	(2) Tube O.D.	Type	Discount Pkg/10
LM UD3814	3/8"	1/4"	White	15%

U-Bend

Gray Acetal Nitrile



Part No.	Tube O.D.	Type	Discount Pkg/10
LM UB12	1/2"	Gray	15%
LM UB38	3/8"	Gray	15%