

FESTO Push-To-Connect Fittings

FESTO Push-To-Connect Fittings are top quality and highly reliable. While most products are fixed, there are some offerings that have a bearing system which allows for free rotation or swivel functionality. Rated to 145 PSI. High-alloy stainless steel retaining claws. Housing material is nickel-plated brass. Tubing seal is NBR (*nitrile buna*). MPT ends come standard with coating to ensure good thread connection. Releasing ring material is POM (*polymer*). * **More Sizes Available and Ask About Quantity Discounts.**

Straight Fixed Connector



Part No.	Description
FO 533270	1/8" MPT x 1/8" Tube
FO 533276	1/4" MPT x 1/4" Tube
FO 533281	3/8" MPT x 3/8" Tube

90° Elbow Swivel Connector

Part No.	Description
FO 153966	1/8" MPT x 1/4" Tube
FO 153967	1/4" MPT x 1/4" Tube
FO 153971	3/8" MPT x 3/8" Tube.....



Straight Swivel Connector



Part No.	Description
FO 153954	1/8" MPT x 1/4" Tube
FO 153955	1/4" MPT x 1/4" Tube
FO 153959	3/8" MPT x 3/8" Tube

Fixed Tee Connector



Part No.	Description
FO 533308	1/8" MPT x 1/8" Tube x 1/8" Tube
FO 573068	1/8" MPT x 1/4" Tube x 1/4" Tube
FO 533314	1/4" MPT x 1/4" Tube x 1/4" Tube

Fixed Wye Connector Tube X Tube X MPT



Part No.	Description
FO 564694	1/4" MPT x 1/4" Tube x 1/4" Tube
FO 564696	1/4" MPT x 3/8" Tube x 3/8" Tube
FO 564697	1/4" MPT x 1/2" Tube x 1/2" Tube
FO 564698	3/8" MPT x 1/4" Tube x 1/4" Tube
FO 564701	3/8" MPT x 3/8" Tube x 3/8" Tube
FO 564702	3/8" MPT x 1/2" Tube x 1/2" Tube
FO 564705	1/2" MPT x 1/2" Tube x 1/2" Tube

Unfastening Tool / Fork

Unfastening Tool / Fork from *FESTO*. This tool allows an end user to easily disengage the teeth lock on push-to-connect fittings. Sized for metric tubing 4 – 10. For use with imperial sizes a drill press can be used to widen diameter.



Part No.	Description
FO 158419	Unfastening Fork/Tool ...

ZRS Tube / Pipe Cutter



ZRS Tube / Pipe Cutter from *FESTO*. This high-quality tube/pipe cutter is ergonomically designed to help improve efficiency when cutting small diameter pipe or tubing. Maximum diameter is .788" (20mm). The ZRS tool is ideal for cutting plastic and nitrile rubber. It uses a small textile insert. Not suitable for metal casing. Integrated safety catch to prevent unwanted opening.

Part No.	Description
FO 7658	Tube Cutter, ZRS.....
FO 218606	Spare Blades, ZRS, 10 Pack...



Fixed Wye Connector



Part No.	Description
FO 564774	1/4" Tube x 1/4" Tube x 1/4" Tube
FO 564776	3/8" Tube x 3/8" Tube x 3/8" Tube
FO 564777	1/2" Tube x 1/2" Tube x 1/2" Tube

SERVICE & REPAIRS

Did you know?

We can service almost every brand of pump we sell in our catalog.

Call us at **1-800-228-9666** (Omaha, NE) for a quote!

