

AG-LITE Water Hoses

AG-LITE Water Hoses are the strongest, lightest, most flexible rubber water hoses made. Ideal for a wide variety of washdown applications.

- 40% Lighter than standard rubber hoses
- 5/8", 3/4" and 1" sizes
- Plated Brass, 3/4" garden hose fittings
- Bend Restrictors for reduced bend stress
- Handles hot water to 212° F.
- Flexible down to -50° F.
- Covers are Ozone, Abrasion and Kink resistant
- 100% Rubber construction
- High strength, polyester reinforced braid
- Rated to 150 PSI working, 500 PSI burst pressure
- Industry Leading 10-Year Limited Warranty.



Garden Hose Fittings



AG-LITE

Part No.	ID/Length	Flow @ 35 PSI	** Std. Pack	Wt.
RX BS5806	* 5/8" x 6'	10 GPM	5	1.0 lbs.
RX BS5815	* 5/8" x 15'	10 GPM	4	2.7 lbs.
RX BS5825	5/8" x 25'	10 GPM	4	4 lbs.
RX BS5850	5/8" x 50'	10 GPM	4	7 lbs.
RX BS58100	5/8" x 100'	10 GPM	2	13 lbs.
RX BS58150	5/8" x 150'	10 GPM	-	19 lbs.
RX BS3406	* 3/4" x 6'	11 GPM	5	1.3 lbs.
RX BS3415	* 3/4" x 15'	11 GPM	6	3 lbs.
RX BS3450	3/4" x 50'	11 GPM	3	8 lbs.
RX BS34100	3/4" x 100'	11 GPM	-	15 lbs.
RX BS34150	3/4" x 150'	11 GPM	34	8 lbs.
RX B50NE15	* 1" x 15'	20 GPM	4	4 lbs.
RX B50NE50	1" x 50'	20 GPM	2	9 lbs.
RX B50NE100	1" x 100'	20 GPM	-	17 lbs.


* These sizes are ideal as feed hoses to reels or pumps.

** 5% discount for orders in standard packs.

AG-LITE Portable Water Reels

Lightest, Strongest & Most Flexible

Spring Rewind Reel and Water Hose Combinations. Great for a variety of wash down applications. Rated to 150 PSI working, 500 PSI burst pressure and 212° F. Corrosion-resistant, 18-Gauge powder-coated steel or stainless steel construction. Heavy-duty spring, 12 point ratchet and specialized internal system reduces vibration and extends spring life. Best in class, 100% rubber water hoses, are the lightest, strongest and most flexible water hoses available.



All reels are complete with 5/8" or 3/4" x 50' hoses with 3/4" garden hose fittings, 6' feeder hose, 4-way rollers, hose stop and adjustable spray nozzle. Complete and ready to use. Can be mounted to floor, ceiling or walls. 2-year warranty.

Part No.	Hose	Construction	Wt.
RX BSWR5850	5/8" x 50'	Powder-Coated Steel	45 lbs.
RX BSWR3450	3/4" x 50'	Powder-coated steel	48 lbs.

Contractor Duty Garden Hoses

Premium-grade, washdown garden hoses. Rubber construction. Abrasion, Ozone and kink resistant. Extreme flexibility even at low temperatures. Chrome-plated brass GHT garden hose fittings and bend restrictor protectors on each end. Available in 50ft and 100ft lengths. Rated to 150 PSI working, 500 PSI burst pressure. Rated to 180° F.



Part No.	Size	GPM @ 65 PSI	Wt.
EV PGH50	5/8" x 50ft	11.90	9 lbs.
EV PGH100	5/8" x 100ft	11.90	17 lbs.
EV CWH50	3/4" x 50ft	17.10	18 lbs.
EV CWH100	3/4" x 100ft	17.10	35 lbs.

13808 Industrial Road
Omaha, NE 68137
1-800-228-9666 • 1-402-333-1444
FAX: 1-402-333-5546

email: dultmeier@dultmeier.com
website: dultmeier.com



601 West 76th St.
Daveport, IA 52806
1-800-553-6975 • 1-563-386-0930
FAX: 1-563-386-5448

WE APPRECIATE YOUR

BUSINESS!

Please remember there are No Returns on customer specified cut lengths of hose.



@Dultmeier Sales



FOLLOW US!



@dultmeier

