

## Air Hose Reels

**Spring rewind air hose/reel packages** from *BluBird*. **Standard Blue** or **Oilshield Yellow** hoses are 30% lighter than traditional air hoses yet still rated to 300 PSI. Ozone, abrasion and kink-resistant design. Rated from -50° F to +190° F.

**Single Arm** reels are a good choice for shops or garages with permanent mounting.

**Dual Arm** reels can be used for the same applications but are a better choice for vehicles or trailer use where added vibrations exist.



### Blue Standard Air Hoses

Part No.	Hose	Arm	Wt.
RX BBR3850	Blue 3/8" x 50ft	Single	30 lbs
RX BBR1250	Blue 1/2" x 50ft	Single	35 lbs
RX BBRDA38100	Blue 3/8" x 100ft	Dual	54 lbs
RX BBRDA12100	Blue 1/2" x 100ft	Dual	81 lbs

### Yellow OilShield Air Hoses

Part No.	Hose	Arm	Wt.
RX OSRHD3850	Yellow 3/8" x 50ft	Single	30 lbs
RX OSRHD1250	Yellow 1/2" x 50ft	Single	35 lbs
RX OSRDA38100	Yellow 3/8" x 100ft	Dual	55 lbs
RX OSRDA12100	Yellow 1/2" x 100ft	Dual	81 lbs

## Hose Reel Swivel Mount Brackets

**Universal Hose Reel Swivel** fit most *BluBird* spring wind reels or other reels with 4-hole brackets. These brackets can be easily mounted to walls or ceilings. Heavy-duty, powder-coated steel construction.

**HRS** series is single arm reels, 180 degree travel.

**HRSDA** series is for dual arm reels, 140 degree travel.



Part No.	Wt.
RX HRS180 Swivel bracket for single arm reels	5.5 lbs
RX HRSDA3812 Swivel bracket for dual arm reels	7.5 lbs

## Fleet Tire Inflator Kit

**Fleet Tire Inflator Kit** is a great item to carry in your tractor/trailer units. Glad Hand adapter is designed to fit your existing air line from the cab to the trailer. Allows for a quick air source to fill flat or low tires on the road. Kits include 3/8" x 50ft air hose, Universal Glad Hand adapter, Dual foot chuck inflator and Carry bag for easy storage. Hose is rated to 300 PSI and from -50° F to +190° F.



Part No.	Wt.
RX BBFLT3850 Fleet Edition Tire Inflator Kit	10 lbs.

**\*5% Discount for box of 4 kits**



## Oil Resistant Air Hoses

**Oilshield Air Hoses** are 100% Nitrile rubber construction and have a Class A oil resistant rating. 30% lighter weight than traditional air hoses but with added flexibility and strength. The perfect choice where hoses come in contact with oil, diesel, gasoline and cleaning agents. Unique cover will even stand up to welding splatter and grinding sparks.

Ozone resistant, Flame and spark resistant, Abrasion resistant, Kink Resistant. Standard with bend restrictors and 3/8"mpt solid brass fittings with 1/4" reducers for most any application. Rated to 300psi and -30° F to +180° F.

### 3 YEAR WARRANTY



Part No.	Size	*Std Pack	Wt.
RX OS3835	3/8" x 35'	5	3 lbs.
RX OS3850	3/8" x 50'	4	5.5 lbs.
RX OS38100	3/8" x 100'	3	11 lbs.
RX OS1250	1/2" x 50'	4	7 lbs.
RX OS12100	1/2" x 100'	2	14 lbs.

**\*5% Discount for Orders in Standard Packs**

## Jack Hammer Air Hose Assemblies

**Jack Hammer Air Hose Assemblies.** Fitted with crimped steel, universal air twist connect fittings. General applications include air supply for air compressors and air tools – including jack hammers. The cover is made from EPDM to resist ozone, heat, and cracking while in service. Red EPDM Cover.

### FEATURES:

- **Oil Resistance:** Class C minimal oil mist
- EPDM Cover/Tube
- **Reinforcement:** Spiral Polyester Yarn
- 50ft Box Packages
- **Temperature Rating:** -40°F to 200°F
- **Pressure Rating:** 300PSI working pressure
- Universal Air Connection Fittings

Part No.	Wt.
TF RJCR-3/4X50	3/4" x 50' Red, EPDM Jack Hammer Hose Assembly

