

## wilo® Wilo Centrifugal Pump Units



The NL-HE end-suction centrifugal pump line from Wilo features a stout pump with solid efficiency ratings across the product line. The NL-HE line is available from 2" X 1-1/4" (5" Impeller) up to 8" X 6" (16" Impeller) Pump casings. Cathaphoretic electro coating of all cast iron components help increase the pump lifespan. The coating process helps to fight against rust and corrosion. Pumps are fitted with a single mechanical seal (Viton®-FKM Carbon/Silicone Carbide).

These 4-pole 1750RPM motor driven pump units are designed to transfer heavier fluids like liquid fertilizer. Pump units for water transfer are also available in EPDM fitted options. Dultmeier Sales is available for consultation on pump sizing for other solution transfer – Please call for details. All units come baseplate mounted and are ready for installation. Pump end only available.

- Flanged Suction/Discharge Ports
- 316SS Impelle
- Improved Hydraulic Design
- High Corrosion Resistance
- Long Service Life
- High-Efficiency
- Viton®-FKM Carbon/Silicone Carbide Mechanical Seals
- Viton®-FKM Housing Oring



Part No.	Flanged Ports	GPM Max Flow	Max S.G	HP	Wt. Lbs.
DU NLHE4X3-20	4 x 3	500 GPM	1.33	20	500
DU NLHE5X4-20	5 x 4	1000 GPM	1.47	20	650
DU NLHE5X4-25	5 x 4	700 GPM	1.46	25	700
DU NLHE6X5-25	6 x 5	1000 GPM	1.58	25	730
DU NLHE6X5-40	6 x 5	900 GPM	1.38	40	850
DU NLHE6X5-75*	6 x 5	1400 GPM	1.0	75	1000
DU NLHE8X6-75	8 x 6	1600 GPM	1.47	75	1250

WO 3395790 Viton®-FKM Carbon-Silicon Carbide Mechanical Seal, NL-HE Pump  
 WO 2036574 Viton®-FKM Housing Gasket, 8IN Pump Housings  
 WO 2152020 Viton®-FKM Housing Gasket, 10IN Pump Housings  
 WO 2056470 Viton®-FKM Housing Gasket, 12IN Pump Housings

\* Sized for Water

## SERVICE & REPAIRS

*Did you know?*

We can service almost every brand of pump we sell in our catalog.

Call us at **1-800-228-9666** (Omaha, NE) for a quote!



## wilo® Wilo NL-HE Pump End Only

The NL-HE end-suction centrifugal pump line from Wilo features a stout pump with solid efficiency ratings across the product line. The NL-HE line is available from 2" X 1-1/4" (5" Impeller) up to 8" X 6" (16" Impeller) Pump casings. Cathaphoretic electro coating of all cast iron components help increase the pump lifespan. The coating process helps to fight against rust and corrosion. Pumps are fitted with a single mechanical seal (Viton®-FKM Carbon/Silicone Carbide). EPDM-fitted options are available – Call for Details. These pumps are designed to be long coupled to 4-pole (1750RPM) electric motors. Other options available within the NL-HE line for 2-pole (3500RPM) electric motors – Call for Details

- Flanged Suction/Discharge Ports
- 316SS Impeller
- Improved Hydraulic Design
- High Corrosion Resistance
- Long Service Life
- High-Efficiency
- Viton®-FKM Carbon/Silicone Carbide Mechanical Seals
- Viton®-FKM Housing Oring



### PUMPS ONLY—RUN AT 1750RPM

Part No.	Flanged Ports	Flow @ 25PSI*	Impeller	Wt. Lbs.
WO NL-HE5X4X8.11-V	5 x 4	750 GPM	8.11"	170
WO NL-HE5X4X9.38-V	5 x 4	950 GPM	9.38"	190
WO NL-HE6X5X7.90-V	6 x 5	770 GPM	7.90"	235
WO NL-HE6X5X10.12-V	6 x 5	1900 GPM	10.12"	245
WO NL-HE6X5X12.75-V	6 x 5	2350 GPM	12.75"	265
WO NLHE8X6X10.98-V	8 x 6	2700 GPM	10.98"	415

WO 3395790 Viton®-FKM Carbon-Silicon Carbide Mechanical Seal, NL-HE Pumps  
 WO 2036574 Viton®-FKM Housing Gasket, 8IN Pump Housings  
 WO 2152020 Viton®-FKM Housing Gasket, 10IN Pump Housings  
 WO 2056470 Viton®-FKM Housing Gasket, 12IN Pump Housings

\* Flow Rates Based on Water (1.0 SG) at 70° F.

### Visit our office in Omaha, Nebraska



13808 Industrial Road • Omaha, NE 68137

1-800-228-9666 • 1-402-333-1444 • FAX: 1-402-333-5546

### Visit our office in Davenport, Iowa



601 West 76th St. • Davenport, IA 52806

1-800-553-6975 • 1-563-386-0930 • FAX: 1-563-386-5448

email: [dultmeier@dultmeier.com](mailto:dultmeier@dultmeier.com) • website: [dultmeier.com](http://dultmeier.com)

WE APPRECIATE YOUR

# BUSINESS!

Viton® is a registered trademark of DuPont Performance Elastomers