

## Keystone 990 Series Split Body Wafer Butterfly Valves



150 PSI W.P. Rating  
75 PSI Deadhead

Thin disc, resilient seat, split body (*two piece*) design allows for easy field replacement of seat & disc/stem. One-piece thin profile disc/stem (*316SS*) results in maximum flow rates, lowest pressure drops (*high CV*) and best control capabilities. Suitable for installation between ANSI Class 125/150 flanges. Wafer style cast iron bodies (*stainless and lug style also available*). Replaceable EPDM seats standard (*Buna & PTFE lined available*). **Not for Vacuum.**

### Keystone

Valve Size	2"	2-1/2"	3"	4"	6"	8"
*GPM Flow	267	451	693	1,314	2,790	5,208

\*Flow rates for water at 1 PSI drop.

Part No.	Size	Wt.
KE 990-20	2"	6 lbs.
KE 990-25	2-1/2"	8 lbs.
KE 990-30	3"	9 lbs.
KE 990-40	4"	11 lbs.
KE 990-50	5"	16 lbs.
KE 990-60	6"	18 lbs.
KE 990-80	8"	30 lbs.

**CALL FOR PRICING**

## +GF+ Wafer Butterfly Valves (PVC)

**Features**  
**A Double Eccentric Valve**  
**Design for Significantly Less Wear**



+GF+

**567 Wafer Style Butterfly Valves** from *GEORGE FISCHER* feature a double eccentric valve design for significantly less wear and 50% less torque required to open or close. Locking lever handles are shown, but gear handles and air or pneumatic actuators are available.

**Applications Include:** Chemical processing, water treatment, food and beverage, mining, HVAC and more. Multiple construction options and seals are shown to meet most any need.

All valves are bi-directional with adjustment increments of 5 degrees. Compatible with ANSI 150, DIN and JIS bolt patterns. Rated for vacuum service. 2" through 8" shown, but up to 12" sizes are available. All valves are tested and certified bubble tight. Lug style valves also available.

PVC Butterfly Valves are available with EPDM or Viton® seals. Rated to 150 PSI @ 80° F. or up to 140° F. @ 30 PSI. NSF 61 rated.

Part No.	Size	Valve	Seal	Wt.
GF 567W-PVE2	2"	PVC	EPDM	2 lbs.
GF 567W-PVE3	3"	PVC	EPDM	2.5 lbs.
GF 567W-PVE4	4"	PVC	EPDM	4 lbs.
GF 567W-PVE6	6"	PVC	EPDM	8 lbs.
GF 567W-PVE8	8"	PVC	EPDM	12 lbs.
GF 567W-PV2V	2"	PVC	Viton®	2 lbs.
GF 567W-PV3V	3"	PVC	Viton®	2.5 lbs.
GF 567W-PV4V	4"	PVC	Viton®	4 lbs.
GF 567W-PV6V	6"	PVC	Viton®	8 lbs.
GF 567W-PV8V	8"	PVC	Viton®	12 lbs.



600A-6



## Butterfly Valves

These **Butterfly Valves** feature precision-machined parts to assure years of dependable operation. Standard replaceable seat is EPDM, the 316 Stainless Steel discs are machined and polished to assure leak tight shut-off while providing maximum seat life. Pressure rated to 200 PSI. Standard with locking handle and notched top plate.

**Stem:** 316 Stainless Steel     **Body:** Ductile Iron  
**Disc:** 316 Stainless Steel     **Seat:** EPDM Replaceable

Part No.	Size	Wt.
CL 200A-2	2"	8 lbs.
CL 300A-3	3"	12 lbs.
CL 400A-4	4"	16 lbs.
CL 600A-6	6"	23 lbs.

**NOTE:** The EPDM seats used in these valves are not suitable for use with Diesel Fuel.



## Pneumatic Rotary Actuators

These air actuators mount directly to 2" through 6" Centerline Valves. Double Acting, aluminum body with 1/4" FPT air connections.

**Note:** You Need to Order Centerline Valve Separately.

Shown with Centerline Valve that must be ordered separately - or see below for Package



Part No.	Size	Wt.
CL CD23	2" - 3"	6 lbs.
CL CD6	4"	8 lbs.
CL CD50	6"	13 lbs.

## Centerline Air Actuated Valves

Includes *Centerline* valves above **with** *Centerline* double-acting air actuators installed on valve.



Part No.	Size	Wt.
CL 300A-3AA	3" Valve with Actuator.....	
CL 400A-4AA	4" Valve with Actuator .....	

Viton® is a registered trademark of DuPont Performance Elastomers

## dultmeier.COM

- Shop and Order On-Line 24 Hours a Day, 7 Days a Week!
- Large Inventories of Over 2.2 Million Total Items!
- View Current Pricing!
- Web Specials and Bargain Corner!
- Know Your Part Numbers? Use the Web Quick Order Page!
- Hundreds of Parts List Schematics (*and more to come!*)
- Technical Library packed with information!
- See New Items not Shown in Our Printed Catalogs!
- Track Your Order Status and History!
- Secure Site for Safe On-Line Ordering.