



Piranha Sewer Hose

Piranha Sewer Hoses are constructed to provide rugged and reliable service under the most severe conditions found in high pressure sewer cleaning. All hoses feature a yellow Olefin tube with single or double braid reinforcement. Urethane covers are color coded to WASTEC specifications and provide exceptional cut, abrasion and fungus resistance. Rated for -40° to 150° F. (*190° F. on some sizes). Available in a wide variety of lengths and styles to meet your needs. All assemblies are standard with Male NPT hose ends matched to the hose size shown. (Other lengths and hose ends are available on request).



SP Orange Hoses are rated to 2500 PSI. Single, high tensile braid reinforcement with orange cover. Available in 3/4", 1" and 1-1/4" I.D. sizes.

Part No.	Color	I.D.	O.D.	Max.PSI	Length	Wt.
TF SP12-400	Orange	3/4"	1.180"	2500	400'	114 lbs.
TF SP12-500	Orange	3/4"	1.180"	2500	500'	142 lbs.
TF SP12-600	Orange	3/4"	1.180"	2500	600'	170 lbs.
TF SP16-400	Orange	1"	1.460"	2500	400'	162 lbs.
TF SP16-500	Orange	1"	1.460"	2500	500'	202 lbs.
TF SP16-600	Orange	1"	1.460"	2500	600'	242 lbs.
TF SP20-400	Orange	1-1/4"	1.800"	2500	400'	238 lbs.
TF SP20-500	Orange	1-1/4"	1.800"	2500	500'	297 lbs.
TF SP20-600	Orange	1-1/4"	1.800"	2500	600'	356 lbs.



LLBU 1/2" & HPBU 3/4' & 1" Blue Hoses are rated to 3000 PSI. Double, high tensile braid reinforcement with blue cover. Available in 1/2", 3/4", 1" I.D. sizes. * (Rated to 190° F. on 1/2").

Part No.	Color	I.D.	O.D.	Max.PSI	Length	Wt.
TF HP10-200	Blue	1/2"	0.83"	3000 *	200'	32 lbs.
TF HP10-300	Blue	1/2"	0.83"	3000 *	300'	48 lbs.
TF HP10-400	Blue	1/2"	0.83"	3000 *	400'	65 lbs.
TF HP10-500	Blue	1/2"	0.83"	3000 *	500'	81 lbs.
TF HP10-600	Blue	1/2"	0.83"	3000 *	600'	97 lbs.
TF HP12-400	Blue	3/4"	1.180"	3000	400'	117 lbs.
TF HP12-500	Blue	3/4"	1.180"	3000	500'	146 lbs.
TF HP12-600	Blue	3/4"	1.180"	3000	600'	175 lbs.
TF HP16-400	Blue	1"	1.480"	3000	400'	165 lbs.
TF HP16-500	Blue	1"	1.480"	3000	500'	207 lbs.
TF HP16-600	Blue	1"	1.480"	3000	600'	248 lbs.



LLGR Green Hoses are rated to 4000 PSI. Double, high tensile braid reinforcement with green cover. Available in 1/4", 3/8" and 1/2" I.D. sizes. * (Rated to 190° F.).

Part No.	Color	I.D.	O.D.	Max.PSI	Length	Wt.
TF LL4-100	Green	1/4"	0.830"	4000*	100'	6 lbs.
TF LL4-200	Green	1/4"	0.830"	4000*	200'	12 lbs.
TF LL4-300	Green	1/4"	0.830"	4000*	300'	18 lbs.
TF LL6-100	Green	3/8"	0.830"	4000*	100'	11 lbs.
TF LL6-200	Green	3/8"	0.830"	4000*	200'	22 lbs.
TF LL6-300	Green	3/8"	0.830"	4000*	300'	33 lbs.
TF LL8-300	Green	1/2"	0.830"	4000*	300'	48 lbs.
TF LL8-400	Green	1/2"	0.830"	4000*	400'	65 lbs.
TF LL8-500	Green	1/2"	0.830"	4000*	500'	81 lbs.
TF LL8-600	Green	1/2"	0.830"	4000*	600'	97 lbs.



LLRD Red Hoses are rated to 5000 PSI. Single Aramid braid reinforcement with red cover. Available in 1/2" I.D. size. * (Rated to 160° F.).

Part No.	Color	I.D.	O.D.	Max.PSI	Length	Wt.
TF LL85-400	Red	1/2"	0.800"	5000*	400'	53 lbs.
TF LL85-500	Red	1/2"	0.800"	5000*	500'	66 lbs.
TF LL85-600	Red	1/2"	0.800"	5000*	600'	79 lbs.

Portable Jetter Reel & Hose Unit

Simply Attach to Your Jetter or Pressure Washer

Compact and Easy-To-Use Jetter Reel includes 100' of 1/4" jetter hose, hand carry reel, inlet shut-off valve, laser jetting nozzle and inlet quick connect fitting. Rated to 3000 PSI. Simply attach to your jetter or pressure washer.




Part No.	Hose	Max. PSI	Wt.
DU PT100R	1/4" x 100'	3,000	35 lbs.

AG-LITE Portable Water Reels

Lightest, Strongest & Most Flexible

Spring Rewind Reel and Water Hose Combinations. Great for a variety of wash down applications. Rated to 150 PSI working, 500 PSI burst pressure and 212° F. Corrosion-resistant, 18-Gauge powder-coated steel or stainless steel construction. Heavy-duty spring, 12 point ratchet and specialized internal system reduces vibration and extends spring life. Best in class, 100% rubber water hoses, are the lightest, strongest and most flexible water hoses available.



All reels are complete with 5/8" or 3/4" x 50' hoses with 3/4" garden hose fittings, 6' feeder hose, 4-way rollers, hose stop and adjustable spray nozzle. Complete and ready to use. Can be mounted to floor, ceiling or walls. 2-year warranty.

Part No.	Hose	Construction	Wt.
RX BSWR5850	5/8" x 50'	Powder-Coated Steel	45 lbs.
RX BSWRSS5850	5/8" x 50'	Stainless steel	45 lbs.
RX BSWR3450	3/4" x 50'	Powder-coated steel	48 lbs

AG-LITE Portable Water Reel

Heavy-Duty Hose Reel features tubular steel frame with powder-coated finish. Holds up to 400' of 5/8" or 250' of 3/4" ID hose (not included).

Features: include 6ft feed hose, 10" flat free tires, 3/4" garden hose inlet and outlet fittings, Non-slip handle, Storage basket.



Part No.	AG-LITE
RX HRC01	Portable Hose Reel