

Jurop Power Packs

Jurop Jurop Power Paks - Engine Driven -

Engine Driven Jurop Pumps featuring Vacuum and Pressure capabilities. All units are pre assembled and ready-to-install on your truck or tank.
Standard Features Include: Electric start *Honda* or *Kohler* gas engines • Powder-coated, steel baseplate and belt guards • Pulleys and belts • 12-Volt battery • Pressure relief valve • Vacuum relief valve • Vacuum/Pressure gauge • Changeover valves for Pressure or Vacuum • Swivel elbows.



PM260VP1



PM23VP1

Part No.	Pump	CFM	Engine	Base
DU PM23VP1	PN23	90	8 HP, <i>Honda</i>	Painted
DU PM58VP1	PN58	229	13 HP, <i>Honda</i>	Painted
DU PM84VP1	PN84	318	20 HP, <i>Kohler</i>	Painted
DU PM260VP1	R260	364	25 HP, <i>Kohler</i>	Painted



Jurop Jurop Power Paks - Gear Box Driven -

Jurop Pumps with Gear Box Drive. For Vacuum and Pressure. All units are pre-assembled and ready for hookup.

Juro-Paks Feature: Pump • Gear box • Secondary filter • Final filter • Pressure relief valve • Vacuum relief valve • Gear box aligning bracket • Pressure/Vacuum gauge • Swivel fittings (*No muffler included*).

Razor-Paks Feature: Pump • Muffler • Gear box • Secondary filter • Final filter • Pressure relief valve • Vacuum relief valve • Gear box aligning bracket • Pressure/Vacuum gauge • Swivel fittings.



RP260



JP260

Part No.	Pump	CFM	Ports
DU JP23	Juropak PN23	92	2"
DU JP33	Juropak PN33	127	2"
DU JP58	Juropak PN58	230	3"
DU JP84	Juropak PN84	317	3"
DU JP260	Juropak R260	363	3"
DU JP420	Juropak LC420	420	3", 4"
DU RP84	Razorpak PN84	317	3"
DU RP260	Razorpak R260	363	3"
DU RP420	Razorpak LC420	420	3", 4"


PRO-VAC Liquid Waste Pumpout Station

Conde ProVac is an Industrial Liquid Waste Pumping System is ideal for grease trap pump-out and remote, tough-to-get to jobs. Extremely quiet yet pumps up to 120 gallons per minute. Built-in exhaust deodorizer keeps odor at a minimum. Simple switch design easily changes from vac-up to pump-out. Easy to maneuver, easy to maintain and built to last.

Standard Features: Heavy-duty, aluminum construction • 35CFM *Conde* pump • Easy access controls • 24" Width fits through any door • 45" Height fits into standard cargo doors • Hand parking brake • Exhaust deodorizer • Retractable cord reel • Hose rack and tool holder • 2" x 10' Hose with wand • 6" Cleanouts • Heavy-duty wheels and casters.

SPECIFICATIONS:

- 1.5 HP/110 Volt Motor Draws 13.4 Amps, Works On Any 15 Amp Service
- 24" Wide x 45" High x 50" Long
- Operating Vacuum, 16" hg.
- Operating Pressure, 5 PSI
- Tank Volume, 52 Gallons
- Air Volume, 35 CFM
- 25' Power Cord
- Weight is 250 lbs.



Part No.	Wt.
CO LWUNP60A ProVac PumpOut System	250 lbs.

