E3268 Rotary & Manhole Cleaners • Tank Cleaner

Rotary Tank Nozzle


Self-Rotating Tank Cleaning Nozzle. Designed for cleaning interior surfaces of tanks, drums, barrels, pipe or tubing. (4) Spinning nozzles travel in an orbital axis for complete coverage. Stainless steel construction, built in strainer, teflon seals and EPDM o-rings are standard. Rated from 5-21 GPM and from 400 to 2000 PSI.

Models are available for fixed rigid pipe mounting or non-rigid hose mounting. Rotation speed is 10-16 RPM. Temperatures to 195° F. Inlet is 3/4". Length is 10-1/2". Minimum tank opening is 7-1/2". (**Note:** Must specify flow rate, pressure, diameter to be cleaned and if any chemicals will be used).

Part No. Mo

Mount Wt. Rigid 11 lbs





Unique Rotary Cleaners are designed to fit 16" or 24" manhole openings. Two-arm cleaners feature debris shield and safety cage. All stainless steel construction. Rated to 2500 PSI. Inlet swivel is 1"

debris shield and safety cage. All stainless steel construction. Rated to 2500 PSI. Inlet swivel is 1" FPT. Designed for (4) 1/8" MPT, (zero or 5 degree) spray nozzles which are not included and should be matched to your pump system. Dual protection plate. 250° F.

 Part No.
 Size
 Max. Flow
 Wt.

 MM 81928
 16"
 50 GPM
 12 lbs.

 MM 81923
 20"
 50 GPM
 15 lbs.



ì

mosmatic,


Manhole

Cleaners

swiss quality







High Pressure Rotary Cleaners for cleaning, restoration and service of manholes, lift stations and other long vertical drops. Stainless steel construction. Rated to 25 GPM, 2500 PSI and 250° F. Inlet is 1/2° FPT. Designed for (2) 1/8" MPT, zero or 5 degree nozzles matched to your pump output (Nozzles are sold separately, call for details). Standing with (1) protection plate. Available in a variety of diameters to meet your needs.



Cina	14/4
Size	<u>Wt.</u>
12" Diameter	8.1 lbs.
16" Diameter	8.0 lbs.
20" Diameter	11.7 lbs.
24" Diameter	14.0 lbs.
32" Diameter	17.0 lbs.
	16" Diameter 20" Diameter 24" Diameter






Rotary Cleaners

An ideal accessory for use with hot or cold water pressure washers. Can be used to clean tanks, ducts, vents, portable toilets, pipe runs and many more. Easily mounted to rigid lance or high pressure hose.

high pressure hose.
Corrosion-resistant, stainless
and plated brass construction with selflubricated bearings and carbide swivels.

Adjustable 2 or 3 nozzle design is perfect for 360 degree cleaning. (1/8" nozzles are not included and must be matched to your system). Rated to 4000 PSI and 250° F. Inlet is 3/8" FPT. (1/4" also available in all sizes).





81556 or

81756

Adjustable Nozzle Bars



No. 81925 Rotary Wand Assembly is a complete wand/rotary cleaner for Portable Toilet Cleanup. Features trigger wand, hose swivel, 40" lance, 6"3 nozzle adjustable cleaning head with 1502 nozzles. Works well for IBC shuttle tote cleanout.

Part No.	Diameter	Nozzle Type	Wt.
MM 81506	3"	2	1.1 lbs.
MM 81526	6"	2	2.2 lbs.
MM 81556	12"	2	2.8 lbs.
MM 81566	16"	2	3.3 lbs.
MM 81586	24"	2	4.0 lbs.
MM 81706	3"	3	1.1 lbs.
MM 81726	6"	3	2.2 lbs.
MM 81756	12"	3	2.8 lbs.
MM 81766	16"	3	3.3 lbs.
MM 81786	24"	3	4.0 lbs.

CURRENT PRICING

CALL

for

MM 81925 TRL Cleaning Lance w/ 6" Cleaning Head (3) nozzles



Tank Cleaner



Mosmatic Tank Cleaner is an excellent solution for complete and consistent cleaning inside tanks and containers. Water pressure driven, the stainless steel Tank Cleaner achieves 360° automated or manual internal cleaning without the need for post-processing.

A unique feature of the Mosmatic Tank Cleaner is the infinitely adjustable rotation speed. Simply loosen a single screw to set the perfect adjustment for different pump capacities and cleaning requirements. Mosmatic stabilizer nozzles (sold separately) allow for enhanced distance cleaning in large diameter tanks.

Available in 45° and 20° drive angles. 1/2" NPTF Inlet. Rated to 2900 PSI and 250° Max Temp.

* Requires (2) EG nozzles that are sold separately and must be matched to your flow and pressure requirements.

Part No.	Drive Angle	Flow Rate	Diameter	Weight
MM 101622	45°	4-13 GPM	6.50"	15 lbs.
MM 101672	20°	13-26 GPM	7 83"	15 lbs

Nozzle Holder, 1/4" NPTF

CALL for CURRENT PRICING

MM 906135